
Standard Commutative Rings

Release 10.5.rc0

The Sage Development Team

Nov 16, 2024

CONTENTS

| | | |
|----------|----------------------------|------------|
| 1 | Integers | 1 |
| 2 | Rationals | 153 |
| 3 | Indices and Tables | 195 |
| | Python Module Index | 197 |
| | Index | 199 |

INTEGERS

1.1 Ring \mathbf{Z} of Integers

The `IntegerRing_class` represents the ring \mathbf{Z} of (arbitrary precision) integers. Each integer is an instance of `Integer`, which is defined in a Pyrex extension module that wraps GMP integers (the `mpz_t` type in GMP).

```
sage: Z = IntegerRing(); Z
Integer Ring
sage: Z.characteristic()
0
sage: Z.is_field()
False
```

There is a unique instance of the `integer ring`. To create an `Integer`, coerce either a Python int, long, or a string. Various other types will also coerce to the integers, when it makes sense.

```
sage: a = Z(1234); a
1234
sage: b = Z(5678); b
5678
sage: type(a)
<class 'sage.rings.integer.Integer'>
sage: a + b
6912
sage: Z('94803849083985934859834583945394')
94803849083985934859834583945394
```

`sage.rings.integer_ring.IntegerRing()`

Return the integer ring.

EXAMPLES:

```
sage: IntegerRing()
Integer Ring
sage: ZZ==IntegerRing()
True
```

`class sage.rings.integer_ring.IntegerRing_class`

Bases: `CommutativeRing`

The ring of integers.

In order to introduce the ring \mathbf{Z} of integers, we illustrate creation, calling a few functions, and working with its elements.

```
sage: Z = IntegerRing(); Z
Integer Ring
sage: Z.characteristic()
0
sage: Z.is_field()
False
sage: Z.category()
Join of Category of Dedekind domains
and Category of euclidean domains
and Category of noetherian rings
and Category of infinite enumerated sets
and Category of metric spaces
sage: Z(2^(2^5) + 1)
4294967297
```

One can give strings to create integers. Strings starting with `0x` are interpreted as hexadecimal, and strings starting with `0o` are interpreted as octal:

```
sage: parent('37')
<... 'str'>
sage: parent(Z('37'))
Integer Ring
sage: Z('0x10')
16
sage: Z('0x1a')
26
sage: Z('0o20')
16
```

As an inverse to `digits()`, lists of digits are accepted, provided that you give a base. The lists are interpreted in little-endian order, so that entry `i` of the list is the coefficient of `base^i`:

```
sage: Z([4,1,7], base=100)
70104
sage: Z([4,1,7], base=10)
714
sage: Z([3, 7], 10)
73
sage: Z([3, 7], 9)
66
sage: Z([], 10)
0
```

Alphanumeric strings can be used for bases 2..36; letters `a` to `z` represent numbers 10 to 36. Letter case does not matter.

```
sage: Z("sage", base=32)
928270
sage: Z("SAGE", base=32)
928270
sage: Z("Sage", base=32)
928270
sage: Z([14, 16, 10, 28], base=32)
928270
sage: 14 + 16*32 + 10*32^2 + 28*32^3
928270
```

We next illustrate basic arithmetic in \mathbf{Z} :

```
sage: a = Z(1234); a
1234
sage: b = Z(5678); b
5678
sage: type(a)
<class 'sage.rings.integer.Integer'>
sage: a + b
6912
sage: b + a
6912
sage: a * b
7006652
sage: b * a
7006652
sage: a - b
-4444
sage: b - a
4444
```

When we divide two integers using `/`, the result is automatically coerced to the field of rational numbers, even if the result is an integer.

```
sage: a / b
617/2839
sage: type(a/b)
<class 'sage.rings.rational.Rational'>
sage: a/a
1
sage: type(a/a)
<class 'sage.rings.rational.Rational'>
```

For floor division, use the `//` operator instead:

```
sage: a // b
0
sage: type(a//b)
<class 'sage.rings.integer.Integer'>
```

Next we illustrate arithmetic with automatic coercion. The types that coerce are: str, int, long, Integer.

```
sage: a + 17
1251
sage: a * 374
461516
sage: 374 * a
461516
sage: a/19
1234/19
sage: 0 + Z(-64)
-64
```

Integers can be coerced:

```
sage: a = Z(-64)
sage: int(a)
-64
```

We can create integers from several types of objects:

```
sage: Z(17/1)
17
sage: Z(Mod(19, 23))
19
sage: Z(2 + 3*5 + O(5^3)) #_
˓needs sage.rings.padics
17
```

Arbitrary numeric bases are supported; strings or list of integers are used to provide the digits (more details in [IntegerRing_class](#)):

```
sage: Z("sage", base=32)
928270
sage: Z([14, 16, 10, 28], base=32)
928270
```

The `digits` method allows you to get the list of digits of an integer in a different basis (note that the digits are returned in little-endian order):

```
sage: b = Z([4, 1, 7], base=100)
sage: b
70104
sage: b.digits(base=71)
[27, 64, 13]

sage: Z(15).digits(2)
[1, 1, 1, 1]
sage: Z(15).digits(3)
[0, 2, 1]
```

The `str` method returns a string of the digits, using letters `a` to `z` to represent digits 10..36:

```
sage: Z(928270).str(base=32)
'sage'
```

Note that `str` only works with bases 2 through 36.

`absolute_degree()`

Return the absolute degree of the integers, which is 1.

Here, absolute degree refers to the rank of the ring as a module over the integers.

EXAMPLES:

```
sage: ZZ.absolute_degree()
1
```

`characteristic()`

Return the characteristic of the integers, which is 0.

EXAMPLES:

```
sage: ZZ.characteristic()
0
```

`completion(p, prec, extras={})`

Return the metric completion of the integers at the prime p .

INPUT:

- p – a prime (or infinity)
- prec – the desired precision
- extras – any further parameters to pass to the method used to create the completion

OUTPUT: the completion of \mathbf{Z} at p

EXAMPLES:

```
sage: ZZ.completion(infinity, 53)
Integer Ring
sage: ZZ.completion(5, 15, {'print_mode': 'bars'}) #_
→needs sage.rings.padics
5-adic Ring with capped relative precision 15
```

degree()

Return the degree of the integers, which is 1.

Here, degree refers to the rank of the ring as a module over the integers.

EXAMPLES:

```
sage: ZZ.degree()
1
```

extension(*poly, names, **kwds*)

Return the order generated by the specified list of polynomials.

INPUT:

- poly – list of one or more polynomials
- names – a parameter which will be passed to `EquationOrder()`
- embedding – a parameter which will be passed to `EquationOrder()`

OUTPUT:

- Given a single polynomial as input, return the order generated by a root of the polynomial in the field generated by a root of the polynomial.

Given a list of polynomials as input, return the relative order generated by a root of the first polynomial in the list, over the order generated by the roots of the subsequent polynomials.

EXAMPLES:

```
sage: x = polygen(ZZ, 'x')
sage: ZZ.extension(x^2 - 5, 'a') #_
→needs sage.rings.number_field
Order of conductor 2 generated by a in Number Field in a with defining_
→polynomial x^2 - 5
sage: ZZ.extension([x^2 + 1, x^2 + 2], 'a,b') #_
→needs sage.rings.number_field
Relative Order generated by [-b*a - 1, -3*a + 2*b] in Number Field in a
with defining polynomial x^2 + 1 over its base field
```

fraction_field()

Return the field of rational numbers - the fraction field of the integers.

EXAMPLES:

```
sage: ZZ.fraction_field()
Rational Field
sage: ZZ.fraction_field() == QQ
True
```

`from_bytes` (*input_bytes*, *byteorder='big'*, *is_signed=False*)

Return the integer represented by the given array of bytes.

Internally relies on the python `int.from_bytes()` method.

INPUT:

- *input_bytes* – a bytes-like object or iterable producing bytes
- *byteorder* – string (default: 'big'); determines the byte order of *input_bytes* (can only be 'big' or 'little')
- *is_signed* – boolean (default: False); determines whether to use two's compliment to represent the integer

EXAMPLES:

```
sage: ZZ.from_bytes(b'\x00\x10', byteorder='big')
16
sage: ZZ.from_bytes(b'\x00\x10', byteorder='little')
4096
sage: ZZ.from_bytes(b'\xfc\x00', byteorder='big', is_signed=True)
-1024
sage: ZZ.from_bytes(b'\xfc\x00', byteorder='big', is_signed=False)
64512
sage: ZZ.from_bytes([255, 0, 0], byteorder='big')
16711680
sage: type(_)
<class 'sage.rings.integer.Integer'>
```

`gen` (*n=0*)

Return the additive generator of the integers, which is 1.

INPUT:

- *n* – (default: 0) in a ring with more than one generator, the optional parameter *n* indicates which generator to return; since there is only one generator in this case, the only valid value for *n* is 0

EXAMPLES:

```
sage: ZZ.gen()
1
sage: type(ZZ.gen())
<class 'sage.rings.integer.Integer'>
```

`gens` ()

Return the tuple (1,) containing a single element, the additive generator of the integers, which is 1.

EXAMPLES:

```
sage: ZZ.gens(); ZZ.gens()[0]
(1,)
1
sage: type(ZZ.gens()[0])
<class 'sage.rings.integer.Integer'>
```

is_field(*proof=True*)

Return `False` since the integers are not a field.

EXAMPLES:

```
sage: ZZ.is_field()
False
```

is_integrally_closed()

Return that the integer ring is, in fact, integrally closed.

Note

This should rather be inherited from the category of `DedekindDomains`.

EXAMPLES:

```
sage: ZZ.is_integrally_closed()
True
```

krull_dimension()

Return the Krull dimension of the integers, which is 1.

Note

This should rather be inherited from the category of `DedekindDomains`.

EXAMPLES:

```
sage: ZZ.krull_dimension()
1
```

ngens()

Return the number of additive generators of the ring, which is 1.

EXAMPLES:

```
sage: ZZ.ngens()
1
sage: len(ZZ.gens())
1
```

order()

Return the order (cardinality) of the integers, which is `+Infinity`.

EXAMPLES:

```
sage: ZZ.order()
+Infinity
```

parameter()

Return an integer of degree 1 for the Euclidean property of \mathbf{Z} , namely 1.

EXAMPLES:

```
sage: ZZ.parameter()
1
```

quotient (*I, names=None, **kwds*)

Return the quotient of \mathbf{Z} by the ideal or integer \mathbb{I} .

EXAMPLES:

```
sage: ZZ.quo(6*ZZ)
Ring of integers modulo 6
sage: ZZ.quo(0*ZZ)
Integer Ring
sage: ZZ.quo(3)
Ring of integers modulo 3
sage: ZZ.quo(3*QQ)
Traceback (most recent call last):
...
TypeError: I must be an ideal of ZZ
```

random_element (*x=None, y=None, distribution=None*)

Return a random integer.

INPUT:

- *x, y* integers – bounds for the result
- *distribution* – string:
 - 'uniform'
 - 'mpz_rrandomb'
 - '1/n'
 - 'gaussian'

OUTPUT: with no input, return a random integer

If only one integer x is given, return an integer between 0 and $x - 1$.

If two integers are given, return an integer between x and $y - 1$ inclusive.

If at least one bound is given, the default distribution is the uniform distribution; otherwise, it is the distribution described below.

If the distribution '1/n' is specified, the bounds are ignored.

If the distribution 'mpz_rrandomb' is specified, the output is in the range from 0 to $2^x - 1$.

If the distribution 'gaussian' is specified, the output is sampled from a discrete Gaussian distribution with parameter $\sigma = x$ and centered at zero. That is, the integer v is returned with probability proportional to $\exp(-v^2/(2\sigma^2))$. See `sage.stats.distributions.discrete_gaussian_integer` for details. Note that if many samples from the same discrete Gaussian distribution are needed, it is faster to construct a `sage.stats.distributions.discrete_gaussian_integer.DiscreteGaussianDistributionIntegerSampler` object which is then repeatedly queried.

The default distribution for `ZZ.random_element()` is based on $X = \text{trunc}(4/(5R))$, where R is a random variable uniformly distributed between -1 and 1. This gives $\Pr(X = 0) = 1/5$, and $\Pr(X = n) = 2/(5|n|(|n| + 1))$ for $n \neq 0$. Most of the samples will be small; -1, 0, and 1 occur with probability 1/5

each. But we also have a small but non-negligible proportion of “outliers”; $\Pr(|X| \geq n) = 4/(5n)$, so for instance, we expect that $|X| \geq 1000$ on one in 1250 samples.

We actually use an easy-to-compute truncation of the above distribution; the probabilities given above hold fairly well up to about $|n| = 10000$, but around $|n| = 30000$ some values will never be returned at all, and we will never return anything greater than 2^{30} .

EXAMPLES:

```
sage: ZZ.random_element().parent() is ZZ
True
```

The default uniform distribution is integers in $[-2, 2]$:

```
sage: from collections import defaultdict
sage: def add_samples(*args, **kwds):
....:     global dic, counter
....:     for _ in range(100):
....:         counter += 1
....:         dic[ZZ.random_element(*args, **kwds)] += 1
....:
sage: def prob(x):
....:     return 1/5
sage: dic = defaultdict(Integer)
sage: counter = 0.0
sage: add_samples(distribution='uniform')
sage: while any(abs(dic[i]/counter - prob(i)) > 0.01 for i in dic):
....:     add_samples(distribution='uniform')
```

Here we use the distribution ' $1/n$ ':

```
sage: def prob(n):
....:     if n == 0:
....:         return 1/5
....:     return 2/(5*abs(n)*(abs(n) + 1))
sage: dic = defaultdict(Integer)
sage: counter = 0.0
sage: add_samples(distribution='1/n')
sage: while any(abs(dic[i]/counter - prob(i)) > 0.01 for i in dic):
....:     add_samples(distribution='1/n')
```

If a range is given, the default distribution is uniform in that range:

```
sage: -10 <= ZZ.random_element(-10, 10) < 10
True
sage: def prob(x):
....:     return 1/20
sage: dic = defaultdict(Integer)
sage: counter = 0.0
sage: add_samples(-10, 10)
sage: while any(abs(dic[i]/counter - prob(i)) > 0.01 for i in dic):
....:     add_samples(-10, 10)
....:
sage: 0 <= ZZ.random_element(5) < 5
True
sage: def prob(x):
....:     return 1/5
sage: dic = defaultdict(Integer)
```

(continues on next page)

(continued from previous page)

```
sage: counter = 0.0
sage: add_samples(5)
sage: while any(abs(dic[i]/counter - prob(i)) > 0.01 for i in dic):
....:     add_samples(5)

sage: while ZZ.random_element(10^50) < 10^49:
....:     pass
```

Notice that the right endpoint is not included:

```
sage: all(ZZ.random_element(-2, 2) < 2 for _ in range(100))
True
```

We return a sample from a discrete Gaussian distribution:

```
sage: ZZ.random_element(11.0, distribution='gaussian').parent() is ZZ      #_
˓needs sage.modules
True
```

range (*start*, *end=None*, *step=None*)

Optimized range function for Sage integers.

AUTHORS:

- Robert Bradshaw (2007-09-20)

EXAMPLES:

```
sage: ZZ.range(10)
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
sage: ZZ.range(-5, 5)
[-5, -4, -3, -2, -1, 0, 1, 2, 3, 4]
sage: ZZ.range(0, 50, 5)
[0, 5, 10, 15, 20, 25, 30, 35, 40, 45]
sage: ZZ.range(0, 50, -5)
[]
sage: ZZ.range(50, 0, -5)
[50, 45, 40, 35, 30, 25, 20, 15, 10, 5]
sage: ZZ.range(50, 0, 5)
[]
sage: ZZ.range(50, -1, -5)
[50, 45, 40, 35, 30, 25, 20, 15, 10, 5, 0]
```

It uses different code if the step doesn't fit in a long:

```
sage: ZZ.range(0, 2^83, 2^80)
[0, 1208925819614629174706176, 2417851639229258349412352,
3626777458843887524118528, 4835703278458516698824704, ...
˓6044629098073145873530880,
7253554917687775048237056, 8462480737302404222943232]
```

Make sure Issue #8818 is fixed:

```
sage: ZZ.range(1r, 10r)
[1, 2, 3, 4, 5, 6, 7, 8, 9]
```

residue_field (*prime*, *check=True*, *names=None*)

Return the residue field of the integers modulo the given prime, i.e. $\mathbf{Z}/p\mathbf{Z}$.

INPUT:

- prime – a prime number
- check – boolean (default: True); whether or not to check the primality of prime
- names – ignored (for compatibility with number fields)

OUTPUT: the residue field at this prime**EXAMPLES:**

```
sage: # needs sage.libs.pari
sage: F = ZZ.residue_field(61); F
Residue field of Integers modulo 61
sage: pi = F.reduction_map(); pi
Partially defined reduction map:
From: Rational Field
To: Residue field of Integers modulo 61
sage: pi(123/234)
6
sage: pi(1/61)
Traceback (most recent call last):
...
ZeroDivisionError: Cannot reduce rational 1/61 modulo 61:
it has negative valuation
sage: lift = F.lift_map(); lift
Lifting map:
From: Residue field of Integers modulo 61
To: Integer Ring
sage: lift(F(12345/67890))
33
sage: (12345/67890) % 61
33
```

Construction can be from a prime ideal instead of a prime:

```
sage: ZZ.residue_field(ZZ.ideal(97))
Residue field of Integers modulo 97
```

valuation(*p*)

Return the discrete valuation with uniformizer p.

EXAMPLES:

```
sage: v = ZZ.valuation(3); v
˓needs sage.rings.padics
3-adic valuation
sage: v(3)
˓needs sage.rings.padics
1
```

See also`Order.valuation()`, `RationalField.valuation()`**zeta(*n=2*)**

Return a primitive n-th root of unity in the integers, or raise an error if none exists.

INPUT:

- n – (default: 2) a positive integer

OUTPUT:

an n -th root of unity in \mathbb{Z}

EXAMPLES:

```
sage: ZZ.zeta()
-1
sage: ZZ.zeta(1)
1
sage: ZZ.zeta(3)
Traceback (most recent call last):
...
ValueError: no nth root of unity in integer ring
sage: ZZ.zeta(0)
Traceback (most recent call last):
...
ValueError: n must be positive in zeta()
```

`sage.rings.integer_ring.crt_basis(X, xgcd=None)`

Compute and return a Chinese Remainder Theorem basis for the list X of coprime integers.

INPUT:

- X – list of Integers that are coprime in pairs
- $xgcd$ – an optional parameter which is ignored

OUTPUT:

- E – list of Integers such that $E[i] \equiv 1 \pmod{X[i]}$ and $E[i] \equiv 0 \pmod{X[j]}$ for all $j \neq i$

For this explanation, let $E[i]$ be denoted by E_i .

The E_i have the property that if A is a list of objects, e.g., integers, vectors, matrices, etc., where A_i is understood modulo X_i , then a CRT lift of A is simply

$$\sum_i E_i A_i.$$

ALGORITHM: To compute E_i , compute integers s and t such that

$$sX_i + t \prod_{i \neq j} X_j = 1.()$$

Then

$$E_i = t \prod_{i \neq j} X[j].$$

Notice that equation (*) implies that E_i is congruent to 1 modulo X_i and to 0 modulo the other X_j for $j \neq i$.

COMPLEXITY: We compute $\text{len}(X)$ extended GCD's.

EXAMPLES:

```
sage: X = [11, 20, 31, 51]
sage: E = crt_basis([11, 20, 31, 51])
sage: E[0] % X[0], E[1] % X[0], E[2] % X[0], E[3] % X[0]
(1, 0, 0, 0)
sage: E[0] % X[1], E[1] % X[1], E[2] % X[1], E[3] % X[1]
(0, 1, 0, 0)
sage: E[0] % X[2], E[1] % X[2], E[2] % X[2], E[3] % X[2]
(0, 0, 1, 0)
sage: E[0] % X[3], E[1] % X[3], E[2] % X[3], E[3] % X[3]
(0, 0, 0, 1)
```

`sage.rings.integer_ring.is_IntegerRing(x)`

Internal function: return True iff x is the ring \mathbf{Z} of integers.

1.2 Elements of the ring \mathbf{Z} of integers

Sage has highly optimized and extensive functionality for arithmetic with integers and the ring of integers.

EXAMPLES:

Add 2 integers:

```
sage: a = Integer(3); b = Integer(4)
sage: a + b == 7
True
```

Add an integer and a real number:

```
sage: a + 4.0
# needs sage.rings.real_mpfr
7.000000000000000
```

Add an integer and a rational number:

```
sage: a + Rational(2)/5
17/5
```

Add an integer and a complex number:

```
sage: # needs sage.rings.real_mpfr
sage: b = ComplexField().0 + 1.5
sage: loads((a + b).dumps()) == a + b
True

sage: z = 32
sage: -z
-32
sage: z = 0; -z
0
sage: z = -0; -z
0
sage: z = -1; -z
1
```

Multiplication:

```
sage: a = Integer(3); b = Integer(4)
sage: a * b == 12
True
sage: loads((a * 4.0).dumps()) == a*b
True
sage: a * Rational(2)/5
6/5
```

```
sage: [2,3] * 4
[2, 3, 2, 3, 2, 3, 2, 3]
```

```
sage: 'sage' * Integer(3)
'sagesage'
```

COERCIONS:

Return version of this integer in the multi-precision floating real field \mathbf{R} :

```
sage: n = 9390823
sage: RR = RealField(200) #_
˓needs sage.rings.real_mpfr
sage: RR(n) #_
˓needs sage.rings.real_mpfr
9.3908230000000000000000000000000000000000000000000000000000000000000000000000e6
```

AUTHORS:

- William Stein (2005): initial version
- Gonzalo Tornaria (2006-03-02): vastly improved python/GMP conversion; hashing
- Didier Deshommes (2006-03-06): numerous examples and docstrings
- William Stein (2006-03-31): changes to reflect GMP bug fixes
- William Stein (2006-04-14): added GMP factorial method (since it's now very fast).
- David Harvey (2006-09-15): added nth_root, exact_log
- David Harvey (2006-09-16): attempt to optimise Integer constructor
- Rishikesh (2007-02-25): changed quo_rem so that the rem is positive
- David Harvey, Martin Albrecht, Robert Bradshaw (2007-03-01): optimized Integer constructor and pool
- Pablo De Napoli (2007-04-01): multiplicative_order should return +infinity for non zero numbers
- Robert Bradshaw (2007-04-12): is_perfect_power, Jacobi symbol (with Kronecker extension). Convert some methods to use GMP directly rather than PARI, Integer(), PY_NEW(Integer)
- David Roe (2007-03-21): sped up valuation and is_square, added val_unit, is_power, is_power_of and divide_knowing_divisible_by
- Robert Bradshaw (2008-03-26): gamma function, multifactorials
- Robert Bradshaw (2008-10-02): bounded squarefree part
- David Loeffler (2011-01-15): fixed bug #10625 (inverse_mod should accept an ideal as argument)
- Vincent Delecroix (2010-12-28): added unicode in Integer.__init__
- David Roe (2012-03): deprecate is_power() in favour of is_perfect_power() (see Issue #12116)
- Vincent Delecroix (2017-05-03): faster integer-rational comparisons

- Vincent Klein (2017-05-11): add `__mpz__()` to class Integer
- Vincent Klein (2017-05-22): Integer constructor support gmpy2.mpz parameter
- Samuel Lelièvre (2018-08-02): document that divisors are sorted ([Issue #25983](#))

```
sage.rings.integer.GCD_list(v)
```

Return the greatest common divisor of a list of integers.

INPUT:

- v – list or tuple

Elements of v are converted to Sage integers. An empty list has GCD zero.

This function is used, for example, by `rings/arith.py`.

EXAMPLES:

```
sage: from sage.rings.integer import GCD_list
sage: w = GCD_list([3,9,30]); w
3
sage: type(w)
<class 'sage.rings.integer.Integer'>
```

Check that the bug reported in [Issue #3118](#) has been fixed:

```
sage: sage.rings.integer.GCD_list([2,2,3])
1
```

The inputs are converted to Sage integers.

```
sage: w = GCD_list([int(3), int(9), '30']); w
3
sage: type(w)
<class 'sage.rings.integer.Integer'>
```

Check that the GCD of the empty list is zero ([Issue #17257](#)):

```
sage: GCD_list([])
0
```

class sage.rings.integer.Integer

Bases: EuclideanDomainElement

The `Integer` class represents arbitrary precision integers. It derives from the `Element` class, so integers can be used as ring elements anywhere in Sage.

The constructor of `Integer` interprets strings that begin with `0o` as octal numbers, strings that begin with `0x` as hexadecimal numbers and strings that begin with `0b` as binary numbers.

The class `Integer` is implemented in Cython, as a wrapper of the GMP `mpz_t` integer type.

EXAMPLES:

```
sage: Integer(123)
123
sage: Integer("123")
123
```

Sage Integers support [PEP 3127](#) literals:

```
sage: Integer('0x12')
18
sage: Integer('-0o12')
-10
sage: Integer('+0b101010')
42
```

Conversion from PARI:

```
sage: Integer(pari('-10380104371593008048799446356441519384'))          #
˓needs sage.libs.pari
-10380104371593008048799446356441519384
sage: Integer(pari('Pol([-3])'))
˓needs sage.libs.pari
-3
```

Conversion from gmpy2:

```
sage: from gmpy2 import mpz
sage: Integer(mpz(3))
3
```

`__pow__` (*left, right, modulus*)

Return $(\text{left} \wedge \text{right}) \% \text{modulus}$.

EXAMPLES:

```
sage: 2^-6
1/64
sage: 2^6
64
sage: 2^0
1
sage: 2^-0
1
sage: (-1)^(1/3)          #
˓needs sage.symbolic
(-1)^(1/3)
```

For consistency with Python and MPFR, 0^0 is defined to be 1 in Sage:

```
sage: 0^0
1
```

See also <http://www.faqs.org/faqs/sci-math-faq/0to0/> and <https://math.stackexchange.com/questions/11150/zero-to-the-zero-power-is-0-0-1>.

The base need not be a Sage integer. If it is a Python type, the result is a Python type too:

```
sage: r = int(2) ^ 10; r; type(r)
1024
<... 'int'>
sage: r = int(3) ^ -3; r; type(r)
0.037037037037037035
<... 'float'>
sage: r = float(2.5) ^ 10; r; type(r)
9536.7431640625
<... 'float'>
```

We raise 2 to various interesting exponents:

```
sage: 2^x                      # symbolic x
      ↪needs sage.symbolic
2^x
sage: 2^1.5                     # real number
      ↪needs sage.rings.real_mpfr
2.82842712474619
sage: 2^float(1.5)              # python float abs tol 3e-16
2.8284271247461903
sage: 2^I                       # complex number
      ↪needs sage.symbolic
2^I
sage: r = 2 ^ int(-3); r; type(r)
1/8
<class 'sage.rings.rational.Rational'>
sage: f = 2^(sin(x)-cos(x)); f
      ↪needs sage.symbolic
2^(-cos(x) + sin(x))
sage: f(x=3)
      ↪needs sage.symbolic
2^(-cos(3) + sin(3))
```

A symbolic sum:

```
sage: # needs sage.symbolic
sage: x, y, z = var('x,y,z')
sage: 2^(x + y + z)
2^(x + y + z)
sage: 2^(1/2)
sqrt(2)
sage: 2^(-1/2)
1/2*sqrt(2)
```

additive_order()

Return the additive order of `self`.

EXAMPLES:

```
sage: ZZ(0).additive_order()
1
sage: ZZ(1).additive_order()
+Infinity
```

as_integer_ratio()

Return the pair `(self.numerator(), self.denominator())`, which is `(self, 1)`.

EXAMPLES:

```
sage: x = -12
sage: x.as_integer_ratio()
(-12, 1)
```

balanced_digits (base=10, positive_shift=True)

Return the list of balanced digits for `self` in the given base.

The balanced base `b` uses `b` digits centered around zero. Thus if `b` is odd, there is only one possibility, namely digits between $-b//2$ and $b//2$ (both included). For instance in base 9, one uses digits from -4 to 4. If `b`

is even, one has to choose between digits from $-b//2$ to $b//2 - 1$ or $-b//2 + 1$ to $b//2$ (base 10 for instance: either -5 to 4 or -4 to 5), and this is defined by the value of `positive_shift`.

INPUT:

- `base` – integer (default: `10`); when `base` is `2`, only the nonnegative or the nonpositive integers can be represented by `balanced_digits`. Thus we say `base` must be greater than `2`.
- `positive_shift` – boolean (default: `True`); for even bases, the representation uses digits from $-b//2 + 1$ to $b//2$ if set to `True`, and from $-b//2$ to $b//2 - 1$ otherwise. This has no effect for odd bases.

EXAMPLES:

```
sage: 8.balanced_digits(3)
[-1, 0, 1]
sage: (-15).balanced_digits(5)
[0, 2, -1]
sage: 17.balanced_digits(6)
[-1, 3]
sage: 17.balanced_digits(6, positive_shift=False)
[-1, -3, 1]
sage: (-46).balanced_digits()
[4, 5, -1]
sage: (-46).balanced_digits(positive_shift=False)
[4, -5]
sage: (-23).balanced_digits(12)
[1, -2]
sage: (-23).balanced_digits(12, positive_shift=False)
[1, -2]
sage: 0.balanced_digits(7)
[]
sage: 14.balanced_digits(5.8)
Traceback (most recent call last):
...
ValueError: base must be an integer
sage: 14.balanced_digits(2)
Traceback (most recent call last):
...
ValueError: base must be > 2
```

See also[digits](#)**binary()**

Return the binary digits of `self` as a string.

EXAMPLES:

```
sage: print(Integer(15).binary())
1111
sage: print(Integer(16).binary())
10000
sage: print(Integer(16938402384092843092843098243).binary())
11011010111011000111000111001001010011101000110101000111111000101000000000101110000100000
```

binomial(*m*, *algorithm*='gmp')

Return the binomial coefficient “self choose *m*”.

INPUT:

- *m* – integer
- *algorithm* – 'gmp' (default), 'mpir' (an alias for gmp), or 'pari'; 'gmp' is faster for small *m*, and 'pari' tends to be faster for large *m*

OUTPUT: integer

EXAMPLES:

```
sage: 10.binomial(2)
45
sage: 10.binomial(2, algorithm='pari') #_
˓needs sage.libs.pari
45
sage: 10.binomial(-2)
0
sage: (-2).binomial(3)
-4
sage: (-3).binomial(0)
1
```

The argument *m* or (self – *m*) must fit into an unsigned long:

```
sage: (2**256).binomial(2**256)
1
sage: (2**256).binomial(2**256 - 1)
115792089237316195423570985008687907853269984665640564039457584007913129639936
sage: (2**256).binomial(2**128)
Traceback (most recent call last):
...
OverflowError: m must fit in an unsigned long
```

bit_length()

Return the number of bits required to represent this integer.

Identical to `int.bit_length()`.

EXAMPLES:

```
sage: 500.bit_length()
9
sage: 5.bit_length()
3
sage: 0.bit_length() == len(0.bits()) == 0.ndigits(base=2)
True
sage: 12345.bit_length() == len(12345.binary())
True
sage: 1023.bit_length()
10
sage: 1024.bit_length()
11
```

bits()

Return the bits in self as a list, least significant first. The result satisfies the identity

```
x == sum(b*2^e for e, b in enumerate(x.bits()))
```

Negative numbers will have negative “bits”. (So, strictly speaking, the entries of the returned list are not really members of $\mathbf{Z}/2\mathbf{Z}$.)

This method just calls `digits()` with `base=2`.

See also

- `bit_length()`, a faster way to compute `len(x.bits())`
- `binary()`, which returns a string in perhaps more familiar notation

EXAMPLES:

```
sage: 500.bits()
[0, 0, 1, 0, 1, 1, 1, 1, 1]
sage: 11.bits()
[1, 1, 0, 1]
sage: (-99).bits()
[-1, -1, 0, 0, 0, -1, -1]
```

`ceil()`

Return the ceiling of `self`, which is `self` since `self` is an integer.

EXAMPLES:

```
sage: n = 6
sage: n.ceil()
6
```

`class_number(proof=True)`

Return the class number of the quadratic order with this discriminant.

INPUT:

- `self` – integer congruent to 0 or 1 mod 4 which is not a square
- `proof` – boolean (default: `True`); if `False`, then for negative discriminants a faster algorithm is used by the PARI library which is known to give incorrect results when the class group has many cyclic factors. However, the results are correct for discriminants D with $|D| \leq 2 \cdot 10^{10}$.

OUTPUT:

(integer) the class number of the quadratic order with this discriminant.

Note

For positive D , this is not always equal to the number of classes of primitive binary quadratic forms of discriminant D , which is equal to the narrow class number. The two notions are the same when $D < 0$, or $D > 0$ and the fundamental unit of the order has negative norm; otherwise the number of classes of forms is twice this class number.

EXAMPLES:

```

sage: (-163).class_number() #_
˓needs sage.libs.pari
1
sage: (-104).class_number() #_
˓needs sage.libs.pari
6
sage: [((4*n + 1), (4*n + 1).class_number()) for n in [21..29]] #_
˓needs sage.libs.pari
[(85, 2),
(89, 1),
(93, 1),
(97, 1),
(101, 1),
(105, 2),
(109, 1),
(113, 1),
(117, 1)]

```

conjugate ()

Return the complex conjugate of this integer, which is the integer itself.

EXAMPLES:

```

sage: n = 205
sage: n.conjugate()
205

```

coprime_integers (m)

Return the nonnegative integers $< m$ that are coprime to this integer.

EXAMPLES:

```

sage: n = 8
sage: n.coprime_integers(8)
[1, 3, 5, 7]
sage: n.coprime_integers(11)
[1, 3, 5, 7, 9]
sage: n = 5; n.coprime_integers(10)
[1, 2, 3, 4, 6, 7, 8, 9]
sage: n.coprime_integers(5)
[1, 2, 3, 4]
sage: n = 99; n.coprime_integers(99)
[1, 2, 4, 5, 7, 8, 10, 13, 14, 16, 17, 19, 20, 23, 25, 26, 28, 29, 31, 32, 34,
˓ 35, 37, 38, 40, 41, 43, 46, 47, 49, 50, 52, 53, 56, 58, 59, 61, 62, 64, 65,
˓ 67, 68, 70, 71, 73, 74, 76, 79, 80, 82, 83, 85, 86, 89, 91, 92, 94, 95, 97,
˓ 98]

```

AUTHORS:

- Naqi Jaffery (2006-01-24): examples
- David Roe (2017-10-02): Use sieving
- Jeroen Demeyer (2018-06-25): allow returning zero (only relevant for 1.coprime_integers(n))

ALGORITHM:

Create an integer with m bits and set bits at every multiple of a prime p that divides this integer and is less than m . Then return a list of integers corresponding to the unset bits.

crt (y, m, n)

Return the unique integer between 0 and mn that is congruent to the integer modulo m and to y modulo n .

We assume that m and n are coprime.

EXAMPLES:

```
sage: n = 17
sage: m = n.crt(5, 23, 11); m
247
sage: m%23
17
sage: m%11
5
```

denominator()

Return the denominator of this integer, which of course is always 1.

EXAMPLES:

```
sage: x = 5
sage: x.denominator()
1
sage: x = 0
sage: x.denominator()
1
```

digits ($base=10, digits=None, padto=0$)

Return a list of digits for `self` in the given base in little endian order.

The returned value is unspecified if `self` is a negative number and the digits are given.

INPUT:

- `base` – integer (default: 10)
- `digits` – (optional) indexable object as source for the digits
- `padto` – the minimal length of the returned list, sufficient number of zeros are added to make the list minimum that length (default: 0)

As a shorthand for `digits(2)`, you can use `bits()`.

Also see `ndigits()`.

EXAMPLES:

```
sage: 17.digits()
[7, 1]
sage: 5.digits(base=2, digits=["zero", "one"])
['one', 'zero', 'one']
sage: 5.digits(3)
[2, 1]
sage: 0.digits(base=10)  # 0 has 0 digits
[]
sage: 0.digits(base=2)  # 0 has 0 digits
[]
sage: 10.digits(16, '0123456789abcdef')
['a']
sage: 0.digits(16, '0123456789abcdef')
[]
```

(continues on next page)

(continued from previous page)

```
sage: 0.digits(16,'0123456789abcdef',padto=1)
['0']
sage: 123.digits(base=10,padto=5)
[3, 2, 1, 0, 0]
sage: 123.digits(base=2,padto=3)          # padto is the minimal length
[1, 1, 0, 1, 1, 1]
sage: 123.digits(base=2,padto=10,digits=(1,-1))
[-1, -1, 1, -1, -1, -1, 1, 1, 1]
sage: a=9939082340; a.digits(10)
[0, 4, 3, 2, 8, 0, 9, 3, 9, 9]
sage: a.digits(512)
[100, 302, 26, 74]
sage: (-12).digits(10)
[-2, -1]
sage: (-12).digits(2)
[0, 0, -1, -1]
```

We support large bases.

```
sage: n=2^6000
sage: n.digits(2^3000)
[0, 0, 1]
```

```
sage: base=3; n=25
sage: l=n.digits(base)
sage: # the next relationship should hold for all n,base
sage: sum(base^i*l[i] for i in range(len(l)))==n
True
sage: base=3; n=-30; l=n.digits(base); sum(base^i*l[i] for i in_
range(len(l)))==n
True
```

The inverse of this method – constructing an integer from a list of digits and a base – can be done using the above method or by simply using `ZZ()` with a base:

```
sage: x = 123; ZZ(x.digits(), 10)
123
sage: x == ZZ(x.digits(6), 6)
True
sage: x == ZZ(x.digits(25), 25)
True
```

Using `sum()` and `enumerate()` to do the same thing is slightly faster in many cases (and `balanced_sum()` may be faster yet). Of course it gives the same result:

```
sage: base = 4
sage: sum(digit * base^i for i, digit in enumerate(x.digits(base))) == ZZ(x.
...digits(base), base)
True
```

Note: In some cases it is faster to give a digits collection. This would be particularly true for computing the digits of a series of small numbers. In these cases, the code is careful to allocate as few python objects as reasonably possible.

```
sage: digits = list(range(15))
sage: l = [ZZ(i).digits(15,digits) for i in range(100)]
```

(continues on next page)

(continued from previous page)

```
sage: l[16]
[1, 1]
```

This function is comparable to `str()` for speed.

```
sage: n=3^100000
sage: n.digits(base=10)[-1]  # slightly slower than str
                           # needs sage.rings.real_interval_field
1
sage: n=10^10000
sage: n.digits(base=10)[-1]  # slightly faster than str
                           # needs sage.rings.real_interval_field
1
```

AUTHORS:

- Joel B. Mohler (2008-03-02): significantly rewrote this entire function

`divide_knowing_divisible_by(right)`

Return the integer `self / right` when `self` is divisible by `right`.

If `self` is not divisible by `right`, the return value is undefined, and may not even be close to `self / right` for multi-word integers.

EXAMPLES:

```
sage: a = 8; b = 4
sage: a.divide_knowing_divisible_by(b)
2
sage: (100000).divide_knowing_divisible_by(25)
4000
sage: (100000).divide_knowing_divisible_by(26) # close (random)
3846
```

However, often it's way off.

```
sage: a = 2^70; a
1180591620717411303424
sage: a // 11 # floor divide
107326510974310118493
sage: a.divide_knowing_divisible_by(11) # way off and possibly random
43215361478743422388970455040
```

`divides(n)`

Return True if `self` divides `n`.

EXAMPLES:

```
sage: Z = IntegerRing()
sage: Z(5).divides(Z(10))
True
sage: Z(0).divides(Z(5))
False
sage: Z(10).divides(Z(5))
False
```

`divisors(method=None)`

Return the list of all positive integer divisors of this integer, sorted in increasing order.

EXAMPLES:

```
sage: (-3).divisors()
[1, 3]
sage: 6.divisors()
[1, 2, 3, 6]
sage: 28.divisors()
[1, 2, 4, 7, 14, 28]
sage: (2^5).divisors()
[1, 2, 4, 8, 16, 32]
sage: 100.divisors()
[1, 2, 4, 5, 10, 20, 25, 50, 100]
sage: 1.divisors()
[1]
sage: 0.divisors()
Traceback (most recent call last):
...
ValueError: n must be nonzero
sage: (2^3 * 3^2 * 17).divisors()
[1, 2, 3, 4, 6, 8, 9, 12, 17, 18, 24, 34, 36, 51, 68, 72,
102, 136, 153, 204, 306, 408, 612, 1224]
sage: a = odd_part(factorial(31))
sage: v = a.divisors() #_
˓needs sage.libs.pari
sage: len(v) #_
˓needs sage.libs.pari
172800
sage: prod(e + 1 for p, e in factor(a)) #_
˓needs sage.libs.pari
172800
sage: all(t.divides(a) for t in v) #_
˓needs sage.libs.pari
True
```

```
sage: n = 2^551 - 1
sage: L = n.divisors() #_
˓needs sage.libs.pari
sage: len(L) #_
˓needs sage.libs.pari
256
sage: L[-1] == n #_
˓needs sage.libs.pari
True
```

Note

If one first computes all the divisors and then sorts it, the sorting step can easily dominate the runtime. Note, however, that (nonnegative) multiplication on the left preserves relative order. One can leverage this fact to keep the list in order as one computes it using a process similar to that of the merge sort algorithm.

euclidean_degree()

Return the degree of this element as an element of a Euclidean domain.

If this is an element in the ring of integers, this is simply its absolute value.

EXAMPLES:

```
sage: ZZ(1).euclidean_degree()
1
```

exact_log(m)

Return the largest integer k such that $m^k \leq \text{self}$, i.e., the floor of $\log_m(\text{self})$.

This is guaranteed to return the correct answer even when the usual log function doesn't have sufficient precision.

INPUT:

- $m - \text{integer} \geq 2$

AUTHORS:

- David Harvey (2006-09-15)
- Joel B. Mohler (2009-04-08) – rewrote this to handle small cases and/or easy cases up to 100x faster..

EXAMPLES:

```
sage: Integer(125).exact_log(5)
3
sage: Integer(124).exact_log(5)
2
sage: Integer(126).exact_log(5)
3
sage: Integer(3).exact_log(5)
0
sage: Integer(1).exact_log(5)
0
sage: Integer(178^1700).exact_log(178)
1700
sage: Integer(178^1700-1).exact_log(178)
1699
sage: Integer(178^1700+1).exact_log(178)
1700
sage: # we need to exercise the large base code path too
sage: Integer(1780^1700-1).exact_log(1780)          #_
  ↳needs sage.rings.real_interval_field
1699

sage: # The following are very very fast.
sage: # Note that for base m a perfect power of 2, we get the exact log by_
  ↳counting bits.
sage: n = 2983579823750185701375109835; m = 32
sage: n.exact_log(m)
18
sage: # The next is a favorite of mine. The log2 approximate is exact and_
  ↳immediately provable.
sage: n = 90153710570912709517902579010793251709257901270941709247901209742124
sage: m = 213509721309572
sage: n.exact_log(m)
4
```

```
sage: # needs sage.rings.real_mpfr
sage: x = 3^100000
sage: RR(log(RR(x), 3))
100000.000000000
```

(continues on next page)

(continued from previous page)

```
sage: RR(log(RR(x + 100000), 3))
100000.000000000
```

```
sage: # needs sage.rings.real_mpfr
sage: x.exact_log(3)
100000
sage: (x + 1).exact_log(3)
100000
sage: (x - 1).exact_log(3)
99999
```

```
sage: # needs sage.rings.real_mpfr
sage: x.exact_log(2.5)
Traceback (most recent call last):
...
TypeError: Attempt to coerce non-integral RealNumber to Integer
```

exp(*prec=None*)

Return the exponential function of *self* as a real number.

This function is provided only so that Sage integers may be treated in the same manner as real numbers when convenient.

INPUT:

- *prec* – integer (default: `None`); if `None`, returns symbolic, else to given bits of precision as in `RealField`

EXAMPLES:

```
sage: Integer(8).exp() #_
˓needs sage.symbolic
e^8
sage: Integer(8).exp(prec=100) #_
˓needs sage.symbolic
2980.9579870417282747435920995
sage: exp(Integer(8)) #_
˓needs sage.symbolic
e^8
```

For even fairly large numbers, this may not be useful.

```
sage: y = Integer(145^145)
sage: y.exp() #_
˓needs sage.symbolic
e^
˓250242070113490792104595852795536756979321836584215652603235924094327073065541632248761100
sage: y.exp(prec=53) # default RealField precision #_
˓needs sage.symbolic
+infinity
```

factor(*algorithm='pari'*, *proof=None*, *limit=None*, *int_=False*, *verbose=0*)

Return the prime factorization of this integer as a formal Factorization object.

INPUT:

- *algorithm* – string; one of

- ‘pari’ – (default) use the PARI library
- ‘flint’ – use the FLINT library
- ‘kash’ – use the KASH computer algebra system (requires kash)
- ‘magma’ – use the MAGMA computer algebra system (requires an installation of MAGMA)
- ‘qsieve’ – use Bill Hart’s quadratic sieve code; WARNING: this may not work as expected, see qsieve? for more information
- ‘ecm’ – use ECM-GMP, an implementation of Hendrik Lenstra’s elliptic curve method
- proof – boolean (default: True); whether or not to prove primality of each factor (only applicable for ‘pari’ and ‘ecm’)
- limit – integer or None (default: None); if limit is given it must fit in a signed int, and the factorization is done using trial division and primes up to limit

OUTPUT: a Factorization object containing the prime factors and their multiplicities

EXAMPLES:

```
sage: n = 2^100 - 1; n.factor()
# ...
→needs sage.libs.pari
3 * 5^3 * 11 * 31 * 41 * 101 * 251 * 601 * 1801 * 4051 * 8101 * 268501
```

This factorization can be converted into a list of pairs (p, e) , where p is prime and e is a positive integer. Each pair can also be accessed directly by its index (ordered by increasing size of the prime):

```
sage: f = 60.factor()
sage: list(f)
[(2, 2), (3, 1), (5, 1)]
sage: f[2]
(5, 1)
```

Similarly, the factorization can be converted to a dictionary so the exponent can be extracted for each prime:

```
sage: f = (3^6).factor()
sage: dict(f)
{3: 6}
sage: dict(f)[3]
6
```

We use proof=False, which doesn’t prove correctness of the primes that appear in the factorization:

```
sage: n = 920384092842390423848290348203948092384082349082
sage: n.factor(proof=False)
# ...
→needs sage.libs.pari
2 * 11 * 1531 * 4402903 * 10023679 * 619162955472170540533894518173
sage: n.factor(proof=True)
# ...
→needs sage.libs.pari
2 * 11 * 1531 * 4402903 * 10023679 * 619162955472170540533894518173
```

We factor using trial division only:

```
sage: n.factor(limit=1000)
2 * 11 * 41835640583745019265831379463815822381094652231
```

An example where FLINT is used:

```
sage: n = 82862385732327628428164127822
sage: n.factor(algorithm='flint')
→needs sage.libs.flint
2 * 3 * 11 * 13 * 41 * 73 * 22650083 * 1424602265462161
```

We factor using a quadratic sieve algorithm:

We factor using the elliptic curve method:

factorial()

Return the factorial $n! = 1 \cdot 2 \cdot 3 \cdots n$.

If the input does not fit in an `unsigned long int`, an `OverflowError` is raised.

EXAMPLES:

```
sage: for n in strange(7):
....:     print("{} {}".format(n, n.factorial()))
0 1
1 1
2 2
3 6
4 24
5 120
6 720
```

Large integers raise an `OverflowError`:

```
sage: (2**64).factorial()
Traceback (most recent call last):
...
OverflowError: argument too large for factorial
```

And negative ones a `ValueError`:

```
sage: (-1).factorial()
Traceback (most recent call last):
...
ValueError: factorial only defined for nonnegative integers
```

floor()

Return the floor of `self`, which is just `self` since `self` is an integer.

EXAMPLES:

```
sage: n = 6
sage: n.floor()
6
```

gamma ()

The gamma function on integers is the factorial function (shifted by one) on positive integers, and $\pm\infty$ on nonpositive integers.

EXAMPLES:

```
sage: # needs sage.symbolic
sage: gamma(5)
24
sage: gamma(0)
Infinity
sage: gamma(-1)
Infinity
sage: gamma(-2^150)
Infinity
```

global height (*prec=None*)

Return the absolute logarithmic height of this rational integer.

INPUT·

- `prec` – integer; desired floating point precision (default: default RealField precision)

OUTPUT·

(real) The absolute logarithmic height of this rational integer.

ALGORITHM·

The height of the integer n is $\log |n|$.

EXAMPLES:

```
sage: # needs sage rings, rings
```

sage: ZZ(5)

```
1.60943791243410
sage: ZZ(-2).global_height(pre)
0.6931471805599453094172321214
sage: exp(_)
2.0000000000000000000000000000000
```

hex ()

Return the hexadecimal digits of `self` in lower case.

Note

'0x' is *not* prepended to the result like is done by the corresponding Python function on `int`. This is for efficiency sake—adding and stripping the string wastes time; since this function is used for conversions from integers to other C-library structures, it is important that it be fast.

EXAMPLES:

```
sage: print(Integer(15).hex())
f
sage: print(Integer(16).hex())
10
sage: print(Integer(16938402384092843092843098243).hex())
36bb1e3929d1a8fe2802f083
```

imag()

Return the imaginary part of `self`, which is zero.

EXAMPLES:

```
sage: Integer(9).imag()
0
```

inverse_mod(*n*)

Return the inverse of `self` modulo *n*, if this inverse exists.

Otherwise, raise a `ZeroDivisionError` exception.

INPUT:

- `self` – integer
- `n` – integer or ideal of integer ring

OUTPUT:

- `x` – integer such that $x * \text{self} = 1 \pmod{n}$, or raises `ZeroDivisionError`

IMPLEMENTATION:

Call the `mpz_invert` GMP library function.

EXAMPLES:

```
sage: a = Integer(189)
sage: a.inverse_mod(10000)
4709
sage: a.inverse_mod(-10000)
4709
sage: a.inverse_mod(1890)
Traceback (most recent call last):
...
ZeroDivisionError: inverse of Mod(189, 1890) does not exist
sage: a = Integer(19)**100000 # long time
sage: c = a.inverse_mod(a*a) # long time
Traceback (most recent call last):
...
ZeroDivisionError: inverse of Mod(..., ...) does not exist
```

We check that Issue #10625 is fixed:

```
sage: ZZ(2).inverse_mod(ZZ.ideal(3))
2
```

We check that Issue #9955 is fixed:

```
sage: Rational(3) % Rational(-1)
0
```

inverse_of_unit()

Return inverse of self if self is a unit in the integers, i.e., self is -1 or 1 . Otherwise, raise a `ZeroDivisionError`.

EXAMPLES:

```
sage: (1).inverse_of_unit()
1
sage: (-1).inverse_of_unit()
-1
sage: 5.inverse_of_unit()
Traceback (most recent call last):
...
ArithmeError: inverse does not exist
sage: 0.inverse_of_unit()
Traceback (most recent call last):
...
ArithmeError: inverse does not exist
```

is_discriminant()

Return `True` if this integer is a discriminant.

Note

A discriminant is an integer congruent to 0 or 1 modulo 4 .

EXAMPLES:

```
sage: (-1).is_discriminant()
False
sage: (-4).is_discriminant()
True
sage: 100.is_discriminant()
True
sage: 101.is_discriminant()
True
```

is_fundamental_discriminant()

Return `True` if this integer is a fundamental discriminant.

Note

A fundamental discriminant is a discriminant, not 0 or 1 and not a square multiple of a smaller discriminant.

EXAMPLES:

```
sage: (-4).is_fundamental_discriminant()
# needs sage.libs.pari
True
```

#

(continues on next page)

(continued from previous page)

```
sage: (-12).is_fundamental_discriminant()
False
sage: 101.is_fundamental_discriminant() #_
˓needs sage.libs.pari
True
```

is_integer()

Return True as they are integers.

EXAMPLES:

```
sage: sqrt(4).is_integer()
True
```

is_integral()

Return True since integers are integral, i.e., satisfy a monic polynomial with integer coefficients.

EXAMPLES:

```
sage: Integer(3).is_integral()
True
```

is_irreducible()

Return True if self is irreducible, i.e. +/- prime

EXAMPLES:

```
sage: z = 2^31 - 1
sage: z.is_irreducible() #_
˓needs sage.libs.pari
True
sage: z = 2^31
sage: z.is_irreducible()
False
sage: z = 7
sage: z.is_irreducible()
True
sage: z = -7
sage: z.is_irreducible()
True
```

is_norm(*K, element=False, proof=True*)

See `QQ(self).is_norm()`.

EXAMPLES:

```
sage: n = 7
sage: n.is_norm(QQ)
True
sage: n.is_norm(QQ, element=True)
(True, 7)

sage: # needs sage.rings.number_field
sage: x = polygen(ZZ, 'x')
sage: K = NumberField(x^2 - 2, 'beta')
sage: n = 4
sage: n.is_norm(K)
```

(continues on next page)

(continued from previous page)

```
True
sage: 5.is_norm(K)
False
sage: n.is_norm(K, element=True)
(True, -4*beta + 6)
sage: n.is_norm(K, element=True)[1].norm()
4
sage: n = 5
sage: n.is_norm(K, element=True)
(False, None)
```

is_one()

Return True if the integer is 1, otherwise False.

EXAMPLES:

```
sage: Integer(1).is_one()
True
sage: Integer(0).is_one()
False
```

is_perfect_power()

Return True if self is a perfect power, ie if there exist integers a and b , $b > 1$ with $\text{self} = a^b$.

See also

- [*perfect_power\(\)*](#): Finds the minimal base for which this integer is a perfect power.
- [*is_power_of\(\)*](#): If you know the base already, this method is the fastest option.
- [*is_prime_power\(\)*](#): Checks whether the base is prime.

EXAMPLES:

```
sage: Integer(-27).is_perfect_power()
True
sage: Integer(12).is_perfect_power()
False

sage: z = 8
sage: z.is_perfect_power()
True
sage: 144.is_perfect_power()
True
sage: 10.is_perfect_power()
False
sage: (-8).is_perfect_power()
True
sage: (-4).is_perfect_power()
False
```

is_power_of(n)

Return True if there is an integer b with $\text{self} = n^b$.

See also

- *perfect_power()*: Finds the minimal base for which this integer is a perfect power.
- *is_perfect_power()*: If you don't know the base but just want to know if this integer is a perfect power, use this function.
- *is_prime_power()*: Checks whether the base is prime.

EXAMPLES:

```
sage: Integer(64).is_power_of(4)
True
sage: Integer(64).is_power_of(16)
False
```

Note

For large integers `self`, *is_power_of()* is faster than *is_perfect_power()*. The following examples give some indication of how much faster.

```
sage: b = lcm(range(1,10000))
sage: b.exact_log(2)
14446
sage: t = cputime()
sage: for a in range(2, 1000): k = b.is_perfect_power()
sage: cputime(t)      # random
0.5320329999999976
sage: t = cputime()
sage: for a in range(2, 1000): k = b.is_power_of(2)
sage: cputime(t)      # random
0.0
sage: t = cputime()
sage: for a in range(2, 1000): k = b.is_power_of(3)
sage: cputime(t)      # random
0.032002000000000308
```

```
sage: b = lcm(range(1, 1000))
sage: b.exact_log(2)
1437
sage: t = cputime()
sage: for a in range(2, 10000): # note: changed range from the example above
....:     k = b.is_perfect_power()
sage: cputime(t)      # random
0.17201100000000036
sage: t = cputime(); TWO = int(2)
sage: for a in range(2, 10000): k = b.is_power_of(TWO)
sage: cputime(t)      # random
0.004000000000000036
sage: t = cputime()
sage: for a in range(2, 10000): k = b.is_power_of(3)
sage: cputime(t)      # random
0.040003000000000011
sage: t = cputime()
```

(continues on next page)

(continued from previous page)

```
sage: for a in range(2, 10000): k = b.is_power_of(a)
sage: cputime(t)      # random
0.0280019999999986
```

is_prime(*proof=None*)Test whether *self* is prime.

INPUT:

- *proof* – boolean or None (default). If False, use a strong pseudo-primality test (see *is_pseudoprime()*). If True, use a provable primality test. If unset, use the *default arithmetic proof* flag.

Note

Integer primes are by definition *positive*! This is different than Magma, but the same as in PARI. See also the *is_irreducible()* method.

EXAMPLES:

```
sage: z = 2^31 - 1
sage: z.is_prime()
# needs sage.libs.pari
True
sage: z = 2^31
sage: z.is_prime()
False
sage: z = 7
sage: z.is_prime()
True
sage: z = -7
sage: z.is_prime()
False
sage: z.is_irreducible()
True
```

```
sage: z = 10^80 + 129
sage: z.is_prime(proof=False)
# needs sage.libs.pari
True
sage: z.is_prime(proof=True)
# needs sage.libs.pari
True
```

When starting Sage the arithmetic proof flag is True. We can change it to False as follows:

```
sage: proof.arithmetic()
True
sage: n = 10^100 + 267
sage: timeit("n.is_prime()")      # not tested
# needs sage.libs.pari
5 loops, best of 3: 163 ms per loop
sage: proof.arithmetic(False)
sage: proof.arithmetic()
False
```

(continues on next page)

(continued from previous page)

```
sage: timeit("n.is_prime()")          # not tested
˓needs sage.libs.pari
1000 loops, best of 3: 573 us per loop
```

ALGORITHM:Calls the PARI function `pari:isprime`.**`is_prime_power` (*proof=None*, *get_data=False*)**Return `True` if this integer is a prime power, and `False` otherwise.

A prime power is a prime number raised to a positive power. Hence 1 is not a prime power.

For a method that uses a pseudoprimality test instead see `is_pseudoprime_power()`.**INPUT:**

- *proof* – boolean or `None` (default). If `False`, use a strong pseudo-primality test (see `is_pseudoprime()`). If `True`, use a provable primality test. If unset, use the default arithmetic proof flag.
- *get_data* – (default: `False`), if `True` return a pair (p, k) such that this integer equals p^k with p a prime and k a positive integer or the pair $(\text{self}, 0)$ otherwise.

See also

- `perfect_power()`: Finds the minimal base for which integer is a perfect power.
- `is_perfect_power()`: Doesn't test whether the base is prime.
- `is_power_of()`: If you know the base already this method is the fastest option.
- `is_pseudoprime_power()`: If the entry is very large.

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: 17.is_prime_power()
True
sage: 10.is_prime_power()
False
sage: 64.is_prime_power()
True
sage: (3^10000).is_prime_power()
True
sage: (10000).is_prime_power()
False
sage: (-3).is_prime_power()
False
sage: 0.is_prime_power()
False
sage: 1.is_prime_power()
False
sage: p = next_prime(10^20); p
10000000000000000000039
sage: p.is_prime_power()
True
sage: (p^97).is_prime_power()
True
```

(continues on next page)

(continued from previous page)

```
sage: (p + 1).is_prime_power()
False
```

With the `get_data` keyword set to `True`:

The method works for large entries when `proof=False`:

```
sage: proof.arithmetc(False)
sage: ((10^500 + 961)^4).is_prime_power()
needs sage.libs.pari
True
sage: proof.arithmetc(True)
```

We check that Issue #4777 is fixed:

```
sage: n = 150607571^14
sage: n.is_prime_power()
˓needs sage.libs.pari
True
```

is_pseudoprime()

Test whether `self` is a pseudoprime.

This uses PARI's Baillie-PSW probabilistic primality test. Currently, there are no known pseudoprimes for Baillie-PSW that are not actually prime. However, it is conjectured that there are infinitely many.

See Wikipedia article Baillie-PSW_primality_test

EXAMPLES:

```
sage: z = 2^31 - 1
sage: z.is_pseudoprime()
→needs sage.libs.pari
True
sage: z = 2^31
sage: z.is_pseudoprime()
→needs sage.libs.pari
False
```

is_pseudoprime_power (*get_data=False*)

Test if this number is a power of a pseudoprime number.

For large numbers, this method might be faster than `is_prime_power()`.

INPUT:

- `get_data` – (default: `False`) if `True` return a pair (p, k) such that this number equals p^k with p a pseudoprime and k a positive integer or the pair `(self, 0)` otherwise

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: x = 10^200 + 357
sage: x.is_pseudoprime()
True
sage: (x^12).is_pseudoprime_power()
True
sage: (x^12).is_pseudoprime_power(get_data=True)
(1000...000357, 12)
sage: (997^100).is_pseudoprime_power()
True
sage: (998^100).is_pseudoprime_power()
False
sage: ((10^1000 + 453)^2).is_pseudoprime_power()
True
```

`is_rational()`

Return `True` as an integer is a rational number.

EXAMPLES:

```
sage: 5.is_rational()
True
```

`is_square()`

Return `True` if `self` is a perfect square.

EXAMPLES:

```
sage: Integer(4).is_square()
True
sage: Integer(41).is_square()
False
```

`is_squarefree()`

Return `True` if this integer is not divisible by the square of any prime and `False` otherwise.

EXAMPLES:

```
sage: 100.is_squarefree() #_
˓needs sage.libs.pari
False
sage: 102.is_squarefree() #_
˓needs sage.libs.pari
True
sage: 0.is_squarefree() #_
˓needs sage.libs.pari
False
```

`is_unit()`

Return `True` if this integer is a unit, i.e., 1 or -1 .

EXAMPLES:

```
sage: for n in strange(-2,3):
....:     print("{} {}".format(n, n.is_unit()))
-2 False
-1 True
0 False
1 True
2 False
```

isqrt()

Return the integer floor of the square root of `self`, or raises an `ValueError` if `self` is negative.

EXAMPLES:

```
sage: a = Integer(5)
sage: a.isqrt()
2
```

```
sage: Integer(-102).isqrt()
Traceback (most recent call last):
...
ValueError: square root of negative integer not defined
```

jacobi(*b*)

Calculate the Jacobi symbol $\left(\frac{\text{self}}{b}\right)$.

EXAMPLES:

```
sage: z = -1
sage: z.jacobi(17)
1
sage: z.jacobi(19)
-1
sage: z.jacobi(17*19)
-1
sage: (2).jacobi(17)
1
sage: (3).jacobi(19)
-1
sage: (6).jacobi(17*19)
-1
sage: (6).jacobi(33)
0
sage: a = 3; b = 7
sage: a.jacobi(b) == -b.jacobi(a)
True
```

kronecker(*b*)

Calculate the Kronecker symbol $\left(\frac{\text{self}}{b}\right)$ with the Kronecker extension $(\text{self}/2) = (2/\text{self})$ when `self` is odd, or $(\text{self}/2) = 0$ when `self` is even.

EXAMPLES:

```
sage: z = 5
sage: z.kronecker(41)
1
sage: z.kronecker(43)
-1
```

(continues on next page)

(continued from previous page)

```
sage: z.kronecker(8)
-1
sage: z.kronecker(15)
0
sage: a = 2; b = 5
sage: a.kronecker(b) == b.kronecker(a)
True
```

list()

Return a list with this integer in it, to be compatible with the method for number fields.

EXAMPLES:

```
sage: m = 5
sage: m.list()
[5]
```

log(m=None, prec=None)

Return symbolic log by default, unless the logarithm is exact (for an integer argument). When `prec` is given, the RealField approximation to that bit precision is used.

This function is provided primarily so that Sage integers may be treated in the same manner as real numbers when convenient. Direct use of `exact_log()` is probably best for arithmetic log computation.

INPUT:

- `m` – (default: natural) log base e
- `prec` – integer (default: None); if None, returns symbolic, else to given bits of precision as in RealField

EXAMPLES:

```
sage: Integer(124).log(5) #_
˓needs sage.symbolic
log(124)/log(5)
sage: Integer(124).log(5, 100) #_
˓needs sage.rings.real_mpfr
2.9950093311241087454822446806
sage: Integer(125).log(5)
3
sage: Integer(125).log(5, prec=53) #_
˓needs sage.rings.real_mpfr
3.000000000000000
sage: log(Integer(125)) #_
˓needs sage.symbolic
3*log(5)
```

For extremely large numbers, this works:

```
sage: x = 3^100000
sage: log(x, 3) #_
˓needs sage.rings.real_interval_field
100000
```

Also `log(x)`, giving a symbolic output, works in a reasonable amount of time for this `x`:

```
sage: x = 3^100000
sage: log(x)
˓needs sage.symbolic
log(1334971414230...5522000001)
```

But approximations are probably more useful in this case, and work to as high a precision as we desire:

We can use non-integer bases, with default e:

```
sage: x.log(2.5, prec=53)
→needs sage.rings.real_mpfr
119897.784671579
```

We also get logarithms of negative integers, via the symbolic ring, using the branch from $-\pi$ to π :

```
sage: log(-1)
→needs sage.symbolic
I*pi
```

The logarithm of zero is done likewise:

```
sage: log(0)
      ↪needs sage.symbolic
-Infinity
```

Some rational bases yield integer logarithms ([Issue #21517](#)):

```
sage: ZZ(8).log(1/2)
-3
```

Check that Python ints are accepted (Issue #21518):

```
sage: ZZ(8).log(int(2))
```

multifactorial(k)

Compute the k -th factorial $n!^{(k)}$ of self.

The multifactorial number $n!^{(k)}$ is defined for nonnegative integers n as follows. For $k = 1$ this is the standard factorial, and for k greater than 1 it is the product of every k -th terms down from n to 1. The recursive definition is used to extend this function to the negative integers n .

This function uses direct call to GMP if k and n are nonnegative and uses simple transformation for other cases.

EXAMPLES.

```
sage: 5.multifactorial(1)
120
sage: 5.multifactorial(2)
15
sage: 5.multifactorial(3)
10

sage: 23.multifactorial(2)
316234143225
sage: prod([1..23, step=2])
316234143225

sage: (-29).multifactorial(7)
1/2640
sage: (-3).multifactorial(5)
1/2
sage: (-9).multifactorial(3)
Traceback (most recent call last):
...
ValueError: multifactorial undefined
```

When entries are too large an `OverflowError` is raised:

```
sage: (2**64).multifactorial(2)
Traceback (most recent call last):
...
OverflowError: argument too large for multifactorial
```

`multiplicative_order()`

Return the multiplicative order of `self`.

EXAMPLES:

```
sage: ZZ(1).multiplicative_order()
1
sage: ZZ(-1).multiplicative_order()
2
sage: ZZ(0).multiplicative_order()
+Infinity
sage: ZZ(2).multiplicative_order()
+Infinity
```

`nbits()`

Alias for `bit_length()`.

`ndigits(base=10)`

Return the number of digits of `self` expressed in the given base.

INPUT:

- `base` – integer (default: 10)

EXAMPLES:

```
sage: n = 52
sage: n.ndigits()
2
sage: n = -10003
```

(continues on next page)

(continued from previous page)

```
sage: n.ndigits()
5
sage: n = 15
sage: n.ndigits(2)
4
sage: n = 1000**1000000+1
sage: n.ndigits()
# needs sage.rings.real_interval_field
3000001
sage: n = 1000**1000000-1
sage: n.ndigits()
# needs sage.rings.real_interval_field
3000000
sage: n = 10**10000000-10**9999990
sage: n.ndigits()
# needs sage.rings.real_interval_field
10000000
```

next_prime (*proof=None*)

Return the next prime after `self`.

This method calls the PARI function `pari:nextprime`.

INPUT:

- `proof` – boolean or `None` (default: `None`, see `proof.arithmetic` or `sage.structure.proof`); note that the global Sage default is `proof=True`

EXAMPLES:

Use `proof=False`, which is way faster since it does not need a primality proof:

```
sage: Integer(0).next_prime() # ...
→needs sage.libs.pari
2
sage: Integer(1001).next_prime() # ...
→needs sage.libs.pari
1009
```

next_prime_power(*proof=None*)

Return the next prime power after self.

INPUT:

- `proof` – if `True` ensure that the returned value is the next prime power and if set to `False` uses probabilistic methods (i.e. the result is not guaranteed). By default it uses global configuration variables to determine which alternative to use (see `proof.arithmetic` or `sage.structure.proof`).

ALGORITHM:

The algorithm is naive. It computes the next power of 2 and goes through the odd numbers calling `is_prime_power()`.

See also

- `previous_prime_power()`
- `is_prime_power()`
- `next_prime()`
- `previous_prime()`

EXAMPLES:

```
sage: (-1).next_prime_power()
2
sage: 2.next_prime_power()
3
sage: 103.next_prime_power() #_
˓needs sage.libs.pari
107
sage: 107.next_prime_power()
109
sage: 2044.next_prime_power() #_
˓needs sage.libs.pari
2048
```

`next_probable_prime()`

Return the next probable prime after `self`, as determined by PARI.

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: (-37).next_probable_prime()
2
sage: (100).next_probable_prime()
101
sage: (2^512).next_probable_prime()
13407807929942597099574024998205846127479365820592393377723561443721764030073546976801874298
sage: 0.next_probable_prime()
2
sage: 126.next_probable_prime()
127
sage: 144168.next_probable_prime()
144169
```

`nth_root(n, truncate_mode=0)`

Return the (possibly truncated) n-th root of `self`.

INPUT:

- `n` – integer ≥ 1 (must fit in the C `int` type)

- `truncate_mode` – boolean, whether to allow truncation if `self` is not an n -th power

OUTPUT:

If `truncate_mode` is 0 (default), then returns the exact n 'th root if `self` is an n 'th power, or raises a `ValueError` if it is not.

If `truncate_mode` is 1, then if either n is odd or `self` is positive, returns a pair `(root, exact_flag)` where `root` is the truncated n -th root (rounded towards zero) and `exact_flag` is a boolean indicating whether the root extraction was exact; otherwise raises a `ValueError`.

AUTHORS:

- David Harvey (2006-09-15)
- Interface changed by John Cremona (2009-04-04)

EXAMPLES:

```
sage: Integer(125).nth_root(3)
5
sage: Integer(124).nth_root(3)
Traceback (most recent call last):
...
ValueError: 124 is not a 3rd power
sage: Integer(124).nth_root(3, truncate_mode=1)
(4, False)
sage: Integer(125).nth_root(3, truncate_mode=1)
(5, True)
sage: Integer(126).nth_root(3, truncate_mode=1)
(5, False)
```

```
sage: Integer(-125).nth_root(3)
-5
sage: Integer(-125).nth_root(3,truncate_mode=1)
(-5, True)
sage: Integer(-124).nth_root(3,truncate_mode=1)
(-4, False)
sage: Integer(-126).nth_root(3,truncate_mode=1)
(-5, False)
```

```
sage: Integer(125).nth_root(2, True)
(11, False)
sage: Integer(125).nth_root(3, True)
(5, True)
```

```
sage: Integer(125).nth_root(-5)
Traceback (most recent call last):
...
ValueError: n (=-5) must be positive
```

```
sage: Integer(-25).nth_root(2)
Traceback (most recent call last):
...
ValueError: cannot take even root of negative number
```

```
sage: a=9
sage: a.nth_root(3)
```

(continues on next page)

(continued from previous page)

```

Traceback (most recent call last):
...
ValueError: 9 is not a 3rd power

sage: a.nth_root(22)
Traceback (most recent call last):
...
ValueError: 9 is not a 22nd power

sage: ZZ(2^20).nth_root(21)
Traceback (most recent call last):
...
ValueError: 1048576 is not a 21st power

sage: ZZ(2^20).nth_root(21, truncate_mode=1)
(1, False)

```

numerator()

Return the numerator of this integer.

EXAMPLES:

```

sage: x = 5
sage: x.numerator()
5

```

```

sage: x = 0
sage: x.numerator()
0

```

oct()

Return the digits of `self` in base 8.

Note

‘0’ (or ‘0o’) is *not* prepended to the result like is done by the corresponding Python function on `int`. This is for efficiency sake—adding and stripping the string wastes time; since this function is used for conversions from integers to other C-library structures, it is important that it be fast.

EXAMPLES:

```

sage: print(Integer(800).oct())
1440
sage: print(Integer(8).oct())
10
sage: print(Integer(-50).oct())
-62
sage: print(Integer(-899).oct())
-1603
sage: print(Integer(16938402384092843092843098243).oct())
15535436162247215217705000570203

```

Behavior of Sage integers vs. Python integers:

```
sage: Integer(10).oct()
'12'
sage: oct(int(10))
'0o12'

sage: Integer(-23).oct()
'-27'
sage: oct(int(-23))
'-0o27'
```

odd_part()

The odd part of the integer n . This is $n/2^v$, where $v = \text{valuation}(n, 2)$.

IMPLEMENTATION:

Currently returns 0 when `self` is 0. This behaviour is fairly arbitrary, and in Sage 4.6 this special case was not handled at all, eventually propagating a `TypeError`. The caller should not rely on the behaviour in case `self` is 0.

EXAMPLES:

```
sage: odd_part(5)
5
sage: odd_part(4)
1
sage: odd_part(factorial(31))
122529844256906551386796875
```

ord(p)

Return the p -adic valuation of `self`.

INPUT:

- p – integer at least 2

EXAMPLES:

```
sage: n = 60
sage: n.valuation(2)
2
sage: n.valuation(3)
1
sage: n.valuation(7)
0
sage: n.valuation(1)
Traceback (most recent call last):
...
ValueError: You can only compute the valuation with respect to a integer
↳ larger than 1.
```

We do not require that p is a prime:

```
sage: (2^11).valuation(4)
5
```

ordinal_str()

Return a string representation of the ordinal associated to `self`.

EXAMPLES:

```

sage: [ZZ(n).ordinal_str() for n in range(25)]
['0th',
 '1st',
 '2nd',
 '3rd',
 '4th',
 ...
 '10th',
 '11th',
 '12th',
 '13th',
 '14th',
 ...
 '20th',
 '21st',
 '22nd',
 '23rd',
 '24th']

sage: ZZ(1001).ordinal_str()
'1001st'

sage: ZZ(113).ordinal_str()
'113th'
sage: ZZ(112).ordinal_str()
'112th'
sage: ZZ(111).ordinal_str()
'111th'

```

p_primary_part(*p*)

Return the *p*-primary part of *self*.

INPUT:

- *p* – prime integer

OUTPUT: largest power of *p* dividing *self*

EXAMPLES:

```

sage: n = 40
sage: n.p_primary_part(2)
8
sage: n.p_primary_part(5)
5
sage: n.p_primary_part(7)
1
sage: n.p_primary_part(6)
Traceback (most recent call last):
...
ValueError: 6 is not a prime number

```

perfect_power()

Return (*a*, *b*), where this integer is a^b and *b* is maximal.

If called on -1 , 0 or 1 , *b* will be 1 , since there is no maximal value of *b*.

See also

- `is_perfect_power()`: testing whether an integer is a perfect power is usually faster than finding a and b .
- `is_prime_power()`: checks whether the base is prime.
- `is_power_of()`: if you know the base already, this method is the fastest option.

EXAMPLES:

```
sage: 144.perfect_power() #_
˓needs sage.libs.pari
(12, 2)
sage: 1.perfect_power()
(1, 1)
sage: 0.perfect_power()
(0, 1)
sage: (-1).perfect_power()
(-1, 1)
sage: (-8).perfect_power() #_
˓needs sage.libs.pari
(-2, 3)
sage: (-4).perfect_power()
(-4, 1)
sage: (101^29).perfect_power() #_
˓needs sage.libs.pari
(101, 29)
sage: (-243).perfect_power() #_
˓needs sage.libs.pari
(-3, 5)
sage: (-64).perfect_power() #_
˓needs sage.libs.pari
(-4, 3)
```

popcount()

Return the number of 1 bits in the binary representation. If `self < 0`, we return `Infinity`.

EXAMPLES:

```
sage: n = 123
sage: n.str(2)
'1111011'
sage: n.popcount()
6

sage: n = -17
sage: n.popcount()
+Infinity
```

powermod(*exp, mod*)

Compute `self**exp` modulo `mod`.

EXAMPLES:

```
sage: z = 2
sage: z.powermod(31, 31)
```

(continues on next page)

(continued from previous page)

```

2
sage: z.powermod(0, 31)
1
sage: z.powermod(-31, 31) == 2^-31 % 31
True

```

As expected, the following is invalid:

```

sage: z.powermod(31, 0)
Traceback (most recent call last):
...
ZeroDivisionError: cannot raise to a power modulo 0

```

[previous_prime](#) (*proof=None*)

Return the previous prime before *self*.

This method calls the PARI function `pari:precprime`.

INPUT:

- *proof* – if `True` ensure that the returned value is the next prime power and if set to `False` uses probabilistic methods (i.e. the result is not guaranteed). By default it uses global configuration variables to determine which alternative to use (see `proof.arithmetic` or `sage.structure.proof`).

See also

- [next_prime\(\)](#)

EXAMPLES:

```

sage: 10.previous_prime()                                     #_
˓needs sage.libs.pari
7
sage: 7.previous_prime()                                     #_
˓needs sage.libs.pari
5
sage: 14376485.previous_prime()                            #_
˓needs sage.libs.pari
14376463

sage: 2.previous_prime()
Traceback (most recent call last):
...
ValueError: no prime less than 2

```

An example using `proof=False`, which is way faster since it does not need a primality proof:

```

sage: b = (2^1024).previous_prime(proof=False)             #_
˓needs sage.libs.pari
sage: 2^1024 - b                                         #_
˓needs sage.libs.pari
105

```

[previous_prime_power](#) (*proof=None*)

Return the previous prime power before *self*.

INPUT:

- `proof` – if `True` ensure that the returned value is the next prime power and if set to `False` uses probabilistic methods (i.e. the result is not guaranteed). By default it uses global configuration variables to determine which alternative to use (see `proof.arithmetic` or `sage.structure.proof`).

ALGORITHM:

The algorithm is naive. It computes the previous power of 2 and goes through the odd numbers calling the method `is_prime_power()`.

See also

- `next_prime_power()`
- `is_prime_power()`
- `previous_prime()`
- `next_prime()`

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: 3.previous_prime_power()
2
sage: 103.previous_prime_power()
101
sage: 107.previous_prime_power()
103
sage: 2044.previous_prime_power()
2039

sage: 2.previous_prime_power()
Traceback (most recent call last):
...
ValueError: no prime power less than 2
```

prime_divisors(*args, **kwds)

Return the prime divisors of this integer, sorted in increasing order.

If this integer is negative, we do *not* include -1 among its prime divisors, since -1 is not a prime number.

INPUT:

- `limit` – (integer, optional keyword argument) Return only prime divisors up to this bound, and the factorization is done by checking primes up to `limit` using trial division.

Any additional arguments are passed on to the `factor()` method.

EXAMPLES:

```
sage: a = 1; a.prime_divisors()
[]
sage: a = 100; a.prime_divisors()
[2, 5]
sage: a = -100; a.prime_divisors()
[2, 5]
sage: a = 2004; a.prime_divisors()
[2, 3, 167]
```

Setting the optional `limit` argument works as expected:

```
sage: a = 10^100 + 1
sage: a.prime_divisors()
needs sage.libs.pari
[73, 137, 401, 1201, 1601, 1676321, 5964848081,
129694419029057750551385771184564274499075700947656757821537291527196801]
sage: a.prime_divisors(limit=10^3)
[73, 137, 401]
sage: a.prime_divisors(limit=10^7)
[73, 137, 401, 1201, 1601, 1676321]
```

`prime_factors (*args, **kwds)`

Return the prime divisors of this integer, sorted in increasing order.

If this integer is negative, we do *not* include -1 among its prime divisors, since -1 is not a prime number.

INPUT:

- `limit` – (integer, optional keyword argument) Return only prime divisors up to this bound, and the factorization is done by checking primes up to `limit` using trial division.

Any additional arguments are passed on to the `factor()` method.

EXAMPLES:

```
sage: a = 1; a.prime_divisors()
[]
sage: a = 100; a.prime_divisors()
[2, 5]
sage: a = -100; a.prime_divisors()
[2, 5]
sage: a = 2004; a.prime_divisors()
[2, 3, 167]
```

Setting the optional `limit` argument works as expected:

```
sage: a = 10^100 + 1
sage: a.prime_divisors()
needs sage.libs.pari
[73, 137, 401, 1201, 1601, 1676321, 5964848081,
129694419029057750551385771184564274499075700947656757821537291527196801]
sage: a.prime_divisors(limit=10^3)
[73, 137, 401]
sage: a.prime_divisors(limit=10^7)
[73, 137, 401, 1201, 1601, 1676321]
```

`prime_to_m_part(m)`

Return the prime-to- m part of `self`, i.e., the largest divisor of `self` that is coprime to m .

INPUT:

- m – integer

OUTPUT: integer

EXAMPLES:

```
sage: 43434.prime_to_m_part(20)
21717
```

(continues on next page)

(continued from previous page)

```
sage: 2048.prime_to_m_part(2)
1
sage: 2048.prime_to_m_part(3)
2048

sage: 0.prime_to_m_part(2)
Traceback (most recent call last):
...
ArithmetricError: self must be nonzero
```

quo_rem(*other*)

Return the quotient and the remainder of *self* divided by *other*. Note that the remainder returned is always either zero or of the same sign as *other*.

INPUT:

- *other* – the divisor

OUTPUT:

- *q* – the quotient of *self*/*other*
- *r* – the remainder of *self*/*other*

EXAMPLES:

```
sage: z = Integer(231)
sage: z.quo_rem(2)
(115, 1)
sage: z.quo_rem(-2)
(-116, -1)
sage: z.quo_rem(0)
Traceback (most recent call last):
...
ZeroDivisionError: Integer division by zero

sage: a = ZZ.random_element(10**50)
sage: b = ZZ.random_element(10**15)
sage: q, r = a.quo_rem(b)
sage: q*b + r == a
True

sage: 3.quo_rem(ZZ['x'].0)
(0, 3)
```

rational_reconstruction(*m*)

Return the rational reconstruction of this integer modulo *m*, i.e., the unique (if it exists) rational number that reduces to *self* modulo *m* and whose numerator and denominator is bounded by $\sqrt{m}/2$.

INPUT:

- *self* – integer
- *m* – integer

OUTPUT: a *Rational***EXAMPLES:**

```
sage: (3/7) %100
29
sage: (29).rational_reconstruction(100)
3/7
```

real()

Return the real part of `self`, which is `self`.

EXAMPLES:

```
sage: Integer(-4).real()
-4
```

round(*mode='away'*)

Return the nearest integer to `self`, which is `self` since `self` is an integer.

EXAMPLES:

This example addresses Issue #23502:

```
sage: n = 6
sage: n.round()
6
```

sign()

Return the sign of this integer, which is -1 , 0 , or 1 depending on whether this number is negative, zero, or positive respectively.

OUTPUT: integer

EXAMPLES:

```
sage: 500.sign()
1
sage: 0.sign()
0
sage: (-10^43).sign()
-1
```

sqrt(*prec=None, extend=True, all=False*)

The square root function.

INPUT:

- `prec` – integer (default: `None`); if `None`, return an exact square root; otherwise return a numerical square root, to the given bits of precision.
- `extend` – boolean (default: `True`); if `True`, return a square root in an extension ring, if necessary. Otherwise, raise a `ValueError` if the square is not in the base ring. Ignored if `prec` is not `None`.
- `all` – boolean (default: `False`); if `True`, return all square roots of `self` (a list of length 0, 1, or 2)

EXAMPLES:

```
sage: Integer(144).sqrt()
12
sage: sqrt(Integer(144))
12
sage: Integer(102).sqrt()
```

#

(continues on next page)

(continued from previous page)

```
→needs sage.symbolic
sqrt(102)
```

```
sage: n = 2
sage: n.sqrt(all=True)
→needs sage.symbolic
[sqrt(2), -sqrt(2)]
sage: n.sqrt(prec=10)
→needs sage.rings.real_mpfr
1.4
sage: n.sqrt(prec=100)
→needs sage.rings.real_mpfr
1.4142135623730950488016887242
sage: n.sqrt(prec=100, all=True)
→needs sage.rings.real_mpfr
[1.4142135623730950488016887242, -1.4142135623730950488016887242]
sage: n.sqrt(extend=False)
Traceback (most recent call last):
...
ArithmeError: square root of 2 is not an integer
sage: (-1).sqrt(extend=False)
Traceback (most recent call last):
...
ArithmeError: square root of -1 is not an integer
sage: Integer(144).sqrt(all=True)
[12, -12]
sage: Integer(0).sqrt(all=True)
[0]
```

sqrtrem()

Return (s, r) where s is the integer square root of `self` and r is the remainder such that `self = s2 + r`. Raises `ValueError` if `self` is negative.

EXAMPLES:

```
sage: 25.sqrtrem()
(5, 0)
sage: 27.sqrtrem()
(5, 2)
sage: 0.sqrtrem()
(0, 0)
```

```
sage: Integer(-102).sqrtrem()
Traceback (most recent call last):
...
ValueError: square root of negative integer not defined
```

squarefree_part(bound=-1)

Return the square free part of x ($\equiv \text{``self''}$), i.e., the unique integer z that $x = zy^2$, with y^2 a perfect square and z square-free.

Use `self.radical()` for the product of the primes that divide `self`.

If `self` is 0, just returns 0.

EXAMPLES:

```
sage: squarefree_part(100)
1
sage: squarefree_part(12)
3
sage: squarefree_part(17*37*37)
17
sage: squarefree_part(-17*32)
-34
sage: squarefree_part(1)
1
sage: squarefree_part(-1)
-1
sage: squarefree_part(-2)
-2
sage: squarefree_part(-4)
-1
```

```
sage: a = 8 * 5^6 * 101^2
sage: a.squarefree_part(bound=2).factor()
2 * 5^6 * 101^2
sage: a.squarefree_part(bound=5).factor()
2 * 101^2
sage: a.squarefree_part(bound=1000)
2
sage: a.squarefree_part(bound=2**14)
2
sage: a = 7^3 * next_prime(2^100)^2 * next_prime(2^200) #_
    ↪needs sage.libs.pari
sage: a / a.squarefree_part(bound=1000) #_
    ↪needs sage.libs.pari
49
```

str(base=10)

Return the string representation of `self` in the given base.

EXAMPLES:

```
sage: Integer(2^10).str(2)
'10000000000'
sage: Integer(2^10).str(17)
'394'
```

```
sage: two = Integer(2)
sage: two.str(1)
Traceback (most recent call last):
...
ValueError: base (=1) must be between 2 and 36
```

```
sage: two.str(37)
Traceback (most recent call last):
...
ValueError: base (=37) must be between 2 and 36
```

```
sage: big = 10^5000000
sage: s = big.str()      # long time (2s on sage.math, 2014)
sage: len(s)             # long time (depends on above defn of s)
```

(continues on next page)

(continued from previous page)

```
5000001
sage: s[:10]          # long time (depends on above defn of s)
'1000000000'
```

support()

Return a sorted list of the primes dividing this integer.

OUTPUT: the sorted list of primes appearing in the factorization of this rational with positive exponent

EXAMPLES:

```
sage: factorial(10).support()
[2, 3, 5, 7]
sage: (-999).support()
[3, 37]
```

Trying to find the support of 0 raises an `ArithmeticError`:

```
sage: 0.support()
Traceback (most recent call last):
...
ArithmeticError: support of 0 not defined
```

test_bit(index)

Return the bit at `index`.

If the index is negative, returns 0.

Although internally a sign-magnitude representation is used for integers, this method pretends to use a two's complement representation. This is illustrated with a negative integer below.

EXAMPLES:

```
sage: w = 6
sage: w.str(2)
'110'
sage: w.test_bit(2)
1
sage: w.test_bit(-1)
0
sage: x = -20
sage: x.str(2)
'-10100'
sage: x.test_bit(4)
0
sage: x.test_bit(5)
1
sage: x.test_bit(6)
1
```

to_bytes(length=1, byteorder='big', is_signed=False)

Return an array of bytes representing an integer.

Internally relies on the python `int.to_bytes()` method.

INPUT:

- `length` – positive integer (default: 1); integer represented in `length` bytes

- `byteorder` – string (default: 'big'); determines the byte order of the output (can only be 'big' or 'little')
- `is_signed` – boolean (default: False); determines whether to use two's compliment to represent the integer

Todo

It should be possible to convert straight from the gmp type in cython. This could be significantly faster, but I am unsure of the fastest and cleanest way to do this.

EXAMPLES:

```
sage: (1024).to_bytes(2, byteorder='big')
b'\x04\x00'
sage: (1024).to_bytes(10, byteorder='big')
b'\x00\x00\x00\x00\x00\x00\x00\x00\x04\x00'
sage: (-1024).to_bytes(10, byteorder='big', is_signed=True)
b'\xff\xff\xff\xff\xff\xff\xff\xfc\x00'
sage: x = 1000
sage: x.to_bytes((x.bit_length() + 7) // 8, byteorder='little')
b'\xe8\x03'
```

`trailing_zero_bits()`

Return the number of trailing zero bits in `self`, i.e. the exponent of the largest power of 2 dividing `self`.

EXAMPLES:

```
sage: 11.trailing_zero_bits()
0
sage: (-11).trailing_zero_bits()
0
sage: (11<<5).trailing_zero_bits()
5
sage: (-11<<5).trailing_zero_bits()
5
sage: 0.trailing_zero_bits()
0
```

`trial_division(bound='LONG_MAX', start=2)`

Return smallest prime divisor of `self` up to `bound`, beginning checking at `start`, or `abs(self)` if no such divisor is found.

INPUT:

- `bound` – positive integer that fits in a C signed long
- `start` – positive integer that fits in a C signed long

OUTPUT: a positive integer

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: n = next_prime(10^6)*next_prime(10^7); n.trial_division()
1000003
sage: (-n).trial_division()
1000003
```

(continues on next page)

(continued from previous page)

You can specify a starting point:

```
sage: n = 3*5*101*103
sage: n.trial_division(start=50)
101
```

trunc()

Round this number to the nearest integer, which is `self` since `self` is an integer.

EXAMPLES:

```
sage: n = 6  
sage: n.trunc()  
6
```

val unit (p)

Return a pair: the p -adic valuation of `self`, and the p -adic unit of `self`.

INPUT:

- p – integer at least 2

OUTPUT:

- `v_p(self)` – the p -adic valuation of `self`
- `u_p(self)` – $\text{self} / p^{v_p(\text{self})}$

EXAMPLES:

```
sage: n = 60
sage: n.val_unit(2)
(2, 15)
sage: n.val_unit(3)
(1, 20)
sage: n.val_unit(7)
(0, 60)
sage: (2^11).val_unit(4)
(5, 2)
sage: 0.val_unit(2)
(+Infinity, 1)
```

valuation(p)

Return the p -adic valuation of `self`.

INPUT:

- p – integer at least 2

EXAMPLES:

```
sage: n = 60
sage: n.valuation(2)
2
sage: n.valuation(3)
1
sage: n.valuation(7)
0
sage: n.valuation(1)
Traceback (most recent call last):
...
ValueError: You can only compute the valuation with respect to a integer_
→larger than 1.
```

We do not require that p is a prime:

```
sage: (2^11).valuation(4)
5
```

xgcd(n)

Return the extended gcd of this element and `n`.

INPUT:

- n – integer

OUTPUT:

A triple (g, s, t) such that g is the nonnegative gcd of `self` and `n`, and s and t are cofactors satisfying the Bezout identity

$$g = s \cdot \text{self} + t \cdot n.$$

Note

There is no guarantee that the cofactors will be minimal. If you need the cofactors to be minimal use `_xgcd()`. Also, using `_xgcd()` directly might be faster in some cases, see Issue #13628.

EXAMPLES:

```
sage: 6.xgcd(4)
(2, 1, -1)
```

class sage.rings.integer.**IntegerWrapper**

Bases: `Integer`

Rationale for the `IntegerWrapper` class:

With `Integer` objects, the allocation/deallocation function slots are hijacked with custom functions that stick already allocated `Integer` objects (with initialized parent and `mpz_t` fields) into a pool on “deallocation” and then pull them out whenever a new one is needed. Because `Integers` objects are so common, this is actually a significant savings. However, this does cause issues with subclassing a Python class directly from `Integer` (but that’s ok for a Cython class).

As a workaround, one can instead derive a class from the intermediate class `IntegerWrapper`, which sets statically its alloc/dealloc methods to the *original* `Integer` alloc/dealloc methods, before they are swapped manually for the custom ones.

The constructor of `IntegerWrapper` further allows for specifying an alternative parent to `IntegerRing`.

```
sage.rings.integer.free_integer_pool()
```

class sage.rings.integer.**int_to_Z**

Bases: `Morphism`

EXAMPLES:

```
sage: f = ZZ.coerce_map_from(int)
sage: f
Native morphism:
From: Set of Python objects of class 'int'
To:   Integer Ring
sage: f(1rL)
1
```

```
sage.rings.integer.is_Integer(x)
```

Return True if x is of the Sage `Integer` type.

EXAMPLES:

```
sage: from sage.rings.integer import is_Integer
sage: is_Integer(2)
doctest:warning...
DeprecationWarning: The function is_Integer is deprecated;
use ' isinstance(..., Integer)' instead.
See https://github.com/sagemath/sage/issues/38128 for details.
True
sage: is_Integer(2/1)
False
sage: is_Integer(int(2))
```

(continues on next page)

(continued from previous page)

```
False
sage: is_Integer('5')
False
```

`sage.rings.integer.make_integer(s)`

Create a Sage integer from the base-32 Python *string* *s*. This is used in unpickling integers.

EXAMPLES:

```
sage: from sage.rings.integer import make_integer
sage: make_integer('-29')
-73
sage: make_integer(29)
Traceback (most recent call last):
...
TypeError: expected str...Integer found
```

1.3 Cython wrapper for bernmm library

AUTHOR:

- David Harvey (2008-06): initial version

`sage.rings.bernmm.bernmm_bern_modp(p, k)`

Compute $B_k \bmod p$, where B_k is the k -th Bernoulli number.

If B_k is not p -integral, return -1 .

INPUT:

- *p* – a prime
- *k* – nonnegative integer

COMPLEXITY:

Pretty much linear in *p*.

EXAMPLES:

```
sage: from sage.rings.bernmm import bernmm_bern_modp

sage: bernoulli(0) % 5, bernmm_bern_modp(5, 0)
(1, 1)
sage: bernoulli(1) % 5, bernmm_bern_modp(5, 1)
(2, 2)
sage: bernoulli(2) % 5, bernmm_bern_modp(5, 2)
(1, 1)
sage: bernoulli(3) % 5, bernmm_bern_modp(5, 3)
(0, 0)
sage: bernoulli(4), bernmm_bern_modp(5, 4)
(-1/30, -1)
sage: bernoulli(18) % 5, bernmm_bern_modp(5, 18)
(4, 4)
sage: bernoulli(19) % 5, bernmm_bern_modp(5, 19)
(0, 0)
```

(continues on next page)

(continued from previous page)

```
sage: p = 10000019; k = 1000
sage: bernoulli(k) % p
1972762
sage: bernmm_bern_modp(p, k)
1972762
```

`sage.rings.bernmmp.bernmmp_bern_rat (k, num_threads=1)`

Compute k -th Bernoulli number using a multimodular algorithm. (Wrapper for bernmm library.)

INPUT:

- k – nonnegative integer
- num_threads – integer ≥ 1 , number of threads to use

COMPLEXITY:

Pretty much quadratic in k . See the paper “A multimodular algorithm for computing Bernoulli numbers”, David Harvey, 2008, for more details.

EXAMPLES:

```
sage: from sage.rings.bernmmp import bernmm_bern_rat

sage: bernmm_bern_rat(0)
1
sage: bernmm_bern_rat(1)
-1/2
sage: bernmm_bern_rat(2)
1/6
sage: bernmm_bern_rat(3)
0
sage: bernmm_bern_rat(100)
-
↳ 94598037819122125295227433069493721872702841533066936133385696204311395415197247711/
↳ 33330
sage: bernmm_bern_rat(100, 3)
-
↳ 94598037819122125295227433069493721872702841533066936133385696204311395415197247711/
↳ 33330
```

1.4 Bernoulli numbers modulo p

AUTHOR:

- David Harvey (2006-07-26): initial version
- William Stein (2006-07-28): some touch up.
- David Harvey (2006-08-06): new, faster algorithm, also using faster NTL interface
- David Harvey (2007-08-31): algorithm for a single Bernoulli number mod p
- David Harvey (2008-06): added interface to bernmm, removed old code

`sage.rings.bernoulli_mod_p.bernoulli_mod_p (p)`

Return the Bernoulli numbers B_0, B_2, \dots, B_{p-3} modulo p .

INPUT:

- p – integer; a prime

OUTPUT:

list – Bernoulli numbers modulo p as a list of integers [$B(0)$, $B(2)$, ... $B(p-3)$].

ALGORITHM:

Described in accompanying latex file.

PERFORMANCE:

Should be complexity $O(p \log p)$.

EXAMPLES:

Check the results against PARI's C-library implementation (that computes exact rationals) for $p = 37$:

```
sage: bernoulli_mod_p(37)
[1, 31, 16, 15, 16, 4, 17, 32, 22, 31, 15, 15, 17, 12, 29, 2, 0, 2]
sage: [bernoulli(n) % 37 for n in range(0, 36, 2)]
[1, 31, 16, 15, 16, 4, 17, 32, 22, 31, 15, 15, 17, 12, 29, 2, 0, 2]
```

Boundary case:

```
sage: bernoulli_mod_p(3)
[1]
```

AUTHOR:

- David Harvey (2006-08-06)

`sage.rings.bernoulli_mod_p.bernoulli_mod_p_single(p, k)`

Return the Bernoulli number B_k mod p .

If B_k is not p -integral, an `ArithmetError` is raised.

INPUT:

- p – integer; a prime
- k – nonnegative integer

OUTPUT: the k -th Bernoulli number mod p

EXAMPLES:

```
sage: bernoulli_mod_p_single(1009, 48)
628
sage: bernoulli(48) % 1009
628

sage: bernoulli_mod_p_single(1, 5)
Traceback (most recent call last):
...
ValueError: p (=1) must be a prime >= 3

sage: bernoulli_mod_p_single(100, 4)
Traceback (most recent call last):
...
ValueError: p (=100) must be a prime

sage: bernoulli_mod_p_single(19, 5)
```

(continues on next page)

(continued from previous page)

```
0

sage: bernoulli_mod_p_single(19, 18)
Traceback (most recent call last):
...
ArithmetError: B_k is not integral at p

sage: bernoulli_mod_p_single(19, -4)
Traceback (most recent call last):
...
ValueError: k must be nonnegative
```

Check results against `bernoulli_mod_p`:

```
sage: bernoulli_mod_p(37)
[1, 31, 16, 15, 16, 4, 17, 32, 22, 31, 15, 15, 17, 12, 29, 2, 0, 2]
sage: [bernoulli_mod_p_single(37, n) % 37 for n in range(0, 36, 2)]
[1, 31, 16, 15, 16, 4, 17, 32, 22, 31, 15, 15, 17, 12, 29, 2, 0, 2]

sage: bernoulli_mod_p(31)
[1, 26, 1, 17, 1, 9, 11, 27, 14, 23, 13, 22, 14, 8, 14]
sage: [bernoulli_mod_p_single(31, n) % 31 for n in range(0, 30, 2)]
[1, 26, 1, 17, 1, 9, 11, 27, 14, 23, 13, 22, 14, 8, 14]

sage: bernoulli_mod_p(3)
[1]
sage: [bernoulli_mod_p_single(3, n) % 3 for n in range(0, 2, 2)]
[1]

sage: bernoulli_mod_p(5)
[1, 1]
sage: [bernoulli_mod_p_single(5, n) % 5 for n in range(0, 4, 2)]
[1, 1]

sage: bernoulli_mod_p(7)
[1, 6, 3]
sage: [bernoulli_mod_p_single(7, n) % 7 for n in range(0, 6, 2)]
[1, 6, 3]
```

AUTHOR:

- David Harvey (2007-08-31)
- David Harvey (2008-06): rewrote to use bernmm library

`sage.rings.bernoulli_mod_p.verify_bernoulli_mod_p(data)`

Compute checksum for Bernoulli numbers.

It checks the identity

$$\sum_{n=0}^{(p-3)/2} 2^{2n}(2n+1)B_{2n} \equiv -2 \pmod{p}$$

(see “Irregular Primes to One Million”, Buhler et al)

INPUT:

- `data` – list; same format as output of `bernoulli_mod_p()` function

OUTPUT: boolean; True if checksum passed

EXAMPLES:

```
sage: from sage.rings.bernoulli_mod_p import verify_bernoulli_mod_p
sage: verify_bernoulli_mod_p(bernoulli_mod_p(next_prime(3)))
True
sage: verify_bernoulli_mod_p(bernoulli_mod_p(next_prime(1000)))
True
sage: verify_bernoulli_mod_p([1, 2, 4, 5, 4])
True
sage: verify_bernoulli_mod_p([1, 2, 3, 4, 5])
False
```

This one should test that long longs are working:

```
sage: verify_bernoulli_mod_p(bernoulli_mod_p(next_prime(20000)))
True
```

AUTHOR: David Harvey

1.5 Integer factorization functions

AUTHORS:

- Andre Apitzsch (2011-01-13): initial version

`sage.rings.factorint.aurifeuillian(n, m, F=None, check=True)`

Return the Aurifeuillian factors $F_n^{\pm}(m^2n)$.

This is based off Theorem 3 of [Bre1993].

INPUT:

- `n` – integer
- `m` – integer
- `F` – integer (default: `None`)
- `check` – boolean (default: `True`)

OUTPUT: list of factors

EXAMPLES:

```
sage: from sage.rings.factorint import aurifeuillian

sage: # needs sage.libs.pari sage.rings.real_interval_field
sage: aurifeuillian(2, 2)
[5, 13]
sage: aurifeuillian(2, 2^5)
[1985, 2113]
sage: aurifeuillian(5, 3)
[1471, 2851]
sage: aurifeuillian(15, 1)
[19231, 142111]

sage: # needs sage.libs.pari
```

(continues on next page)

(continued from previous page)

```
sage: aurifeuillian(12, 3)
Traceback (most recent call last):
...
ValueError: n has to be square-free
sage: aurifeuillian(1, 2)
Traceback (most recent call last):
...
ValueError: n has to be greater than 1
sage: aurifeuillian(2, 0)
Traceback (most recent call last):
...
ValueError: m has to be positive
```

Note

There is no need to set F . It's only for increasing speed of `factor_aurifeuillian()`.

`sage.rings.factorint.factor_aurifeuillian(n, check=True)`

Return Aurifeuillian factors of n if $n = x^{(2k-1)x} \pm 1$ (where the sign is ‘-’ if $x = 1 \pmod{4}$, and ‘+’ otherwise) else n

INPUT:

- n – integer

OUTPUT: list of factors of n found by Aurifeuillian factorization

EXAMPLES:

```
sage: # needs sage.libs.pari sage.rings.real_interval_field
sage: from sage.rings.factorint import factor_aurifeuillian as fa
sage: fa(2^6 + 1)
[5, 13]
sage: fa(2^58 + 1)
[536838145, 536903681]
sage: fa(3^3 + 1)
[4, 1, 7]
sage: fa(5^5 - 1)
[4, 11, 71]
sage: prod(_) == 5^5 - 1
True
sage: fa(2^4 + 1)
[17]
sage: fa((6^2*3)^3 + 1)
[109, 91, 127]
```

REFERENCES:

- <http://mathworld.wolfram.com/AurifeuilleanFactorization.html>
- [Bre1993] Theorem 3

`sage.rings.factorint.factor_cunningham(m, proof=None)`

Return factorization of `self` obtained using trial division for all primes in the so called Cunningham table. This is efficient if `self` has some factors of type $b^n + 1$ or $b^n - 1$, with b in $\{2, 3, 5, 6, 7, 10, 11, 12\}$.

You need to install an optional package to use this method, this can be done with the following command line:
`sage -i Cunningham_tables`.

INPUT:

- `proof` – boolean (default: `None`); whether or not to prove primality of each factor, this is only for factors not in the Cunningham table

EXAMPLES:

```
sage: from sage.rings.factorint import factor_cunningham
sage: factor_cunningham(2^257-1) # optional - cunningham_tables
535006138814359 * 1155685395246619182673033 *
    ↵374550598501810936581776630096313181393
sage: factor_cunningham((3^101+1)*(2^60).next_prime(), proof=False) # optional -
    ↵cunningham_tables
2^2 * 379963 * 1152921504606847009 * 1017291527198723292208309354658785077827527
```

`sage.rings.factorint.factor_trial_division(m, limit='LONG_MAX')`

Return partial factorization of `self` obtained using trial division for all primes up to `limit`, where `limit` must fit in a C signed long.

INPUT:

- `limit` – integer (default: `LONG_MAX`); that fits in a C signed long

EXAMPLES:

```
sage: from sage.rings.factorint import factor_trial_division
sage: n = 920384092842390423848290348203948092384082349082
sage: factor_trial_division(n, 1000)
2 * 11 * 41835640583745019265831379463815822381094652231
sage: factor_trial_division(n, 2000)
2 * 11 * 1531 * 27325696005058797691594630609938486205809701
```

1.6 Integer factorization using FLINT

AUTHORS:

- Michael Orlitzky (2023)

`sage.rings.factorint_flint.factor_using_flint(n)`

Factor the nonzero integer `n` using FLINT.

This function returns a list of (factor, exponent) pairs. The factors will be of type `Integer`, and the exponents will be of type `int`.

INPUT:

- `n` – a nonzero sage Integer; the number to factor

OUTPUT:

A list of (`Integer`, `int`) pairs representing the factors and their exponents.

EXAMPLES:

```
sage: from sage.rings.factorint_flint import factor_using_flint
sage: n = ZZ(9962572652930382)
sage: factors = factor_using_flint(n)
sage: factors
[(2, 1), (3, 1), (1660428775488397, 1)]
```

(continues on next page)

(continued from previous page)

```
sage: prod( f^e for (f,e) in factors ) == n
True

Negative numbers will have a leading factor of ``(-1)^1``:::

sage: n = ZZ(-1 * 2 * 3)
sage: factor_using_flint(n)
[(-1, 1), (2, 1), (3, 1)]
```

The factorization of unity is empty:

```
sage: factor_using_flint(ZZ.one())
[]
```

While zero has a single factor, of... zero:

```
sage: factor_using_flint(ZZ.zero())
[(0, 1)]
```

1.7 Integer factorization using PARI

AUTHORS:

- Jeroen Demeyer (2015)

```
sage.rings.factorint_pari.factor_using_pari(n, int_=False, debug_level=0, proof=None)
```

Factor this integer using PARI.

This function returns a list of pairs, not a `Factorization` object. The first element of each pair is the factor, of type `Integer` if `int_` is `False` or `int` otherwise, the second element is the positive exponent, of type `int`.

INPUT:

- `int_` – (default: `False`), whether the factors are of type `int` instead of `Integer`
- `debug_level` – (default: 0), debug level of the call to PARI
- `proof` – (default: `None`), whether the factors are required to be proven prime; if `None`, the global default is used

OUTPUT: list of pairs

EXAMPLES:

```
sage: factor(-2**72 + 3, algorithm='pari') # indirect doctest
-1 * 83 * 131 * 294971519 * 1472414939
```

Check that PARI's debug level is properly reset ([Issue #18792](#)):

```
sage: alarm(0.5); factor(2^1000 - 1, verbose=5)
Traceback (most recent call last):
...
AlarmInterrupt
sage: pari.get_debug_level()
0
```

1.8 Basic arithmetic with C integers

```
class sage.rings.fast_arith.arith_int
    Bases: object
        gcd_int(a, b)
        inverse_mod_int(a, m)
        rational_recon_int(a, m)
            Rational reconstruction of a modulo m.
        xgcd_int(a, b)

class sage.rings.fast_arith.arith_llong
    Bases: object
        gcd_llonglong(a, b)
        inverse_mod_llonglong(a, m)
        rational_recon_llonglong(a, m)
            Rational reconstruction of a modulo m.

sage.rings.fast_arith.prime_range(start, stop=None, algorithm=None, py_ints=False)
```

Return a list of all primes between start and stop – 1, inclusive.

If the second argument is omitted, this returns the primes up to the first argument.

The sage command [primes\(\)](#) is an alternative that uses less memory (but may be slower), because it returns an iterator, rather than building a list of the primes.

INPUT:

- start – integer; lower bound (default: 1)
- stop – integer; upper bound
- algorithm – string (default: None), one of:
 - None: Use algorithm 'pari_primes' if stop <= 436273009 (approximately 4.36E8). Otherwise use algorithm 'pari_isprime'.
 - 'pari_primes': Use PARI's `pari:primes` function to generate all primes from 2 to stop. This is fast but may crash if there is insufficient memory. Raises an error if stop > 436273009.
 - 'pari_isprime': Wrapper for `list(primes(start, stop))`. Each (odd) integer in the specified range is tested for primality by applying PARI's `pari:isprime` function. This is slower but will work for much larger input.
- py_ints – boolean (default: False); return Python ints rather than Sage Integers (faster). Ignored unless algorithm 'pari_primes' is being used.

EXAMPLES:

```
sage: prime_range(10)
[2, 3, 5, 7]
sage: prime_range(7)
[2, 3, 5]
sage: prime_range(2000,2020)
[2003, 2011, 2017]
```

(continues on next page)

(continued from previous page)

```
sage: prime_range(2,2)
[]
sage: prime_range(2,3)
[2]
sage: prime_range(5,10)
[5, 7]
sage: prime_range(-100,10,"pari_isprime")
[2, 3, 5, 7]
sage: prime_range(2,2,algorithm='pari_isprime')
[]
sage: prime_range(10**16,10**16+100,"pari_isprime")
[1000000000000061, 1000000000000069, 1000000000000079, 1000000000000099]
sage: prime_range(10**30,10**30+100,"pari_isprime")
[10000000000000000000000000000000057, 1000000000000000000000000000000099]
sage: type(prime_range(8)[0])
<class 'sage.rings.integer.Integer'>
sage: type(prime_range(8,algorithm='pari_isprime')[0])
<class 'sage.rings.integer.Integer'>
```

Note

`start` and `stop` should be integers, but real numbers will also be accepted as input. In this case, they will be rounded to nearby integers `start*` and `stop*`, so the output will be the primes between `start*` and `stop*` - 1, which may not be exactly the same as the primes between `start` and `stop` - 1.

AUTHORS:

- William Stein (original version)
- Craig Citro (rewrote for massive speedup)
- Kevin Stueve (added primes iterator option) 2010-10-16
- Robert Bradshaw (speedup using Pari prime table, `py_ints` option)

1.9 Fast decomposition of small integers into sums of squares

Implement fast version of decomposition of (small) integers into sum of squares by direct method not relying on factorisation.

AUTHORS:

- Vincent Delecroix (2014): first implementation ([Issue #16374](#))

```
sage.rings.sum_of_squares.four_squares_pyx(n)
```

Return a 4-tuple of nonnegative integers (i, j, k, l) such that $i^2 + j^2 + k^2 + l^2 = n$ and $i \leq j \leq k \leq l$.

The input must be less than $2^{32} = 4294967296$, otherwise an `OverflowError` is raised.

See also

`four_squares()` is much more suited for large input

EXAMPLES:

```
sage: from sage.rings.sum_of_squares import four_squares_pyx
sage: four_squares_pyx(15447)
(2, 5, 17, 123)
sage: 2^2 + 5^2 + 17^2 + 123^2
15447

sage: four_squares_pyx(523439)
(3, 5, 26, 723)
sage: 3^2 + 5^2 + 26^2 + 723^2
523439

sage: four_squares_pyx(2**32)
Traceback (most recent call last):
...
OverflowError: ...
```

`sage.rings.sum_of_squares.is_sum_of_two_squares_pyx(n)`

Return True if n is a sum of two squares and False otherwise.

The input must be smaller than $2^{32} = 4294967296$, otherwise an `OverflowError` is raised.

EXAMPLES:

```
sage: from sage.rings.sum_of_squares import is_sum_of_two_squares_pyx
sage: [x for x in range(30) if is_sum_of_two_squares_pyx(x)]
[0, 1, 2, 4, 5, 8, 9, 10, 13, 16, 17, 18, 20, 25, 26, 29]

sage: is_sum_of_two_squares_pyx(2**32)
Traceback (most recent call last):
...
OverflowError: ...
```

`sage.rings.sum_of_squares.three_squares_pyx(n)`

If n is a sum of three squares return a 3-tuple (i, j, k) of Sage integers such that $i^2 + j^2 + k^2 = n$ and $i \leq j \leq k$. Otherwise raise a `ValueError`.

The input must be less than $2^{32} = 4294967296$, otherwise an `OverflowError` is raised.

EXAMPLES:

```
sage: from sage.rings.sum_of_squares import three_squares_pyx
sage: three_squares_pyx(0)
(0, 0, 0)
sage: three_squares_pyx(1)
(0, 0, 1)
sage: three_squares_pyx(2)
(0, 1, 1)
sage: three_squares_pyx(3)
(1, 1, 1)
sage: three_squares_pyx(4)
(0, 0, 2)
sage: three_squares_pyx(5)
(0, 1, 2)
sage: three_squares_pyx(6)
(1, 1, 2)
sage: three_squares_pyx(7)
Traceback (most recent call last):
...

```

(continues on next page)

(continued from previous page)

```
ValueError: 7 is not a sum of 3 squares
sage: three_squares_pyx(107)
(1, 5, 9)

sage: three_squares_pyx(2**32)
Traceback (most recent call last):
...
OverflowError: ...
```

sage.rings.sum_of_squares.**two_squares_pyx**(n)

Return a pair of nonnegative integers (i, j) such that $i^2 + j^2 = n$.

If n is not a sum of two squares, a `ValueError` is raised. The input must be less than $2^{32} = 4294967296$, otherwise an `OverflowError` is raised.

See also

`two_squares()` is much more suited for large inputs

EXAMPLES:

```
sage: from sage.rings.sum_of_squares import two_squares_pyx
sage: two_squares_pyx(0)
(0, 0)
sage: two_squares_pyx(1)
(0, 1)
sage: two_squares_pyx(2)
(1, 1)
sage: two_squares_pyx(3)
Traceback (most recent call last):
...
ValueError: 3 is not a sum of 2 squares
sage: two_squares_pyx(106)
(5, 9)

sage: two_squares_pyx(2**32)
Traceback (most recent call last):
...
OverflowError: ...
```

1.10 Fast Arithmetic Functions

sage.arith.functions.**LCM_list**(v)

Return the LCM of an iterable v.

Elements of v are converted to Sage objects if they aren't already.

This function is used, e.g., by `lcm()`.

INPUT:

- v – an iterable

OUTPUT: integer

EXAMPLES:

```
sage: from sage.arith.functions import LCM_list
sage: w = LCM_list([3,9,30]); w
90
sage: type(w)
<class 'sage.rings.integer.Integer'>
```

The inputs are converted to Sage integers:

```
sage: w = LCM_list([int(3), int(9), int(30)]); w
90
sage: type(w)
<class 'sage.rings.integer.Integer'>
```

`sage.arith.functions.lcm(a, b=None)`

The least common multiple of a and b , or if a is a list and b is omitted the least common multiple of all elements of a .

Note that LCM is an alias for lcm.

INPUT:

- a, b – two elements of a ring with lcm or
- a – list; tuple or iterable of elements of a ring with lcm

OUTPUT:

First, the given elements are coerced into a common parent. Then, their least common multiple *in that parent* is returned.

EXAMPLES:

```
sage: lcm(97, 100)
9700
sage: LCM(97, 100)
9700
sage: LCM(0, 2)
0
sage: LCM(-3, -5)
15
sage: LCM([1,2,3,4,5])
60
sage: v = LCM(range(1, 10000))    # *very* fast!
sage: len(str(v))
4349
```

1.11 Generic implementation of powering

This implements powering of arbitrary objects using a square-and-multiply algorithm.

`sage.arith.power.generic_power(a, n)`

Return a^n .

If n is negative, return $(1/a)^{-n}$.

INPUT:

- a – any object supporting multiplication (and division if $n < 0$)
- n – any integer (in the duck typing sense)

EXAMPLES:

```
sage: from sage.arith.power import generic_power
sage: generic_power(int(12), int(0))
1
sage: generic_power(int(0), int(100))
0
sage: generic_power(Integer(10), Integer(0))
1
sage: generic_power(Integer(0), Integer(23))
0
sage: sum([generic_power(2,i) for i in range(17)]) #test all 4-bit combinations
131071
sage: F = Zmod(5)
sage: a = generic_power(F(2), 5); a
2
sage: a.parent() is F
True
sage: a = generic_power(F(1), 2)
sage: a.parent() is F
True

sage: generic_power(int(5), 0)
1
sage: generic_power(2, 5/4)
Traceback (most recent call last):
...
NotImplementedError: non-integral exponents not supported
```

```
sage: class SymbolicMul(str):
....:     def __mul__(self, other):
....:         s = "({}*{})".format(self, other)
....:         return type(self)(s)
sage: x = SymbolicMul("x")
sage: print(generic_power(x, 7))
(((x*x)*(x*x))*((x*x)*x))
```

1.12 Utility classes for multi-modular algorithms

class sage.arith.multi_modular.**MultiModularBasis**

Bases: *MultiModularBasis_base*

Class used for storing a MultiModular bases of a fixed length.

class sage.arith.multi_modular.**MultiModularBasis_base**

Bases: *object*

This class stores a list of machine-sized prime numbers, and can do reduction and Chinese Remainder Theorem lifting modulo these primes.

Lifting implemented via Garner's algorithm, which has the advantage that all reductions are word-sized. For each i , precompute $\prod_j = 1^{i-1} m_j$ and $\prod_j = 1^{i-1} m_j^{-1} (\bmod m_i)$.

This class can be initialized in two ways, either with a list of prime moduli or an upper bound for the product of the prime moduli. The prime moduli are generated automatically in the second case.

EXAMPLES:

```
sage: from sage.arith.multi_modular import MultiModularBasis_base
sage: mm = MultiModularBasis_base([3, 5, 7]); mm
MultiModularBasis with moduli [3, 5, 7]

sage: height = 52348798724
sage: mm = MultiModularBasis_base(height); mm
MultiModularBasis with moduli [...]
sage: mm.prod() >= 2*height
True
```

crt (b)

Calculate lift mod $\prod_{i=0}^{\text{len}(b)-1} m_i$.

In the case that offset > 0, z[j] remains unchanged mod $\prod_{i=0}^{\text{offset}-1} m_i$

INPUT:

- b – list of length at most self.n

OUTPUT:

Integer z where $z = b[i] \text{mod } m_i$ for $0 \leq i < \text{len}(b)$

EXAMPLES:

```
sage: from sage.arith.multi_modular import MultiModularBasis_base
sage: mm = MultiModularBasis_base([10007, 10009, 10037, 10039, 17351])
sage: res = mm.crt([3,5,7,9]); res
8474803647063985
sage: res % 10007
3
sage: res % 10009
5
sage: res % 10037
7
sage: res % 10039
9
```

extend_with_primes (plist, partial_products=None, check=True)

Extend the stored list of moduli with the given primes in plist.

EXAMPLES:

```
sage: from sage.arith.multi_modular import MultiModularBasis_base
sage: mm = MultiModularBasis_base([1009, 10007]); mm
MultiModularBasis with moduli [1009, 10007]
sage: mm.extend_with_primes([10037, 10039])
4
sage: mm
MultiModularBasis with moduli [1009, 10007, 10037, 10039]
```

list()

Return a list with the prime moduli.

EXAMPLES:

```
sage: from sage.arith.multi_modular import MultiModularBasis_base
sage: mm = MultiModularBasis_base([46307, 10007])
sage: mm.list()
[46307, 10007]
```

partial_product (n)

Return a list containing precomputed partial products.

EXAMPLES:

```
sage: from sage.arith.multi_modular import MultiModularBasis_base
sage: mm = MultiModularBasis_base([46307, 10007]); mm
MultiModularBasis with moduli [46307, 10007]
sage: mm.partial_product(0)
46307
sage: mm.partial_product(1)
463394149
```

precomputation_list ()

Return a list of the precomputed coefficients $\prod_j 1^{i-1} m_j^{-1} (mod m_i)$ where m_i are the prime moduli.

EXAMPLES:

```
sage: from sage.arith.multi_modular import MultiModularBasis_base
sage: mm = MultiModularBasis_base([46307, 10007]); mm
MultiModularBasis with moduli [46307, 10007]
sage: mm.precomputation_list()
[1, 4013]
```

prod()

Return the product of the prime moduli.

EXAMPLES:

```
sage: from sage.arith.multi_modular import MultiModularBasis_base
sage: mm = MultiModularBasis_base([46307]); mm
MultiModularBasis with moduli [46307]
sage: mm.prod()
46307
sage: mm = MultiModularBasis_base([46307, 10007]); mm
MultiModularBasis with moduli [46307, 10007]
sage: mm.prod()
463394149
```

class sage.arith.multi_modular.MutableMultiModularBasis

Bases: *MultiModularBasis*

Class used for performing multi-modular methods, with the possibility of removing bad primes.

next_prime()

Pick a new random prime between the bounds given during the initialization of this object, update the pre-computed data, and return the new prime modulus.

EXAMPLES:

```
sage: from sage.arith.multi_modular import MutableMultiModularBasis
sage: mm = MutableMultiModularBasis([10007])
```

(continues on next page)

(continued from previous page)

```
sage: p = mm.next_prime()
sage: 1024 < p < 32768
True
sage: p != 10007
True
sage: mm.list() == [10007, p]
True
```

replace_prime(ix)

Replace the prime moduli at the given index with a different one, update the precomputed data accordingly, and return the new prime.

INPUT:

- `ix` – index into list of moduli

OUTPUT: the new prime modulus

EXAMPLES:

```
sage: from sage.arith.multi_modular import MutableMultiModularBasis
sage: mm = MutableMultiModularBasis([10007, 10009, 10037, 10039])
sage: mm
MultiModularBasis with moduli [10007, 10009, 10037, 10039]
sage: prev_prod = mm.prod(); prev_prod
10092272478850909
sage: mm.precomputation_list()
[1, 5004, 6536, 6060]
sage: mm.partial_product(2)
1005306552331
sage: p = mm.replace_prime(1)
sage: mm.list() == [10007, p, 10037, 10039]
True
sage: mm.prod()*10009 == prev_prod*p
True
sage: precomputed = mm.precomputation_list()
sage: precomputed == [prod(Integers(mm[i])(1 / mm[j]))
....:                   for j in range(i)]
....:                   for i in range(4)]
True
sage: mm.partial_product(2) == prod(mm.list()[:3])
True
```

1.13 Miscellaneous arithmetic functions

AUTHORS:

- Kevin Stueve (2010-01-17): `in is_prime(n)`, delegated calculation to `n.is_prime()`

```
sage.arith.misc.CRT(a, b, m=None, n=None)
```

Return a solution to a Chinese Remainder Theorem problem.

INPUT:

- `a, b` – two residues (elements of some ring for which extended gcd is available), or two lists, one of residues and one of moduli

- m, n – (default: `None`) two moduli, or `None`

OUTPUT:

If m, n are not `None`, returns a solution x to the simultaneous congruences $x \equiv a \pmod{m}$ and $x \equiv b \pmod{n}$, if one exists. By the Chinese Remainder Theorem, a solution to the simultaneous congruences exists if and only if $a \equiv b \pmod{\gcd(m, n)}$. The solution x is only well-defined modulo $\text{lcm}(m, n)$.

If a and b are lists, returns a simultaneous solution to the congruences $x \equiv a_i \pmod{b_i}$, if one exists.

See also

- `CRT_list()`

EXAMPLES:

Using `crt` by giving it pairs of residues and moduli:

```
sage: crt(2, 1, 3, 5)
11
sage: crt(13, 20, 100, 301)
28013
sage: crt([2, 1], [3, 5])
11
sage: crt([13, 20], [100, 301])
28013
```

You can also use upper case:

```
sage: c = CRT(2, 3, 3, 5); c
8
sage: c % 3 == 2
True
sage: c % 5 == 3
True
```

Note that this also works for polynomial rings:

```
sage: # needs sage.rings.number_field
sage: x = polygen(ZZ, 'x')
sage: K.<a> = NumberField(x^3 - 7)
sage: R.<y> = K[]
sage: f = y^2 + 3
sage: g = y^3 - 5
sage: CRT(1, 3, f, g)
-3/26*y^4 + 5/26*y^3 + 15/26*y + 53/26
sage: CRT(1, a, f, g)
(-3/52*a + 3/52)*y^4 + (5/52*a - 5/52)*y^3 + (15/52*a - 15/52)*y + 27/52*a + 25/52
```

You can also do this for any number of moduli:

```
sage: # needs sage.rings.number_field
sage: K.<a> = NumberField(x^3 - 7)
sage: R.<x> = K[]
sage: CRT([], [])
0
sage: CRT([a], [x])
```

(continues on next page)

(continued from previous page)

```
a
sage: f = x^2 + 3
sage: g = x^3 - 5
sage: h = x^5 + x^2 - 9
sage: k = CRT([1, a, 3], [f, g, h]); k
(127/26988*a - 5807/386828)*x^9 + (45/8996*a - 33677/1160484)*x^8
+ (2/173*a - 6/173)*x^7 + (133/6747*a - 5373/96707)*x^6
+ (-6/2249*a + 18584/290121)*x^5 + (-277/8996*a + 38847/386828)*x^4
+ (-135/4498*a + 42673/193414)*x^3 + (-1005/8996*a + 470245/1160484)*x^2
+ (-1215/8996*a + 141165/386828)*x + 621/8996*a + 836445/386828
sage: k.mod(f)
1
sage: k.mod(g)
a
sage: k.mod(h)
3
```

If the moduli are not coprime, a solution may not exist:

```
sage: crt(4, 8, 8, 12)
20
sage: crt(4, 6, 8, 12)
Traceback (most recent call last):
...
ValueError: no solution to crt problem since gcd(8,12) does not divide 4-6

sage: x = polygen(QQ)
sage: crt(2, 3, x - 1, x + 1)
-1/2*x + 5/2
sage: crt(2, x, x^2 - 1, x^2 + 1)
-1/2*x^3 + x^2 + 1/2*x + 1
sage: crt(2, x, x^2 - 1, x^3 - 1)
Traceback (most recent call last):
...
ValueError: no solution to crt problem since gcd(x^2 - 1,x^3 - 1) does not divide
 ↴2-x

sage: crt(int(2), int(3), int(7), int(11))
58
```

crt also work with numpy and gmpy2 numbers:

```
sage: import numpy
needs numpy
sage: crt(numpy.int8(2), numpy.int8(3), numpy.int8(7), numpy.int8(11))
needs numpy
58
sage: from gmpy2 import mpz
sage: crt(mpz(2), mpz(3), mpz(7), mpz(11))
58
sage: crt(mpz(2), 3, mpz(7), numpy.int8(11))
needs numpy
58
```

`sage.arith.misc.CRT_basis(moduli)`

Return a CRT basis for the given moduli.

INPUT:

- `moduli` – list of pairwise coprime moduli m which admit an extended Euclidean algorithm

OUTPUT:

- a list of elements a_i of the same length as m such that a_i is congruent to 1 modulo m_i and to 0 modulo m_j for $j \neq i$.

EXAMPLES:

```
sage: a1 = ZZ(mod(42,5))
sage: a2 = ZZ(mod(42,13))
sage: c1,c2 = CRT_basis([5,13])
sage: mod(a1*c1+a2*c2,5*13)
42
```

A polynomial example:

```
sage: x=polygen(QQ)
sage: mods = [x,x^2+1,2*x-3]
sage: b = CRT_basis(mods)
sage: b
[-2/3*x^3 + x^2 - 2/3*x + 1, 6/13*x^3 - x^2 + 6/13*x, 8/39*x^3 + 8/39*x]
sage: [[bi % mj for mj in mods] for bi in b]
[[1, 0, 0], [0, 1, 0], [0, 0, 1]]
```

`sage.arith.misc.CRT_list(values, moduli)`

Given a list `values` of elements and a list of corresponding `moduli`, find a single element that reduces to each element of `values` modulo the corresponding `moduli`.

See also

- `crt()`

EXAMPLES:

```
sage: CRT_list([2,3,2], [3,5,7])
23
sage: x = polygen(QQ)
sage: c = CRT_list([3], [x]); c
3
sage: c.parent()
Univariate Polynomial Ring in x over Rational Field
```

It also works if the moduli are not coprime:

```
sage: CRT_list([32,2,2],[60,90,150])
452
```

But with non coprime moduli there is not always a solution:

```
sage: CRT_list([32,2,1],[60,90,150])
Traceback (most recent call last):
...
ValueError: no solution to crt problem since gcd(180,150) does not divide 92-1
```

The arguments must be lists:

```
sage: CRT_list([1,2,3],"not a list")
Traceback (most recent call last):
...
ValueError: arguments to CRT_list should be lists
sage: CRT_list("not a list",[2,3])
Traceback (most recent call last):
...
ValueError: arguments to CRT_list should be lists
```

The list of moduli must have the same length as the list of elements:

```
sage: CRT_list([1,2,3],[2,3,5])
23
sage: CRT_list([1,2,3],[2,3])
Traceback (most recent call last):
...
ValueError: arguments to CRT_list should be lists of the same length
sage: CRT_list([1,2,3],[2,3,5,7])
Traceback (most recent call last):
...
ValueError: arguments to CRT_list should be lists of the same length
```

`sage.arith.misc.CRT_vectors(X, moduli)`

Vector form of the Chinese Remainder Theorem: given a list of integer vectors v_i and a list of coprime moduli m_i , find a vector w such that $w = v_i \pmod{m_i}$ for all i . This is more efficient than applying `CRT()` to each entry.

INPUT:

- `X` – list or tuple, consisting of lists/tuples/vectors/etc of integers of the same length
- `moduli` – list of `len(X)` moduli

OUTPUT: list; application of CRT componentwise

EXAMPLES:

```
sage: CRT_vectors([[3,5,7],[3,5,11]], [2,3])
[3, 5, 5]

sage: CRT_vectors([vector(ZZ, [2,3,1]), Sequence([1,7,8], ZZ)], [8,9])      #_
  ↵needs sage.modules
[10, 43, 17]
```

`class sage.arith.misc.Euler_Phi`

Bases: `object`

Return the value of the Euler phi function on the integer n . We defined this to be the number of positive integers $\leq n$ that are relatively prime to n . Thus if $n \leq 0$ then `euler_phi(n)` is defined and equals 0.

INPUT:

- `n` – integer

EXAMPLES:

```
sage: euler_phi(1)
1
sage: euler_phi(2)
1
sage: euler_phi(3)      #_

```

(continues on next page)

(continued from previous page)

```

↳needs sage.libs.pari
2
sage: euler_phi(12)                                     #_
↳needs sage.libs.pari
4
sage: euler_phi(37)                                     #_
↳needs sage.libs.pari
36

```

Notice that `euler_phi` is defined to be 0 on negative numbers and 0:

```

sage: euler_phi(-1)
0
sage: euler_phi(0)
0
sage: type(euler_phi(0))
<class 'sage.rings.integer.Integer'>

```

We verify directly that the phi function is correct for 21:

```

sage: euler_phi(21)                                     #_
↳needs sage.libs.pari
12
sage: [i for i in range(21) if gcd(21,i) == 1]
[1, 2, 4, 5, 8, 10, 11, 13, 16, 17, 19, 20]

```

The length of the list of integers ‘i’ in `range(n)` such that the $\gcd(i, n) == 1$ equals `euler_phi(n)`:

```

sage: len([i for i in range(21) if gcd(21,i) == 1]) == euler_phi(21)      #_
↳needs sage.libs.pari
True

```

The phi function also has a special plotting method:

```

sage: P = plot(euler_phi, -3, 71)                                     #_
↳needs sage.libs.pari sage.plot

```

Tests with numpy and gmpy2 numbers:

```

sage: from numpy import int8                                     #_
↳needs numpy
sage: euler_phi(int8(37))                                     #_
↳needs numpy sage.libs.pari
36
sage: from gmpy2 import mpz                                     #_
sage: euler_phi(mpz(37))                                     #_
↳needs sage.libs.pari
36

```

AUTHORS:

- William Stein
- Alex Clemesha (2006-01-10): some examples

`plot(xmin=1, xmax=50, pointsize=30, rbgcolor=(0, 0, 1), join=True, **kwds)`

Plot the Euler phi function.

INPUT:

- `xmin` – (default: 1)
- `xmax` – (default: 50)
- `pointsize` – (default: 30)
- `rgbcolor` – (default: (0,0,1))
- `join` – boolean (default: `True`); whether to join the points
- `**kwds` – passed on

EXAMPLES:

```
sage: from sage.arith.misc import Euler_Phi
sage: p = Euler_Phi().plot() #_
  ↳needs sage.libs.pari sage.plot
sage: p.ymax() #_
  ↳needs sage.libs.pari sage.plot
46.0
```

`sage.arith.misc.GCD(a, b=None, **kwargs)`

Return the greatest common divisor of `a` and `b`.

If `a` is a list and `b` is omitted, return instead the greatest common divisor of all elements of `a`.

INPUT:

- `a, b` – two elements of a ring with gcd or
- `a` – list or tuple of elements of a ring with gcd

Additional keyword arguments are passed to the respectively called methods.

OUTPUT:

The given elements are first coerced into a common parent. Then, their greatest common divisor *in that common parent* is returned.

EXAMPLES:

```
sage: GCD(97, 100)
1
sage: GCD(97*10^15, 19^20*97^2)
97
sage: GCD(2/3, 4/5)
2/15
sage: GCD([2, 4, 6, 8])
2
sage: GCD(srange(0, 10000, 10)) # fast !!
10
```

Note that to take the gcd of n elements for $n \neq 2$ you must put the elements into a list by enclosing them in `[...]`. Before Issue #4988 the following wrongly returned 3 since the third parameter was just ignored:

```
sage: gcd(3, 6, 2)
Traceback (most recent call last):
...
TypeError: ...gcd() takes ...
sage: gcd([3, 6, 2])
1
```

Similarly, giving just one element (which is not a list) gives an error:

```
sage: gcd(3)
Traceback (most recent call last):
...
TypeError: 'sage.rings.integer.Integer' object is not iterable
```

By convention, the gcd of the empty list is (the integer) 0:

```
sage: gcd([])
0
sage: type(gcd([]))
<class 'sage.rings.integer.Integer'>
```

class sage.arith.misc.Möbius

Bases: object

Return the value of the Möbius function of $\text{abs}(n)$, where n is an integer.

DEFINITION: $\mu(n)$ is 0 if n is not square free, and otherwise equals $(-1)^r$, where n has r distinct prime factors.

For simplicity, if $n = 0$ we define $\mu(n) = 0$.

IMPLEMENTATION: Factors or - for integers - uses the PARI C library.

INPUT:

- n – anything that can be factored

OUTPUT: 0, 1, or -1

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: moebius(-5)
-1
sage: moebius(9)
0
sage: moebius(12)
0
sage: moebius(-35)
1
sage: moebius(-1)
1
sage: moebius(7)
-1
```

```
sage: moebius(0)      # potentially nonstandard!
0
```

The moebius function even makes sense for non-integer inputs.

```
sage: x = GF(7) ['x'].0
sage: moebius(x + 2)                                     #
needs sage.libs.pari
-1
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8                                #
needs numpy
```

(continues on next page)

(continued from previous page)

```
sage: moebius(int8(-5))
↳ needs numpy sage.libs.pari
-1
sage: from gmpy2 import mpz
sage: moebius(mpz(-5))
↳ needs sage.libs.pari
-1
```

plot (*xmin=0, xmax=50, pointsize=30, rgbcolor=(0, 0, 1), join=True, **kwds*)

Plot the Möbius function.

INPUT:

- `xmin` – (default: 0)
- `xmax` – (default: 50)
- `pointsize` – (default: 30)
- `rgbcolor` – (default: (0,0,1))
- **`join` – (default: True) whether to join the points**
(very helpful in seeing their order)
- `**kwds` – passed on

EXAMPLES:

```
sage: from sage.arith.misc import Moebius
sage: p = Moebius().plot()
↳ needs sage.libs.pari sage.plot
sage: p.ymax()
↳ needs sage.libs.pari sage.plot
1.0
```

range (*start, stop=None, step=None*)

Return the Möbius function evaluated at the given range of values, i.e., the image of the list `range(start, stop, step)` under the Möbius function.

This is much faster than directly computing all these values with a list comprehension.

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: v = moebius.range(-10, 10); v
[1, 0, 0, -1, 1, -1, 0, -1, -1, 1, 0, 1, -1, -1, 0, -1, 1, -1, 0, 0]
sage: v == [moebius(n) for n in range(-10, 10)]
True
sage: v = moebius.range(-1000, 2000, 4)
sage: v == [moebius(n) for n in range(-1000, 2000, 4)]
True
```

class sage.arith.misc.Sigma

Bases: object

Return the sum of the k -th powers of the divisors of n .

INPUT:

- `n` – integer

- `k` – integer (default: 1)

OUTPUT: integer

EXAMPLES:

```
sage: sigma(5)
6
sage: sigma(5,2)
26
```

The `sigma` function also has a special plotting method.

```
sage: P = plot(sigma, 1, 100)
needs sage.plot
```

#

This method also works with k -th powers.

```
sage: P = plot(sigma, 1, 100, k=2)
needs sage.plot
```

#

AUTHORS:

- William Stein: original implementation
- Craig Citro (2007-06-01): rewrote for huge speedup

`plot` ($xmin=1$, $xmax=50$, $k=1$, $pointsize=30$, $rgbcolor=(0, 0, 1)$, $join=True$, **kwds)

Plot the σ_k (sum of k -th powers of divisors) function.

INPUT:

- `xmin` – (default: 1)
- `xmax` – (default: 50)
- `k` – (default: 1)
- `pointsize` – (default: 30)
- `rgbcolor` – (default: (0,0,1))
- `join` – (default: `True`) whether to join the points
- `*kwds` – passed on

EXAMPLES:

```
sage: from sage.arith.misc import Sigma
sage: p = Sigma().plot()
needs sage.libs.pari sage.plot
sage: p.ymax()
needs sage.libs.pari sage.plot
124.0
```

#

#

`sage.arith.misc.XGCD` (a , $b=None$)

Return the greatest common divisor and the Bézout coefficients of the input arguments.

When both `a` and `b` are given, then return a triple (g, s, t) such that $g = s \cdot a + t \cdot b = \gcd(a, b)$. When only `a` is given, then return a tuple `r` of length `len(a) + 1` such that $r_0 = \sum_{i=0}^{\text{len}(a)-1} r_{i+1} a_i = \gcd(a_0, \dots, a_{\text{len}(a)-1})$

Note

One exception is if the elements are not in a principal ideal domain (see [Wikipedia article Principal_ideal_domain](#)), e.g., they are both polynomials over the integers. Then this function can't in general return (g, s, t) or r as above, since they need not exist. Instead, over the integers, when a and b are given, we first multiply g by a divisor of the resultant of a/g and b/g , up to sign.

INPUT:

One of the following:

- a, b – integers or more generally, element of a ring for which the `xgcd` make sense (e.g. a field or univariate polynomials).
- a – a list or tuple of at least two integers or more generally, elements of a ring which the `xgcd` make sense.

OUTPUT:

One of the following:

- g, s, t – when two inputs a, b are given. They satisfy $g = s \cdot a + t \cdot b$.
- r – a tuple, when only a is given (and $b = \text{None}$). Its first entry $r[0]$ is the gcd of the inputs, and has length one longer than the length of a . Its entries satisfy $r_0 = \sum_{i=0}^{\text{len}(a)-1} r_{i+1} a_i$.

Note

There is no guarantee that the returned cofactors (s and t) are minimal.

EXAMPLES:

```
sage: xgcd(56, 44)
(4, 4, -5)
sage: 4*56 + (-5)*44
4
sage: xgcd([56, 44])
(4, 4, -5)
sage: r = xgcd([30, 105, 70, 42]); r
(1, -255, 85, -17, -2)
sage: (-255)*30 + 85*105 + (-17)*70 + (-2)*42
1
sage: xgcd([])
(0, )
sage: xgcd([42])
(42, 1)

sage: g, a, b = xgcd(5/1, 7/1); g, a, b
(1, 3, -2)
sage: a*(5/1) + b*(7/1) == g
True

sage: x = polygen(QQ)
sage: xgcd(x^3 - 1, x^2 - 1)
(x - 1, 1, -x)
sage: g, a, b, c = xgcd([x^4 - x, x^6 - 1, x^4 - 1]); g, a, b, c
(x - 1, x^3, -x, 1)
sage: a*(x^4 - x) + b*(x^6 - 1) + c*(x^4 - 1) == g
```

(continues on next page)

(continued from previous page)

True

```
sage: K.<g> = NumberField(x^2 - 3) #_
˓needs sage.rings.number_field
sage: g.xgcd(g + 2) #_
˓needs sage.rings.number_field
(1, 1/3*g, 0)

sage: # needs sage.rings.number_field
sage: R.<a,b> = K[]
sage: S.<y> = R.fraction_field() []
sage: xgcd(y^2, a*y + b)
(1, a^2/b^2, ((-a)/b^2)*y + 1/b)
sage: xgcd((b+g)*y^2, (a+g)*y + b)
(1, (a^2 + (2*g)*a + 3)/(b^3 + g*b^2), ((-a + (-g))/b^2)*y + 1/b)
```

Here is an example of a xgcd for two polynomials over the integers, where the linear combination is not the gcd but the gcd multiplied by the resultant:

```
sage: R.<x> = ZZ[]
sage: gcd(2*x*(x-1), x^2)
x
sage: xgcd(2*x*(x-1), x^2)
(2*x, -1, 2)
sage: (2*(x-1)).resultant(x) #_
˓needs sage.libs.pari
2
```

Tests with numpy and gmpy2 types:

```
sage: from numpy import int8 #_
˓needs numpy
sage: xgcd(4, int8(8)) #_
˓needs numpy
(4, 1, 0)
sage: xgcd(int8(4), int8(8)) #_
˓needs numpy
(4, 1, 0)
sage: xgcd([int8(4), int8(8), int(10)]) #_
˓needs numpy
(2, -2, 0, 1)
sage: from gmpy2 import mpz
sage: xgcd(mpz(4), mpz(8)) #_
(4, 1, 0)
sage: xgcd(4, mpz(8)) #_
(4, 1, 0)
sage: xgcd([4, mpz(8), mpz(10)]) #_
(2, -2, 0, 1)
```

```
sage.arith.misc.algdep(z, degree, known_bits=None, use_bits=None, known_digits=None, use_digits=None,
height_bound=None, proof=False)
```

Return an irreducible polynomial of degree at most *degree* which is approximately satisfied by the number *z*.

You can specify the number of known bits or digits of *z* with *known_bits=k* or *known_digits=k*. PARI is then told to compute the result using $0.8k$ of these bits/digits. Or, you can specify the precision to use directly with *use_bits=k* or *use_digits=k*. If none of these are specified, then the precision is taken from the input value.

A height bound may be specified to indicate the maximum coefficient size of the returned polynomial; if a sufficiently small polynomial is not found, then `None` will be returned. If `proof=True` then the result is returned only if it can be proved correct (i.e. the only possible minimal polynomial satisfying the height bound, or no such polynomial exists). Otherwise a `ValueError` is raised indicating that higher precision is required.

ALGORITHM: Uses LLL for real/complex inputs, PARI C-library `algdep` command otherwise.

Note that `algebraic_dependency` is a synonym for `algdep`.

INPUT:

- `z` – real, complex, or p -adic number
- `degree` – integer
- `height_bound` – integer (default: `None`); specifying the maximum coefficient size for the returned polynomial
- `proof` – boolean (default: `False`); requires `height_bound` to be set

EXAMPLES:

```
sage: algdep(1.888888888888888, 1) #_
˓needs sage.libs.pari
9*x - 17
sage: algdep(0.12121212121212, 1) #_
˓needs sage.libs.pari
33*x - 4
sage: algdep(sqrt(2), 2) #_
˓needs sage.libs.pari sage.symbolic
x^2 - 2
```

This example involves a complex number:

```
sage: z = (1/2) * (1 + RDF(sqrt(3)) * CC.0); z #_
˓needs sage.symbolic
0.500000000000000 + 0.866025403784439*I
sage: algdep(z, 6) #_
˓needs sage.symbolic
x^2 - x + 1
```

This example involves a p -adic number:

```
sage: K = Qp(3, print_mode='series') #_
˓needs sage.rings.padics
sage: a = K(7/19); a #_
˓needs sage.rings.padics
1 + 2*3 + 3^2 + 3^3 + 2*3^4 + 2*3^5 + 3^8 + 2*3^9 + 3^11 + 3^12 + 2*3^15 + 2*3^16
˓+ 3^17 + 2*3^19 + O(3^20)
sage: algdep(a, 1) #_
˓needs sage.rings.padics
19*x - 7
```

These examples show the importance of proper precision control. We compute a 200-bit approximation to `sqrt(2)` which is wrong in the 33rd bit:

```
sage: # needs sage.libs.pari sage.rings.real_mpfr
sage: z = sqrt(RealField(200)(2)) + (1/2)^33
sage: p = algdep(z, 4); p
227004321085*x^4 - 216947902586*x^3 - 99411220986*x^2 + 82234881648*x -_
˓
(continues on next page)
```

(continued from previous page)

```

↳211871195088
sage: factor(p)
227004321085*x^4 - 216947902586*x^3 - 99411220986*x^2 + 82234881648*x -_
↳211871195088
sage: algdep(z, 4, known_bits=32)
x^2 - 2
sage: algdep(z, 4, known_digits=10)
x^2 - 2
sage: algdep(z, 4, use_bits=25)
x^2 - 2
sage: algdep(z, 4, use_digits=8)
x^2 - 2

```

Using the `height_bound` and `proof` parameters, we can see that π is not the root of an integer polynomial of degree at most 5 and coefficients bounded above by 10:

```

sage: algdep(pi.n(), 5, height_bound=10, proof=True) is None
#_
↳needs sage.libs.pari sage.symbolic
True

```

For stronger results, we need more precision:

```

sage: # needs sage.libs.pari sage.symbolic
sage: algdep(pi.n(), 5, height_bound=100, proof=True) is None
Traceback (most recent call last):
...
ValueError: insufficient precision for non-existence proof
sage: algdep(pi.n(200), 5, height_bound=100, proof=True) is None
True
sage: algdep(pi.n(), 10, height_bound=10, proof=True) is None
Traceback (most recent call last):
...
ValueError: insufficient precision for non-existence proof
sage: algdep(pi.n(200), 10, height_bound=10, proof=True) is None
True

```

We can also use `proof=True` to get positive results:

```

sage: # needs sage.libs.pari sage.symbolic
sage: a = sqrt(2) + sqrt(3) + sqrt(5)
sage: algdep(a.n(), 8, height_bound=1000, proof=True)
Traceback (most recent call last):
...
ValueError: insufficient precision for uniqueness proof
sage: f = algdep(a.n(1000), 8, height_bound=1000, proof=True); f
x^8 - 40*x^6 + 352*x^4 - 960*x^2 + 576
sage: f(a).expand()
0

```

```

sage.arith.misc.algebraic_dependency(z, degree, known_bits=None, use_bits=None,
                                         known_digits=None, use_digits=None, height_bound=None,
                                         proof=False)

```

Return an irreducible polynomial of degree at most `degree` which is approximately satisfied by the number z .

You can specify the number of known bits or digits of z with `known_bits=k` or `known_digits=k`. PARI is then told to compute the result using $0.8k$ of these bits/digits. Or, you can specify the precision to use directly

with `use_bits=k` or `use_digits=k`. If none of these are specified, then the precision is taken from the input value.

A height bound may be specified to indicate the maximum coefficient size of the returned polynomial; if a sufficiently small polynomial is not found, then `None` will be returned. If `proof=True` then the result is returned only if it can be proved correct (i.e. the only possible minimal polynomial satisfying the height bound, or no such polynomial exists). Otherwise a `ValueError` is raised indicating that higher precision is required.

ALGORITHM: Uses LLL for real/complex inputs, PARI C-library `algdep` command otherwise.

Note that `algebraic_dependency` is a synonym for `algdep`.

INPUT:

- `z` – real, complex, or p -adic number
- `degree` – integer
- `height_bound` – integer (default: `None`); specifying the maximum coefficient size for the returned polynomial
- `proof` – boolean (default: `False`); requires `height_bound` to be set

EXAMPLES:

```
sage: algdep(1.8888888888888888, 1) #_
˓needs sage.libs.pari
9*x - 17
sage: algdep(0.1212121212121212, 1) #_
˓needs sage.libs.pari
33*x - 4
sage: algdep(sqrt(2), 2) #_
˓needs sage.libs.pari sage.symbolic
x^2 - 2
```

This example involves a complex number:

```
sage: z = (1/2) * (1 + RDF(sqrt(3)) * CC.0); z #_
˓needs sage.symbolic
0.500000000000000 + 0.866025403784439*I
sage: algdep(z, 6) #_
˓needs sage.symbolic
x^2 - x + 1
```

This example involves a p -adic number:

```
sage: K = Qp(3, print_mode='series') #_
˓needs sage.rings.padics
sage: a = K(7/19); a #_
˓needs sage.rings.padics
1 + 2*3 + 3^2 + 3^3 + 2*3^4 + 2*3^5 + 3^8 + 2*3^9 + 3^11 + 3^12 + 2*3^15 + 2*3^16
˓+ 3^17 + 2*3^19 + O(3^20)
sage: algdep(a, 1) #_
˓needs sage.rings.padics
19*x - 7
```

These examples show the importance of proper precision control. We compute a 200-bit approximation to $\sqrt{2}$ which is wrong in the 33rd bit:

```
sage: # needs sage.libs.pari sage.rings.real_mpfr
sage: z = sqrt(RealField(200)(2)) + (1/2)^33
sage: p = algdep(z, 4); p
227004321085*x^4 - 216947902586*x^3 - 99411220986*x^2 + 82234881648*x - 211871195088
sage: factor(p)
227004321085*x^4 - 216947902586*x^3 - 99411220986*x^2 + 82234881648*x - 211871195088
sage: algdep(z, 4, known_bits=32)
x^2 - 2
sage: algdep(z, 4, known_digits=10)
x^2 - 2
sage: algdep(z, 4, use_bits=25)
x^2 - 2
sage: algdep(z, 4, use_digits=8)
x^2 - 2
```

Using the `height_bound` and `proof` parameters, we can see that π is not the root of an integer polynomial of degree at most 5 and coefficients bounded above by 10:

```
sage: algdep(pi.n(), 5, height_bound=10, proof=True) is None
# needs sage.libs.pari sage.symbolic
True
```

For stronger results, we need more precision:

```
sage: # needs sage.libs.pari sage.symbolic
sage: algdep(pi.n(), 5, height_bound=100, proof=True) is None
Traceback (most recent call last):
...
ValueError: insufficient precision for non-existence proof
sage: algdep(pi.n(200), 5, height_bound=100, proof=True) is None
True
sage: algdep(pi.n(), 10, height_bound=10, proof=True) is None
Traceback (most recent call last):
...
ValueError: insufficient precision for non-existence proof
sage: algdep(pi.n(200), 10, height_bound=10, proof=True) is None
True
```

We can also use `proof=True` to get positive results:

```
sage: # needs sage.libs.pari sage.symbolic
sage: a = sqrt(2) + sqrt(3) + sqrt(5)
sage: algdep(a.n(), 8, height_bound=1000, proof=True)
Traceback (most recent call last):
...
ValueError: insufficient precision for uniqueness proof
sage: f = algdep(a.n(1000), 8, height_bound=1000, proof=True); f
x^8 - 40*x^6 + 352*x^4 - 960*x^2 + 576
sage: f(a).expand()
0
```

`sage.arith.misc.bernoulli(n, algorithm='default', num_threads=1)`

Return the n -th Bernoulli number, as a rational number.

INPUT:

- `n` – integer
- algorithm:
 - ‘`default`’ – use ‘`flint`’ for $n \leq 20000$, then ‘`arb`’ for $n \leq 300000$ and ‘`bernmm`’ for larger values (this is just a heuristic, and not guaranteed to be optimal on all hardware)
 - ‘`arb`’ – use the `bernoulli_fmpq_ui` function (formerly part of Arb) of the FLINT library
 - ‘`flint`’ – use the `arith_bernoulli_number` function of the FLINT library
 - ‘`pari`’ – use the PARI C library
 - ‘`gap`’ – use GAP
 - ‘`gp`’ – use PARI/GP interpreter
 - ‘`magma`’ – use MAGMA (optional)
 - ‘`bernmm`’ – use bernmm package (a multimodular algorithm)
- `num_threads` – positive integer, number of threads to use (only used for bernmm algorithm)

EXAMPLES:

```
sage: bernoulli(12)
˓needs sage.libs.flint
-691/2730
sage: bernoulli(50)
˓needs sage.libs.flint
495057205241079648212477525/66
```

We demonstrate each of the alternative algorithms:

```
sage: bernoulli(12, algorithm='arb')
˓needs sage.libs.flint
-691/2730
sage: bernoulli(12, algorithm='flint')
˓needs sage.libs.flint
-691/2730
sage: bernoulli(12, algorithm='gap')
˓needs sage.libs.gap
-691/2730
sage: bernoulli(12, algorithm='gp')
˓needs sage.libs.pari
-691/2730
sage: bernoulli(12, algorithm='magma')          # optional - magma
-691/2730
sage: bernoulli(12, algorithm='pari')
˓needs sage.libs.pari
-691/2730
sage: bernoulli(12, algorithm='bernmm')
˓needs sage.libs.ntl
-691/2730
sage: bernoulli(12, algorithm='bernmm', num_threads=4)
˓needs sage.libs.ntl
-691/2730
```

AUTHOR:

- David Joyner and William Stein

`sage.arith.misc.binomial(x, m, **kwds)`

Return the binomial coefficient.

$$\binom{x}{m} = x(x-1)\cdots(x-m+1)/m!$$

which is defined for $m \in \mathbf{Z}$ and any x . We extend this definition to include cases when $x - m$ is an integer but m is not by

$$\binom{x}{m} = \binom{x}{x-m}$$

If $m < 0$, return 0.

INPUT:

- x, m – numbers or symbolic expressions; either m or $x-m$ must be an integer

OUTPUT: number or symbolic expression (if input is symbolic)

EXAMPLES:

```

sage: from sage.arith.misc import binomial
sage: binomial(5, 2)
10
sage: binomial(2, 0)
1
sage: binomial(1/2, 0)                                              #_
˓needs sage.libs.pari
1
sage: binomial(3, -1)
0
sage: binomial(20, 10)
184756
sage: binomial(-2, 5)
-6
sage: binomial(-5, -2)
0
sage: binomial(RealField()('2.5'), 2)                                #_
˓needs sage.rings.real_mpfr
1.87500000000000
sage: binomial(Zp(5)(99), 50)
3 + 4*5^3 + 2*5^4 + 4*5^5 + 4*5^6 + 4*5^7 + 4*5^8 + 5^9 + 2*5^10 + 3*5^11 +
4*5^12 + 4*5^13 + 2*5^14 + 3*5^15 + 3*5^16 + 4*5^17 + 4*5^18 + 2*5^19 + O(5^20)
sage: binomial(Qp(3)(2/3), 2)
2*3^-2 + 2*3^-1 + 2 + 2*3 + 2*3^2 + 2*3^3 + 2*3^4 + 2*3^5 + 2*3^6 + 2*3^7 +
2*3^8 + 2*3^9 + 2*3^10 + 2*3^11 + 2*3^12 + 2*3^13 + 2*3^14 + 2*3^15 + 2*3^16 +_
˓2*3^17 + O(3^18)
sage: n = var('n'); binomial(n, 2)                                     #_
˓needs sage.symbolic
1/2*(n - 1)*n
sage: n = var('n'); binomial(n, n)                                     #_
˓needs sage.symbolic
1
sage: n = var('n'); binomial(n, n - 1)                                 #_
˓needs sage.symbolic
n
sage: binomial(2^100, 2^100)
1

```

(continues on next page)

(continued from previous page)

```
sage: x = polygen(ZZ)
sage: binomial(x, 3)
1/6*x^3 - 1/2*x^2 + 1/3*x
sage: binomial(x, x - 3)
1/6*x^3 - 1/2*x^2 + 1/3*x
```

If $x \in \mathbf{Z}$, there is an optional ‘algorithm’ parameter, which can be ‘gmp’ (faster for small values; alias: ‘mpir’) or ‘pari’ (faster for large values):

```
sage: a = binomial(100, 45, algorithm='gmp')
sage: b = binomial(100, 45, algorithm='pari') #_
˓needs sage.libs.pari
sage: a == b #_
˓needs sage.libs.pari
True
```

`sage.arith.misc.binomial_coefficients(n)`

Return a dictionary containing pairs $\{(k_1, k_2) : C_{k,n}\}$ where $C_{k,n}$ are binomial coefficients and $n = k_1 + k_2$.

INPUT:

- n – integer

OUTPUT: dictionary

EXAMPLES:

```
sage: sorted(binomial_coefficients(3).items())
[((0, 3), 1), ((1, 2), 3), ((2, 1), 3), ((3, 0), 1)]
```

Notice the coefficients above are the same as below:

```
sage: R.<x, y> = QQ[]
sage: (x+y)^3
x^3 + 3*x^2*y + 3*x*y^2 + y^3
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8 #_
˓needs numpy
sage: sorted(binomial_coefficients(int8(3)).items()) #_
˓needs numpy
[((0, 3), 1), ((1, 2), 3), ((2, 1), 3), ((3, 0), 1)]
sage: from gmpy2 import mpz
sage: sorted(binomial_coefficients(mpz(3)).items())
[((0, 3), 1), ((1, 2), 3), ((2, 1), 3), ((3, 0), 1)]
```

AUTHORS:

- Fredrik Johansson

`sage.arith.misc.carmichael_lambda(n)`

Return the Carmichael function of a positive integer n.

The Carmichael function of n , denoted $\lambda(n)$, is the smallest positive integer k such that $a^k \equiv 1 \pmod{n}$ for all $a \in \mathbf{Z}/n\mathbf{Z}$ satisfying $\gcd(a, n) = 1$. Thus, $\lambda(n) = k$ is the exponent of the multiplicative group $(\mathbf{Z}/n\mathbf{Z})^*$.

INPUT:

- n – positive integer

OUTPUT: the Carmichael function of n

ALGORITHM:

If $n = 2, 4$ then $\lambda(n) = \varphi(n)$. Let $p \geq 3$ be an odd prime and let k be a positive integer. Then $\lambda(p^k) = p^{k-1}(p-1) = \varphi(p^k)$. If $k \geq 3$, then $\lambda(2^k) = 2^{k-2}$. Now consider the case where $n > 3$ is composite and let $n = p_1^{k_1} p_2^{k_2} \cdots p_t^{k_t}$ be the prime factorization of n . Then

$$\lambda(n) = \lambda(p_1^{k_1} p_2^{k_2} \cdots p_t^{k_t}) = \text{lcm}(\lambda(p_1^{k_1}), \lambda(p_2^{k_2}), \dots, \lambda(p_t^{k_t}))$$

EXAMPLES:

The Carmichael function of all positive integers up to and including 10:

```
sage: from sage.arith.misc import carmichael_lambda
sage: list(map(carmichael_lambda, [1..10]))
[1, 1, 2, 2, 4, 2, 6, 2, 6, 4]
```

The Carmichael function of the first ten primes:

```
sage: list(map(carmichael_lambda, primes_first_n(10)))
# needs sage.libs.pari
[1, 2, 4, 6, 10, 12, 16, 18, 22, 28]
```

Cases where the Carmichael function is equivalent to the Euler phi function:

```
sage: carmichael_lambda(2) == euler_phi(2)
True
sage: carmichael_lambda(4) == euler_phi(4)
# needs sage.libs.pari
True
sage: p = random_prime(1000, lbound=3, proof=True)
# needs sage.libs.pari
sage: k = randint(1, 1000)
sage: carmichael_lambda(p^k) == euler_phi(p^k)
# needs sage.libs.pari
True
```

A case where $\lambda(n) \neq \varphi(n)$:

```
sage: k = randint(3, 1000)
sage: carmichael_lambda(2^k) == 2^(k - 2)
# needs sage.libs.pari
True
sage: carmichael_lambda(2^k) == 2^(k - 2) == euler_phi(2^k)
# needs sage.libs.pari
False
```

Verifying the current implementation of the Carmichael function using another implementation. The other implementation that we use for verification is an exhaustive search for the exponent of the multiplicative group $(\mathbf{Z}/n\mathbf{Z})^*$.

```
sage: from sage.arith.misc import carmichael_lambda
sage: n = randint(1, 500)
sage: c = carmichael_lambda(n)
sage: def coprime(n):
....:     return [i for i in range(n) if gcd(i, n) == 1]
sage: def znpower(n, k):
....:     L = coprime(n)
....:     return list(map(power_mod, L, [k]^len(L), [n]^len(L)))
```

(continues on next page)

(continued from previous page)

```
sage: def my_carmichael(n):
....:     if n == 1:
....:         return 1
....:     for k in range(1, n):
....:         L = znpower(n, k)
....:         ones = [1] * len(L)
....:         T = [L[i] == ones[i] for i in range(len(L))]
....:         if all(T):
....:             return k
sage: c == my_carmichael(n)
True
```

Carmichael's theorem states that $a^{\lambda(n)} \equiv 1 \pmod{n}$ for all elements a of the multiplicative group $(\mathbf{Z}/n\mathbf{Z})^*$. Here, we verify Carmichael's theorem.

```
sage: from sage.arith.misc import carmichael_lambda
sage: n = randint(2, 1000)
sage: c = carmichael_lambda(n)
sage: ZnZ = IntegerModRing(n)
sage: M = ZnZ.list_of_elements_of_multiplicative_group()
sage: ones = [1] * len(M)
sage: P = [power_mod(a, c, n) for a in M]
sage: P == ones
True
```

REFERENCES:

- Wikipedia article Carmichael_function

`sage.arith.misc.continuant(v, n=None)`

Function returns the continuant of the sequence v (list or tuple).

Definition: see Graham, Knuth and Patashnik, *Concrete Mathematics*, section 6.7: Continuants. The continuant is defined by

- $K_0() = 1$
- $K_1(x_1) = x_1$
- $K_n(x_1, \dots, x_n) = K_{n-1}(x_n, \dots, x_{n-1})x_n + K_{n-2}(x_1, \dots, x_{n-2})$

If $n = \text{None}$ or $n > \text{len}(v)$ the default $n = \text{len}(v)$ is used.

INPUT:

- v – list or tuple of elements of a ring
- n – (optional) integer

OUTPUT: element of ring (integer, polynomial, etcetera).

EXAMPLES:

```
sage: continuant([1, 2, 3])
10
sage: p = continuant([2, 1, 2, 1, 1, 4, 1, 1, 6, 1, 1, 1, 8, 1, 1, 10])
sage: q = continuant([1, 2, 1, 1, 4, 1, 1, 6, 1, 1, 8, 1, 1, 10])
sage: p/q
517656/190435
sage: F = continued_fraction([2, 1, 2, 1, 1, 4, 1, 1, 6, 1, 1, 8, 1, 1, 10])
```

(continues on next page)

(continued from previous page)

```
sage: F.convergent(14)
517656/190435
sage: x = PolynomialRing(RationalField(), 'x', 5).gens()
sage: continuant(x)
x0*x1*x2*x3*x4 + x0*x1*x2 + x0*x1*x4 + x0*x3*x4 + x2*x3*x4 + x0 + x2 + x4
sage: continuant(x, 3)
x0*x1*x2 + x0 + x2
sage: continuant(x, 2)
x0*x1 + 1
```

We verify the identity

$$K_n(z, z, \dots, z) = \sum_{k=0}^n \binom{n-k}{k} z^{n-2k}$$

for $n = 6$ using polynomial arithmetic:

```
sage: z = QQ['z'].0
sage: continuant((z,z,z,z,z,z,z,z,z,z,z,z), 6)
z^6 + 5*z^4 + 6*z^2 + 1

sage: continuant(9)
Traceback (most recent call last):
...
TypeError: object of type 'sage.rings.integer.Integer' has no len()
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
#_
#> needs numpy
sage: continuant([int8(1), int8(2), int8(3)])
#_
#> needs numpy
10
sage: from gmpy2 import mpz
sage: continuant([mpz(1), mpz(2), mpz(3)])
mpz(10)
```

AUTHORS:

- Jaap Spies (2007-02-06)

`sage.arith.misc.coprime_part(x, base)`

Given an element x of a Euclidean domain and a factor base base , return the largest divisor of x that is not divisible by any element of base .

ALGORITHM: Divide x by the `smooth_part()`.

EXAMPLES:

```
sage: from sage.arith.misc import coprime_part, smooth_part
sage: from sage.rings.generic import ProductTree
sage: coprime_part(10^77+1, primes(10000))
2159827213801295896328509719222460043196544298056155507343412527
sage: tree = ProductTree(primes(10000))
sage: coprime_part(10^55+1, tree)
6426667196963538873896485804232411
sage: coprime_part(10^55+1, tree).factor()
```

(continues on next page)

(continued from previous page)

```
sage.arith.misc.crt(a, b, m=None, n=None)
```

Return a solution to a Chinese Remainder Theorem problem.

INPUT:

- a, b – two residues (elements of some ring for which extended gcd is available), or two lists, one of residues and one of moduli
 - m, n – (default: `None`) two moduli, or `None`

OUTPUT:

If m , n are not `None`, returns a solution x to the simultaneous congruences $x \equiv a \pmod{m}$ and $x \equiv b \pmod{n}$, if one exists. By the Chinese Remainder Theorem, a solution to the simultaneous congruences exists if and only if $a \equiv b \pmod{\gcd(m, n)}$. The solution x is only well-defined modulo $\text{lcm}(m, n)$.

If a and b are lists, returns a simultaneous solution to the congruences $x \equiv a_i \pmod{b_i}$, if one exists.

See also

- *CRT_list()*

EXAMPLES:

Using crt by giving it pairs of residues and moduli:

```
sage: crt(2, 1, 3, 5)
11
sage: crt(13, 20, 100, 301)
28013
sage: crt([2, 1], [3, 5])
11
sage: crt([13, 20], [100, 301])
28013
```

You can also use upper case:

```
sage: c = CRT(2,3, 3, 5); c
8
sage: c % 3 == 2
True
sage: c % 5 == 3
True
```

Note that this also works for polynomial rings:

```
sage: # needs sage.rings.number_field
sage: x = polygen(ZZ, 'x')
sage: K.<a> = NumberField(x^3 - 7)
sage: R.<y> = K[]
sage: f = y^2 + 3
sage: q = y^3 - 5
```

(continues on next page)

(continued from previous page)

```
sage: CRT(1, 3, f, g)
-3/26*y^4 + 5/26*y^3 + 15/26*y + 53/26
sage: CRT(1, a, f, g)
(-3/52*a + 3/52)*y^4 + (5/52*a - 5/52)*y^3 + (15/52*a - 15/52)*y + 27/52*a + 25/52
```

You can also do this for any number of moduli:

```
sage: # needs sage.rings.number_field
sage: K.<a> = NumberField(x^3 - 7)
sage: R.<x> = K[]
sage: CRT([], [])
0
sage: CRT([a], [x])
a
sage: f = x^2 + 3
sage: g = x^3 - 5
sage: h = x^5 + x^2 - 9
sage: k = CRT([1, a, 3], [f, g, h]); k
(127/26988*a - 5807/386828)*x^9 + (45/8996*a - 33677/1160484)*x^8
+ (2/173*a - 6/173)*x^7 + (133/6747*a - 5373/96707)*x^6
+ (-6/2249*a + 18584/290121)*x^5 + (-277/8996*a + 38847/386828)*x^4
+ (-135/4498*a + 42673/193414)*x^3 + (-1005/8996*a + 470245/1160484)*x^2
+ (-1215/8996*a + 141165/386828)*x + 621/8996*a + 836445/386828
sage: k.mod(f)
1
sage: k.mod(g)
a
sage: k.mod(h)
3
```

If the moduli are not coprime, a solution may not exist:

```
sage: crt(4, 8, 8, 12)
20
sage: crt(4, 6, 8, 12)
Traceback (most recent call last):
...
ValueError: no solution to crt problem since gcd(8,12) does not divide 4-6

sage: x = polygen(QQ)
sage: crt(2, 3, x - 1, x + 1)
-1/2*x + 5/2
sage: crt(2, x, x^2 - 1, x^2 + 1)
-1/2*x^3 + x^2 + 1/2*x + 1
sage: crt(2, x, x^2 - 1, x^3 - 1)
Traceback (most recent call last):
...
ValueError: no solution to crt problem since gcd(x^2 - 1,x^3 - 1) does not divide
-2*x

sage: crt(int(2), int(3), int(7), int(11))
58
```

crt also work with numpy and gmpy2 numbers:

```
sage: import numpy
#_
↳needs numpy
```

(continues on next page)

(continued from previous page)

```
sage: crt(numpy.int8(2), numpy.int8(3), numpy.int8(7), numpy.int8(11))          #_
˓needs numpy
58
sage: from gmpy2 import mpz
sage: crt(mpz(2), mpz(3), mpz(7), mpz(11))
58
sage: crt(mpz(2), 3, mpz(7), numpy.int8(11))                                     #_
˓needs numpy
58
```

`sage.arith.misc.dedekind_psi(N)`

Return the value of the Dedekind psi function at N.

INPUT:

- N – positive integer

OUTPUT: integer

The Dedekind psi function is the multiplicative function defined by

$$\psi(n) = n \prod_{p|n, p \text{ prime}} (1 + 1/p).$$

See Wikipedia article [Dedekind_psi_function](#) and OEIS sequence A001615.

EXAMPLES:

```
sage: from sage.arith.misc import dedekind_psi
sage: [dedekind_psi(d) for d in range(1, 12)]
[1, 3, 4, 6, 6, 12, 8, 12, 12, 18, 12]
```

`sage.arith.misc.dedekind_sum(p, q, algorithm='default')`

Return the Dedekind sum $s(p, q)$ defined for integers p, q as

$$s(p, q) = \sum_{i=0}^{q-1} \left(\left(\frac{i}{q} \right) \right) \left(\left(\frac{pi}{q} \right) \right)$$

where

$$((x)) = \begin{cases} x - \lfloor x \rfloor - \frac{1}{2} & \text{if } x \in \mathbf{Q} \setminus \mathbf{Z} \\ 0 & \text{if } x \in \mathbf{Z}. \end{cases}$$

Warning

Caution is required as the Dedekind sum sometimes depends on the algorithm or is left undefined when p and q are not coprime.

INPUT:

- p, q – integers
- algorithm – must be one of the following
 - 'default' – (default) use FLINT
 - 'flint' – use FLINT

- '**pari**' – use PARI (gives different results if p and q are not coprime)

OUTPUT: a rational number

EXAMPLES:

Several small values:

```
sage: for q in range(10): print([dedekind_sum(p,q) for p in range(q+1)])
#_
˓needs sage.libs.flint
[0]
[0, 0]
[0, 0, 0]
[0, 1/18, -1/18, 0]
[0, 1/8, 0, -1/8, 0]
[0, 1/5, 0, 0, -1/5, 0]
[0, 5/18, 1/18, 0, -1/18, -5/18, 0]
[0, 5/14, 1/14, -1/14, 1/14, -1/14, -5/14, 0]
[0, 7/16, 1/8, 1/16, 0, -1/16, -1/8, -7/16, 0]
[0, 14/27, 4/27, 1/18, -4/27, 4/27, -1/18, -4/27, -14/27, 0]
```

Check relations for restricted arguments:

```
sage: q = 23; dedekind_sum(1, q); (q-1)*(q-2)/(12*q)
#_
˓needs sage.libs.flint
77/46
77/46
sage: p, q = 100, 723      # must be coprime
sage: dedekind_sum(p, q) + dedekind_sum(q, p)
#_
˓needs sage.libs.flint
31583/86760
sage: -1/4 + (p/q + q/p + 1/(p*q))/12
31583/86760
```

We check that evaluation works with large input:

```
sage: dedekind_sum(3^54 - 1, 2^93 + 1)
#_
˓needs sage.libs.flint
459340694971839990630374299870/29710560942849126597578981379
sage: dedekind_sum(3^54 - 1, 2^93 + 1, algorithm='pari')
#_
˓needs sage.libs.pari
459340694971839990630374299870/29710560942849126597578981379
```

We check consistency of the results:

```
sage: dedekind_sum(5, 7, algorithm='default')
#_
˓needs sage.libs.flint
-1/14
sage: dedekind_sum(5, 7, algorithm='flint')
#_
˓needs sage.libs.flint
-1/14
sage: dedekind_sum(5, 7, algorithm='pari')
#_
˓needs sage.libs.pari
-1/14
sage: dedekind_sum(6, 8, algorithm='default')
#_
˓needs sage.libs.flint
-1/8
sage: dedekind_sum(6, 8, algorithm='flint')
#_
```

(continues on next page)

(continued from previous page)

```

↳needs sage.libs.flint
-1/8
sage: dedekind_sum(6, 8, algorithm='pari') #_
↳needs sage.libs.pari
-1/8

```

Tests with numpy and gmpy2 numbers:

```

sage: from numpy import int8 #_
↳needs numpy
sage: dedekind_sum(int8(5), int8(7), algorithm='default') #_
↳needs numpy sage.libs.flint
-1/14
sage: from gmpy2 import mpz #_
sage: dedekind_sum(mpz(5), mpz(7), algorithm='default') #_
↳needs sage.libs.flint
-1/14

```

REFERENCES:

- [Ap1997]
- Wikipedia article Dedekind_sum

sage.arith.misc.**differences**(*lis, n=1*)

Return the *n* successive differences of the elements in *lis*.

EXAMPLES:

```

sage: differences(prime_range(50)) #_
↳needs sage.libs.pari
[1, 2, 2, 4, 2, 4, 2, 4, 6, 2, 6, 4, 2, 4]
sage: differences([i^2 for i in range(1,11)]) #_
[3, 5, 7, 9, 11, 13, 15, 17, 19]
sage: differences([i^3 + 3*i for i in range(1,21)]) #_
[10, 22, 40, 64, 94, 130, 172, 220, 274, 334, 400, 472, 550, 634, 724, 820, 922, -1030, 1144]
sage: differences([i^3 - i^2 for i in range(1,21)], 2) #_
[10, 16, 22, 28, 34, 40, 46, 52, 58, 64, 70, 76, 82, 88, 94, 100, 106, 112]
sage: differences([p - i^2 for i, p in enumerate(prime_range(50))], 3) #_
↳needs sage.libs.pari
[-1, 2, -4, 4, -4, 4, 0, -6, 8, -6, 0, 4]

```

Tests with numpy and gmpy2 numbers:

```

sage: from numpy import int8 #_
↳needs numpy
sage: differences([int8(1), int8(4), int8(6), int8(19)]) #_
↳needs numpy
[3, 2, 13]
sage: from gmpy2 import mpz #_
sage: differences([mpz(1), mpz(4), mpz(6), mpz(19)]) #_
[mpz(3), mpz(2), mpz(13)]

```

AUTHORS:

- Timothy Clemans (2008-03-09)

```
sage.arith.misc.divisors(n)
```

Return the list of all divisors (up to units) of this element of a unique factorization domain.

For an integer, the list of all positive integer divisors of this integer, sorted in increasing order, is returned.

INPUT:

- n – the element

EXAMPLES:

Divisors of integers:

```
sage: divisors(-3)
[1, 3]
sage: divisors(6)
[1, 2, 3, 6]
sage: divisors(28)
[1, 2, 4, 7, 14, 28]
sage: divisors(2^5)
[1, 2, 4, 8, 16, 32]
sage: divisors(100)
[1, 2, 4, 5, 10, 20, 25, 50, 100]
sage: divisors(1)
[1]
sage: divisors(0)
Traceback (most recent call last):
...
ValueError: n must be nonzero
sage: divisors(2^3 * 3^2 * 17)
[1, 2, 3, 4, 6, 8, 9, 12, 17, 18, 24, 34, 36, 51, 68, 72,
102, 136, 153, 204, 306, 408, 612, 1224]
```

This function works whenever one has unique factorization:

```
sage: # needs sage.rings.number_field
sage: K.<a> = QuadraticField(7)
sage: divisors(K.ideal(7))
[Fractional ideal (1), Fractional ideal (a), Fractional ideal (7)]
sage: divisors(K.ideal(3))
[Fractional ideal (1), Fractional ideal (3),
Fractional ideal (a - 2), Fractional ideal (a + 2)]
sage: divisors(K.ideal(35))
[Fractional ideal (1), Fractional ideal (5), Fractional ideal (a),
Fractional ideal (7), Fractional ideal (5*a), Fractional ideal (35)]
```

```
sage.arith.misc.eratosthenes(n)
```

Return a list of the primes $\leq n$.

This is extremely slow and is for educational purposes only.

INPUT:

- n – positive integer

OUTPUT: list of primes less than or equal to n

EXAMPLES:

```
sage: eratosthenes(3)
[2, 3]
```

(continues on next page)

(continued from previous page)

```
sage: eratosthenes(50)
[2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47]
sage: len(eratosthenes(100))
25
sage: eratosthenes(213) == prime_range(213) #_
˓needs sage.libs.pari
True
```

`sage.arith.misc.factor(n, proof=None, int_=False, algorithm='pari', verbose=0, **kwds)`

Return the factorization of n . The result depends on the type of n .

If n is an integer, returns the factorization as an object of type `Factorization`.

If n is not an integer, `n.factor(proof=proof, **kwds)` gets called. See `n.factor??` for more documentation in this case.

Warning

This means that applying `factor()` to an integer result of a symbolic computation will not factor the integer, because it is considered as an element of a larger symbolic ring.

EXAMPLES:

```
sage: f(n) = n^2
˓needs sage.symbolic
sage: is_prime(f(3))
˓needs sage.symbolic
False
sage: factor(f(3))
˓needs sage.symbolic
9
```

INPUT:

- n – nonzero integer
- `proof` – boolean or `None` (default: `None`)
- `int_` – boolean (default: `False`); whether to return answers as Python integers
- `algorithm` – string
 - '`pari`' – (default) use the PARI C library
 - '`kash`' – use KASH computer algebra system (requires that `kash` be installed)
 - '`magma`' – use Magma (requires `magma` be installed)
- `verbose` – integer (default: 0); PARI's debug variable is set to this. E.g., set to 4 or 8 to see lots of output during factorization.

OUTPUT: factorization of n

The `qsieve` and `ecm` commands give access to highly optimized implementations of algorithms for doing certain integer factorization problems. These implementations are not used by the generic `factor()` command, which currently just calls PARI (note that PARI also implements sieve and ecm algorithms, but they are not as optimized). Thus you might consider using them instead for certain numbers.

The factorization returned is an element of the class `Factorization`; use `Factorization??` to see more details, and examples below for usage. A `Factorization` contains both the unit factor (+1 or -1) and a sorted list of (prime, exponent) pairs.

The factorization displays in pretty-print format but it is easy to obtain access to the (prime, exponent) pairs and the unit, to recover the number from its factorization, and even to multiply two factorizations. See examples below.

EXAMPLES:

```
sage: factor(500)
2^2 * 5^3
sage: factor(-20)
-1 * 2^2 * 5
sage: f=factor(-20)
sage: list(f)
[(2, 2), (5, 1)]
sage: f.unit()
-1
sage: f.value()
-20
sage: factor(-next_prime(10^2) * next_prime(10^7))          #
˓needs sage.libs.pari
-1 * 101 * 10000019
```

```
sage: factor(293292629867846432923017396246429, algorithm='flint')      #
˓needs sage.libs.flint
3 * 4852301647696687 * 20148007492971089
```

```
sage: factor(-500, algorithm='kash')
-1 * 2^2 * 5^3
```

```
sage: factor(-500, algorithm='magma')      # optional - magma
-1 * 2^2 * 5^3
```

```
sage: factor(0)
Traceback (most recent call last):
...
ArithmetricError: factorization of 0 is not defined
sage: factor(1)
1
sage: factor(-1)
-1
sage: factor(2^(2^7) + 1)                  #
˓needs sage.libs.pari
59649589127497217 * 5704689200685129054721
```

Sage calls PARI's `pari:factor`, which has `proof=False` by default. Sage has a global proof flag, set to `True` by default (see `sage.structure.proof.proof`, or use `proof.[tab]`). To override the default, call this function with `proof=False`.

```
sage: factor(3^89 - 1, proof=False)          #
˓needs sage.libs.pari
2 * 179 * 1611479891519807 * 5042939439565996049162197
```

```
sage: factor(2^197 + 1) # long time (2s)
˓needs sage.libs.pari
3 * 197002597249 * 1348959352853811313 * 251951573867253012259144010843
```

Any object which has a factor method can be factored like this:

```
sage: K.<i> = QuadraticField(-1) #_
˓needs sage.rings.number_field
sage: factor(122 - 454*i) #_
˓needs sage.rings.number_field
(-i) * (-i - 2)^3 * (i + 1)^3 * (-2*i + 3) * (i + 4)
```

To access the data in a factorization:

```
sage: # needs sage.libs.pari
sage: f = factor(420); f
2^2 * 3 * 5 * 7
sage: [x for x in f]
[(2, 2), (3, 1), (5, 1), (7, 1)]
sage: [p for p,e in f]
[2, 3, 5, 7]
sage: [e for p,e in f]
[2, 1, 1, 1]
sage: [p^e for p,e in f]
[4, 3, 5, 7]
```

We can factor Python, numpy and gmpy2 numbers:

```
sage: factor(math.pi)
3.141592653589793
sage: import numpy #_
˓needs numpy
sage: factor(numpy.int8(30)) #_
˓needs numpy sage.libs.pari
2 * 3 * 5
sage: import gmpy2
sage: factor(gmpy2.mpz(30))
2 * 3 * 5
```

`sage.arith.misc.factorial(n, algorithm='gmp')`

Compute the factorial of n , which is the product $1 \cdot 2 \cdot 3 \cdots (n-1) \cdot n$.

INPUT:

- n – integer
- `algorithm` – string (default: 'gmp'):
 - 'gmp' – use the GMP C-library factorial function
 - 'pari' – use PARI's factorial function

OUTPUT: integer

EXAMPLES:

```
sage: from sage.arith.misc import factorial
sage: factorial(0)
1
```

(continues on next page)

(continued from previous page)

```
sage: factorial(4)
24
sage: factorial(10)
3628800
sage: factorial(1) == factorial(0)
True
sage: factorial(6) == 6*5*4*3*2
True
sage: factorial(1) == factorial(0)
True
sage: factorial(71) == 71* factorial(70)
True
sage: factorial(-32)
Traceback (most recent call last):
...
ValueError: factorial -- must be nonnegative
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
#_
˓needs numpy
sage: factorial(int8(4))
#_
˓needs numpy
24
sage: from gmpy2 import mpz
sage: factorial(mpz(4))
24
```

PERFORMANCE: This discussion is valid as of April 2006. All timings below are on a Pentium Core Duo 2Ghz MacBook Pro running Linux with a 2.6.16.1 kernel.

- It takes less than a minute to compute the factorial of 10^7 using the GMP algorithm, and the factorial of 10^6 takes less than 4 seconds.
- The GMP algorithm is faster and more memory efficient than the PARI algorithm. E.g., PARI computes 10^7 factorial in 100 seconds on the core duo 2Ghz.
- For comparison, computation in Magma $\leq 2.12-10$ of $n!$ is best done using $*[1..n]$. It takes 113 seconds to compute the factorial of 10^7 and 6 seconds to compute the factorial of 10^6 . Mathematica V5.2 compute the factorial of 10^7 in 136 seconds and the factorial of 10^6 in 7 seconds. (Mathematica is notably very efficient at memory usage when doing factorial calculations.)

`sage.arith.misc.falling_factorial(x, a)`

Return the falling factorial $(x)_a$.

The notation in the literature is a mess: often $(x)_a$, but there are many other notations: GKP: Concrete Mathematics uses x^a .

Definition: for integer $a \geq 0$ we have $x(x - 1) \cdots (x - a + 1)$. In all other cases we use the GAMMA-function:

$$\frac{\Gamma(x+1)}{\Gamma(x-a+1)}.$$

INPUT:

- x – element of a ring
- a – nonnegative integer or
- x, a – any numbers

OUTPUT: the falling factorial

See also

`rising_factorial()`

EXAMPLES:

```
sage: falling_factorial(10, 3)
720
sage: falling_factorial(10, 10)
3628800
sage: factorial(10)
3628800

sage: # needs sage.symbolic
sage: falling_factorial(10, RR('3.0'))
720.000000000000
sage: falling_factorial(10, RR('3.3'))
1310.11633396601
sage: a = falling_factorial(1 + I, I); a
gamma(I + 2)
sage: CC(a)
0.652965496420167 + 0.343065839816545*I
sage: falling_factorial(1 + I, 4)
4*I + 2
sage: falling_factorial(I, 4)
-10

sage: M = MatrixSpace(ZZ, 4, 4) #_
˓needs sage.modules
sage: A = M([1,0,1,0, 1,0,1,0, 1,0,10,10, 1,0,1,1]) #_
˓needs sage.modules
sage: falling_factorial(A, 2) # A(A - I) #_
˓needs sage.modules
[ 1   0   10  10]
[ 1   0   10  10]
[ 20   0  101  100]
[ 2   0   11  10]

sage: x = ZZ['x'].0
sage: falling_factorial(x, 4)
x^4 - 6*x^3 + 11*x^2 - 6*x
```

AUTHORS:

- Jaap Spies (2006-03-05)

`sage.arith.misc.four_squares(n)`

Write the integer n as a sum of four integer squares.

INPUT:

- n – integer

OUTPUT: a tuple (a, b, c, d) of nonnegative integers such that $n = a^2 + b^2 + c^2 + d^2$ with $a \leq b \leq c \leq d$.

EXAMPLES:

```
sage: four_squares(3)
(0, 1, 1, 1)
```

(continues on next page)

(continued from previous page)

```
sage.arith.misc.fundamental_discriminant(D)
```

Return the discriminant of the quadratic extension $K = Q(\sqrt{D})$, i.e. an integer d congruent to either 0 or 1, mod 4, and such that, at most, the only square dividing it is 4.

INPUT:

- D – integer

OUTPUT: integer; the fundamental discriminant

EXAMPLES:

```
sage: fundamental_discriminant(102)
408
sage: fundamental_discriminant(720)
5
sage: fundamental_discriminant(2)
8
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8          #_
˓needs numpy
sage: fundamental_discriminant(int8(102))      #_
˓needs numpy
408
sage: from gmpy2 import mpz
sage: fundamental_discriminant(mpz(102))
408
```

```
sage.arith.misc.gauss_sum(char_value, finite_field)
```

Return the Gauss sums for a general finite field.

INPUT:

- `char_value` – choice of multiplicative character, given by its value on the `finite_field.multiplicative_generator()`
 - `finite_field` – a finite field

OUTPUT:

an element of the parent ring of `char_value`, that can be any field containing enough roots of unity, for example the `UniversalCyclotomicField`, `QQbar` or `ComplexField`

For a finite field F of characteristic p , the Gauss sum associated to a multiplicative character χ (with values in a ring K) is defined as

$$\sum_{x \in F^\times} \chi(x) \zeta_p^{\text{Tr } x},$$

where $\zeta_p \in K$ is a primitive root of unity of order p and Tr is the trace map from F to its prime field \mathbf{F}_p .

For more info on Gauss sums, see [Wikipedia article Gauss_sum](#).

Todo

Implement general Gauss sums for an arbitrary pair (`multiplicative_character`, `additive_character`)

EXAMPLES:

```
sage: # needs sage.libs.pari sage.rings.number_field
sage: from sage.arith.misc import gauss_sum
sage: F = GF(5); q = 5
sage: zq = UniversalCyclotomicField().zeta(q - 1)
sage: L = [gauss_sum(zq**i, F) for i in range(5)]; L
[-1,
 E(20)^4 + E(20)^13 - E(20)^16 - E(20)^17,
 E(5) - E(5)^2 - E(5)^3 + E(5)^4,
 E(20)^4 - E(20)^13 - E(20)^16 + E(20)^17,
 -1]
sage: [g*g.conjugate() for g in L]
[1, 5, 5, 5, 1]

sage: # needs sage.libs.pari sage.rings.number_field
sage: F = GF(11**2); q = 11**2
sage: zq = UniversalCyclotomicField().zeta(q - 1)
sage: g = gauss_sum(zq**4, F)
sage: g*g.conjugate()
121
```

See also

- `sage.rings.padics.misc.gauss_sum()` for a p -adic version
- `sage.modular.dirichlet.DirichletCharacter.gauss_sum()` for prime finite fields
- `sage.modular.dirichlet.DirichletCharacter.gauss_sum_numerical()` for prime finite fields

`sage.arith.misc.gcd(a, b=None, **kwargs)`

Return the greatest common divisor of `a` and `b`.

If `a` is a list and `b` is omitted, return instead the greatest common divisor of all elements of `a`.

INPUT:

- `a, b` – two elements of a ring with gcd or
- `a` – list or tuple of elements of a ring with gcd

Additional keyword arguments are passed to the respectively called methods.

OUTPUT:

The given elements are first coerced into a common parent. Then, their greatest common divisor *in that common parent* is returned.

EXAMPLES:

```
sage: GCD(97,100)
1
sage: GCD(97*10^15, 19^20*97^2)
97
sage: GCD(2/3, 4/5)
2/15
sage: GCD([2,4,6,8])
2
sage: GCD(srange(0,10000,10)) # fast !!
10
```

Note that to take the gcd of n elements for $n \neq 2$ you must put the elements into a list by enclosing them in `[. . .]`. Before Issue #4988 the following wrongly returned 3 since the third parameter was just ignored:

```
sage: gcd(3, 6, 2)
Traceback (most recent call last):
...
TypeError: ...gcd() takes ...
sage: gcd([3, 6, 2])
1
```

Similarly, giving just one element (which is not a list) gives an error:

```
sage: gcd(3)
Traceback (most recent call last):
...
TypeError: 'sage.rings.integer.Integer' object is not iterable
```

By convention, the gcd of the empty list is (the integer) 0:

```
sage: gcd([])
0
sage: type(gcd([]))
<class 'sage.rings.integer.Integer'>
```

`sage.arith.misc.get_gcd(order)`

Return the fastest gcd function for integers of size no larger than order.

EXAMPLES:

```
sage: sage.arith.misc.get_gcd(4000)
<built-in method gcd_int of sage.rings.fast_arith.arith_int object at ...>
sage: sage.arith.misc.get_gcd(400000)
<built-in method gcd_longlong of sage.rings.fast_arith.arith_llong object at ...>
sage: sage.arith.misc.get_gcd(400000000)
<function gcd at ...>
```

`sage.arith.misc.get_inverse_mod(order)`

Return the fastest inverse_mod function for integers of size no larger than order.

EXAMPLES:

```
sage: sage.arith.misc.get_inverse_mod(6000)
<built-in method inverse_mod_int of sage.rings.fast_arith.arith_int object at ...>
sage: sage.arith.misc.get_inverse_mod(600000)
<built-in method inverse_mod_llong of sage.rings.fast_arith.arith_llong object at ...>
sage: sage.arith.misc.get_inverse_mod(6000000000)
<function inverse_mod at ...>
```

`sage.arith.misc.hilbert_conductor(a, b)`

Return the product of all (finite) primes where the Hilbert symbol is -1.

This is the (reduced) discriminant of the quaternion algebra (a, b) over \mathbf{Q} .

INPUT:

- a, b – integers

OUTPUT: squarefree positive integer

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: hilbert_conductor(-1, -1)
2
sage: hilbert_conductor(-1, -11)
11
sage: hilbert_conductor(-2, -5)
5
sage: hilbert_conductor(-3, -17)
17
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
#_
#<needs numpy>
sage: hilbert_conductor(int8(-3), int8(-17))
#_
#<needs numpy sage.libs.pari>
17
sage: from gmpy2 import mpz
#_
sage: hilbert_conductor(mpz(-3), mpz(-17))
#_
#<needs sage.libs.pari>
17
```

AUTHOR:

- Gonzalo Tornaria (2009-03-02)

`sage.arith.misc.hilbert_conductor_inverse(d)`

Finds a pair of integers (a, b) such that $\text{hilbert_conductor}(a, b) == d$.

The quaternion algebra (a, b) over \mathbf{Q} will then have (reduced) discriminant d .

INPUT:

- d – square-free positive integer

OUTPUT: pair of integers

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: hilbert_conductor_inverse(2)
(-1, -1)
sage: hilbert_conductor_inverse(3)
(-1, -3)
sage: hilbert_conductor_inverse(6)
(-1, 3)
sage: hilbert_conductor_inverse(30)
(-3, -10)
sage: hilbert_conductor_inverse(4)
Traceback (most recent call last):
...
ValueError: d needs to be squarefree
sage: hilbert_conductor_inverse(-1)
Traceback (most recent call last):
...
ValueError: d needs to be positive
```

AUTHOR:

- Gonzalo Tornaria (2009-03-02)

`sage.arith.misc.hilbert_symbol(a, b, p, algorithm='pari')`

Return 1 if $ax^2 + by^2$ p -adically represents a nonzero square, otherwise returns -1. If either a or b is 0, returns 0.

INPUT:

- a, b – integers
- p – integer; either prime or -1 (which represents the archimedean place)
- algorithm – string
 - 'pari' – (default) use the PARI C library
 - 'direct' – use a Python implementation
 - '**all**' – use both PARI and direct and check that the results agree, then return the common answer

OUTPUT: integer (0, -1, or 1)

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: hilbert_symbol(-1, -1, -1, algorithm='all')
-1
sage: hilbert_symbol(2, 3, 5, algorithm='all')
1
sage: hilbert_symbol(4, 3, 5, algorithm='all')
1
sage: hilbert_symbol(0, 3, 5, algorithm='all')
0
sage: hilbert_symbol(-1, -1, 2, algorithm='all')
-1
sage: hilbert_symbol(1, -1, 2, algorithm='all')
1
sage: hilbert_symbol(3, -1, 2, algorithm='all')
-1
sage: hilbert_symbol(QQ(-1)/QQ(4), -1, 2) == -1
```

#

(continues on next page)

(continued from previous page)

```

→needs sage.libs.pari
True
sage: hilbert_symbol(QQ(-1)/QQ(4), -1, 3) == 1
#_
→needs sage.libs.pari
True

```

Tests with numpy and gmpy2 numbers:

```

sage: from numpy import int8
→needs numpy
sage: hilbert_symbol(int8(2), int8(3), int8(5), algorithm='all')
#_
→needs numpy sage.libs.pari
1
sage: from gmpy2 import mpz
sage: hilbert_symbol(mpz(2), mpz(3), mpz(5), algorithm='all')
#_
→needs sage.libs.pari
1

```

AUTHORS:

- William Stein and David Kohel (2006-01-05)

sage.arith.misc.**integer_ceil**(*x*)

Return the ceiling of *x*.

EXAMPLES:

```

sage: integer_ceil(5.4)
6
sage: integer_ceil(x)
#_
→needs sage.symbolic
Traceback (most recent call last):
...
NotImplementedError: computation of ceil of x not implemented

```

Tests with numpy and gmpy2 numbers:

```

sage: from numpy import float32
→needs numpy
sage: integer_ceil(float32(5.4))
#_
→needs numpy
6
sage: from gmpy2 import mpfr
sage: integer_ceil(mpfr(5.4))
6

```

sage.arith.misc.**integer_floor**(*x*)

Return the largest integer $\leq x$.

INPUT:

- *x* – an object that has a floor method or is coercible to integer

OUTPUT: integer

EXAMPLES:

```
sage: integer_floor(5.4)
5
sage: integer_floor(float(5.4))
5
sage: integer_floor(-5/2)
-3
sage: integer_floor(RDF(-5/2))
-3

sage: integer_floor(x)
# needs sage.symbolic
Traceback (most recent call last):
...
NotImplementedError: computation of floor of x not implemented
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import float32
# needs numpy
sage: integer_floor(float32(5.4))
# needs numpy
5
sage: from gmpy2 import mpfr
sage: integer_floor(mpfr(5.4))
5
```

sage.arith.misc.integer_trunc(i)

Truncate to the integer closer to zero.

EXAMPLES:

```
sage: from sage.arith.misc import integer_trunc as trunc
sage: trunc(-3/2), trunc(-1), trunc(-1/2), trunc(0), trunc(1/2), trunc(1), trunc(3/2)
(-1, -1, 0, 0, 0, 1, 1)
sage: isinstance(trunc(3/2), Integer)
True
```

sage.arith.misc.inverse_mod(a, m)

The inverse of the ring element a modulo m.

If no special inverse_mod is defined for the elements, it tries to coerce them into integers and perform the inversion there

```
sage: inverse_mod(7, 1)
0
sage: inverse_mod(5, 14)
3
sage: inverse_mod(3, -5)
2
```

Tests with numpy and mpz numbers:

```
sage: from numpy import int8
# needs numpy
sage: inverse_mod(int8(5), int8(14))
# needs numpy
```

(continues on next page)

(continued from previous page)

```
3
sage: from gmpy2 import mpz
sage: inverse_mod(mpz(5), mpz(14))
3
```

sage.arith.misc.**is_power_of_two**(*n*)

Return whether *n* is a power of 2.

INPUT:

- *n* – integer

OUTPUT: boolean

EXAMPLES:

```
sage: is_power_of_two(1024)
True
sage: is_power_of_two(1)
True
sage: is_power_of_two(24)
False
sage: is_power_of_two(0)
False
sage: is_power_of_two(-4)
False
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
needs numpy
sage: is_power_of_two(int8(16))
needs numpy
True
sage: is_power_of_two(int8(24))
needs numpy
False
sage: from gmpy2 import mpz
sage: is_power_of_two(mpz(16))
True
sage: is_power_of_two(mpz(24))
False
```

sage.arith.misc.**is_prime**(*n*)

Determine whether *n* is a prime element of its parent ring.

INPUT:

- *n* – the object for which to determine primality

Exceptional special cases:

- For integers, determine whether *n* is a *positive* prime.
- For number fields except **Q**, determine whether *n* is a prime element *of the maximal order*.

ALGORITHM:

For integers, this function uses a provable primality test or a strong pseudo-primality test depending on the global `arithmetic proof flag`.

See also

- `is_pseudoprime()`
- `sage.rings.integer.Integer.is_prime()`

EXAMPLES:

```
sage: is_prime(389)
True
sage: is_prime(2000)
False
sage: is_prime(2)
True
sage: is_prime(-1)
False
sage: is_prime(1)
False
sage: is_prime(-2)
False
```

```
sage: a = 2**2048 + 981
sage: is_prime(a)      # not tested - takes ~ 1min
sage: proof.arithmetic(False)
sage: is_prime(a)      # instantaneous!
# needs sage.libs.pari
True
sage: proof.arithmetic(True)
```

`sage.arith.misc.is_prime_power(n, get_data=False)`

Test whether n is a positive power of a prime number.

This function simply calls the method `Integer.is_prime_power()` of Integers.

INPUT:

- n – integer
- `get_data` – if set to True, return a pair (p, k) such that this integer equals p^k instead of True or `(self, 0)` instead of False

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: is_prime_power(389)
True
sage: is_prime_power(2000)
False
sage: is_prime_power(2)
True
sage: is_prime_power(1024)
True
sage: is_prime_power(1024, get_data=True)
(2, 10)
```

The same results can be obtained with:

```
sage: # needs sage.libs.pari
sage: 389.is_prime_power()
True
sage: 2000.is_prime_power()
False
sage: 2.is_prime_power()
True
sage: 1024.is_prime_power()
True
sage: 1024.is_prime_power(get_data=True)
(2, 10)
```

`sage.arith.misc.is_pseudoprime(n)`

Test whether n is a pseudo-prime.

The result is *NOT* proven correct - *this is a pseudo-primality test!*.

INPUT:

- n – integer

Note

We do not consider negatives of prime numbers as prime.

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: is_pseudoprime(389)
True
sage: is_pseudoprime(2000)
False
sage: is_pseudoprime(2)
True
sage: is_pseudoprime(-1)
False
sage: factor(-6)
-1 * 2 * 3
sage: is_pseudoprime(1)
False
sage: is_pseudoprime(-2)
False
```

`sage.arith.misc.is_pseudoprime_power(n, get_data=False)`

Test if n is a power of a pseudoprime.

The result is *NOT* proven correct - *this IS a pseudo-primality test!*. Note that a prime power is a positive power of a prime number so that 1 is not a prime power.

INPUT:

- n – integer
- `get_data` – boolean (default: `False`); instead of a boolean return a pair (p, k) so that n equals p^k and p is a pseudoprime or $(n, 0)$ otherwise

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: is_pseudoprime_power(389)
True
sage: is_pseudoprime_power(2000)
False
sage: is_pseudoprime_power(2)
True
sage: is_pseudoprime_power(1024)
True
sage: is_pseudoprime_power(-1)
False
sage: is_pseudoprime_power(1)
False
sage: is_pseudoprime_power(997^100)
True
```

Use of the get_data keyword:

```
sage: # needs sage.libs.pari
sage: is_pseudoprime_power(3^1024, get_data=True)
(3, 1024)
sage: is_pseudoprime_power(2^256, get_data=True)
(2, 256)
sage: is_pseudoprime_power(31, get_data=True)
(31, 1)
sage: is_pseudoprime_power(15, get_data=True)
(15, 0)
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int16
needs numpy
sage: is_pseudoprime_power(int16(1024))
needs numpy sage.libs.pari
True
sage: from gmpy2 import mpz
sage: is_pseudoprime_power(mpz(1024))
True
```

sage.arith.misc.is_square(*n*, root=False)

Return whether or not *n* is square.

If *n* is a square also return the square root. If *n* is not square, also return None.

INPUT:

- *n* – integer
- *root* – whether or not to also return a square root (default: False)

OUTPUT:

- bool – whether or not a square
- object – (optional) an actual square if found, and None otherwise

EXAMPLES:

```
sage: is_square(2)
False
```

(continues on next page)

(continued from previous page)

```
sage: is_square(4)
True
sage: is_square(2.2)
True
sage: is_square(-2.2)
False
sage: is_square(CDF(-2.2))
# needs sage.rings.complex_double
True
sage: is_square((x-1)^2)
# needs sage.symbolic
Traceback (most recent call last):
...
NotImplementedError: is_square() not implemented for
non-constant or relational elements of Symbolic Ring
```

```
sage: is_square(4, True)
(True, 2)
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
# needs numpy
sage: is_square(int8(4))
# needs numpy
True
sage: from gmpy2 import mpz
sage: is_square(mpz(4))
True
```

Tests with Polynomial:

```
sage: R.<v> = LaurentPolynomialRing(QQ, 'v')
sage: H = IwahoriHeckeAlgebra('A3', v**2)
# needs sage.combinat sage.modules
sage: R.<a,b,c,d> = QQ[]
sage: p = a*b + c*d*a*d*a + 5
sage: is_square(p**2)
True
```

`sage.arith.misc.is_squarefree(n)`

Test whether n is square free.

EXAMPLES:

```
sage: is_squarefree(100)
# needs sage.libs.pari
False
sage: is_squarefree(101)
# needs sage.libs.pari
True

sage: R = ZZ['x']
sage: x = R.gen()
sage: is_squarefree((x^2+x+1) * (x-2))
# needs sage.libs.pari
```

(continues on next page)

(continued from previous page)

```

True
sage: is_squarefree((x-1)**2 * (x-3))                                     #_
˓needs sage.libs.pari
False

sage: # needs sage.rings.number_field sage.symbolic
sage: O = ZZ[sqrt(-1)]
sage: I = O.gen(1)
sage: is_squarefree(I + 1)
True
sage: is_squarefree(O(2))
False
sage: O(2).factor()
(-I) * (I + 1)^2

```

This method fails on domains which are not Unique Factorization Domains:

```

sage: O = ZZ[sqrt(-5)]
˓needs sage.rings.number_field sage.symbolic
sage: a = O.gen(1)
˓needs sage.rings.number_field sage.symbolic
sage: is_squarefree(a - 3)                                                 #_
˓needs sage.rings.number_field sage.symbolic
Traceback (most recent call last):
...
ArithmeError: non-principal ideal in factorization

```

Tests with numpy and gmpy2 numbers:

```

sage: # needs sage.libs.pari
sage: from numpy import int8                                         #_
˓needs numpy
sage: is_squarefree(int8(100))                                         #_
˓needs numpy
False
sage: is_squarefree(int8(101))                                         #_
˓needs numpy
True
sage: from gmpy2 import mpz
sage: is_squarefree(mpz(100))
False
sage: is_squarefree(mpz(101))
True

```

`sage.arith.misc.jacobi_symbol(a, b)`

The Jacobi symbol of integers a and b , where b is odd.

Note

The `kronecker_symbol()` command extends the Jacobi symbol to all integers b .

If

$$b = p_1^{e_1} * \dots * p_r^{e_r}$$

then

$$(a|b) = (a|p_1)^{e_1} \dots (a|p_r)^{e_r}$$

where $(a|p_j)$ are Legendre Symbols.

INPUT:

- a – integer
- b – odd integer

EXAMPLES:

```
sage: jacobi_symbol(10, 777)
-1
sage: jacobi_symbol(10, 5)
0
sage: jacobi_symbol(10, 2)
Traceback (most recent call last):
...
ValueError: second input must be odd, 2 is not odd
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int16
needs numpy
sage: jacobi_symbol(int16(10), int16(777))
needs numpy
-1
sage: from gmpy2 import mpz
sage: jacobi_symbol(mpz(10), mpz(777))
-1
```

`sage.arith.misc.kronecker(x, y)`

The Kronecker symbol $(x|y)$.

INPUT:

- x – integer
- y – integer

OUTPUT: integer

EXAMPLES:

```
sage: kronecker_symbol(13, 21)
-1
sage: kronecker_symbol(101, 4)
1
```

This is also available as `kronecker()`:

```
sage: kronecker(3, 5)
-1
sage: kronecker(3, 15)
0
sage: kronecker(2, 15)
1
sage: kronecker(-2, 15)
-1
sage: kronecker(2/3, 5)
1
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8          #_
˓needs numpy
sage: kronecker_symbol(int8(13),int8(21))          #_
˓needs numpy
-1
sage: from gmpy2 import mpz
sage: kronecker_symbol(mpz(13),mpz(21))
-1
```

sage.arith.misc.**kronecker_symbol**(x, y)

The Kronecker symbol ($x|y$).

INPUT:

- x – integer
- y – integer

OUTPUT: integer

EXAMPLES:

```
sage: kronecker_symbol(13,21)
-1
sage: kronecker_symbol(101,4)
1
```

This is also available as `kronecker()`:

```
sage: kronecker(3,5)
-1
sage: kronecker(3,15)
0
sage: kronecker(2,15)
1
sage: kronecker(-2,15)
-1
sage: kronecker(2/3,5)
1
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8          #_
˓needs numpy
sage: kronecker_symbol(int8(13),int8(21))          #_
˓needs numpy
-1
sage: from gmpy2 import mpz
sage: kronecker_symbol(mpz(13),mpz(21))
-1
```

sage.arith.misc.**legendre_symbol**(x, p)

The Legendre symbol ($x|p$), for p prime.

Note

The `kronecker_symbol()` command extends the Legendre symbol to composite moduli and $p = 2$.

INPUT:

- x – integer
- p – odd prime number

EXAMPLES:

```
sage: legendre_symbol(2, 3)
-1
sage: legendre_symbol(1, 3)
1
sage: legendre_symbol(1, 2)
Traceback (most recent call last):
...
ValueError: p must be odd
sage: legendre_symbol(2, 15)
Traceback (most recent call last):
...
ValueError: p must be a prime
sage: kronecker_symbol(2, 15)
1
sage: legendre_symbol(2/3, 7)
-1
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
  ↪needs numpy
#_
sage: legendre_symbol(int8(2), int8(3))
  ↪needs numpy
#_
-1
sage: from gmpy2 import mpz
sage: legendre_symbol(mpz(2), mpz(3))
-1
```

`sage.arith.misc.mqrr_rational_reconstruction(u, m, T)`

Maximal Quotient Rational Reconstruction.

For research purposes only - this is pure Python, so slow.

INPUT:

- u, m, T – integers such that $m > u \geq 0, T > 0$

OUTPUT:

Either integers n, d such that $d > 0, \gcd(n, d) = 1, n/d = u \bmod m$, and $T \cdot d \cdot |n| < m$, or `None`.

Reference: Monagan, Maximal Quotient Rational Reconstruction: An Almost Optimal Algorithm for Rational Reconstruction (page 11)

This algorithm is probabilistic.

EXAMPLES:

```
sage: mqrr_rational_reconstruction(21, 3100, 13)
(21, 1)
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int16          #_
˓needs numpy
sage: mqrr_rational_reconstruction(int16(21), int16(3100), int16(13))      #_
˓needs numpy
(21, 1)
sage: from gmpy2 import mpz
sage: mqrr_rational_reconstruction(mpz(21), mpz(3100), mpz(13))
(21, 1)
```

`sage.arith.misc.multinomial(*ks)`

Return the multinomial coefficient.

INPUT:

- either an arbitrary number of integer arguments k_1, \dots, k_n
- or an iterable (e.g. a list) of integers $[k_1, \dots, k_n]$

OUTPUT: the integer:

$$\binom{k_1 + \cdots + k_n}{k_1, \dots, k_n} = \frac{(\sum_{i=1}^n k_i)!}{\prod_{i=1}^n k_i!} = \prod_{i=1}^n \binom{\sum_{j=1}^i k_j}{k_i}$$

EXAMPLES:

```
sage: multinomial(0, 0, 2, 1, 0, 0)
3
sage: multinomial([0, 0, 2, 1, 0, 0])
3
sage: multinomial(3, 2)
10
sage: multinomial(2^30, 2, 1)
618970023101454657175683075
sage: multinomial([2^30, 2, 1])
618970023101454657175683075
sage: multinomial(Composition([1, 3]))
4
sage: multinomial(Partition([4, 2]))          #_
˓needs sage.combinat
15
```

AUTHORS:

- Gabriel Ebner

`sage.arith.misc.multinomial_coefficients(m, n)`

Return a dictionary containing pairs $\{(k_1, k_2, \dots, k_m) : C_{k,n}\}$ where $C_{k,n}$ are multinomial coefficients such that $n = k_1 + k_2 + \dots + k_m$.

INPUT:

- m – integer
- n – integer

OUTPUT: dictionary

EXAMPLES:

```
sage: sorted(multinomial_coefficients(2, 5).items())
[((0, 5), 1), ((1, 4), 5), ((2, 3), 10), ((3, 2), 10), ((4, 1), 5), ((5, 0), 1)]
```

Notice that these are the coefficients of $(x+y)^5$:

```
sage: R.<x,y> = QQ[]
sage: (x+y)^5
x^5 + 5*x^4*y + 10*x^3*y^2 + 10*x^2*y^3 + 5*x*y^4 + y^5
```

```
sage: sorted(multinomial_coefficients(3, 2).items())
[((0, 0, 2), 1), ((0, 1, 1), 2), ((0, 2, 0), 1), ((1, 0, 1), 2), ((1, 1, 0), 2),
 ((2, 0, 0), 1)]
```

ALGORITHM: The algorithm we implement for computing the multinomial coefficients is based on the following result:

$$\binom{n}{k_1, \dots, k_m} = \frac{k_1+1}{n-k_1} \sum_{i=2}^m \binom{n}{k_1+1, \dots, k_i-1, \dots}$$

e.g.:

```
sage: k = (2, 4, 1, 0, 2, 6, 0, 0, 3, 5, 7, 1) # random value
sage: n = sum(k)
sage: s = 0
sage: for i in range(1, len(k)):
....:     ki = list(k)
....:     ki[0] += 1
....:     ki[i] -= 1
....:     s += multinomial(n, *ki)
sage: multinomial(n, *k) == (k[0] + 1) / (n - k[0]) * s
True
```

sage.arith.misc.next_prime(*n*, proof=None)

The next prime greater than the integer *n*. If *n* is prime, then this function does not return *n*, but the next prime after *n*. If the optional argument proof is False, this function only returns a pseudo-prime, as defined by the PARI nextprime function. If it is None, uses the global default (see sage.structure.proof.proof)

INPUT:

- *n* – integer
- *proof* – boolean or None (default: None)

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: next_prime(-100)
2
sage: next_prime(1)
2
sage: next_prime(2)
3
sage: next_prime(3)
5
sage: next_prime(4)
5
```

Notice that the next_prime(5) is not 5 but 7.

```
sage: next_prime(5) #_
˓needs sage.libs.pari
7
sage: next_prime(2004) #_
˓needs sage.libs.pari
2011
```

sage.arith.misc.**next_prime_power**(*n*)

Return the smallest prime power greater than *n*.

Note that if *n* is a prime power, then this function does not return *n*, but the next prime power after *n*.

This function just calls the method *Integer.next_prime_power()* of Integers.

See also

- *is_prime_power()* (and *Integer.is_prime_power()*)
- *previous_prime_power()* (and *Integer.previous_prime_power()*)

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: next_prime_power(1)
2
sage: next_prime_power(2)
3
sage: next_prime_power(10)
11
sage: next_prime_power(7)
8
sage: next_prime_power(99)
101
```

The same results can be obtained with:

```
sage: 1.next_prime_power()
2
sage: 2.next_prime_power()
3
sage: 10.next_prime_power()
11
```

Note that 2 is the smallest prime power:

```
sage: next_prime_power(-10)
2
sage: next_prime_power(0)
2
```

sage.arith.misc.**next_probable_prime**(*n*)

Return the next probable prime after self, as determined by PARI.

INPUT:

- *n* – integer

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: next_probable_prime(-100)
2
sage: next_probable_prime(19)
23
sage: next_probable_prime(int(99999999))
1000000007
sage: next_probable_prime(2^768)
155251809230070893514897948846250255525688601711669661113905203802605095268637688633087840882864
```

`sage.arith.misc.nth_prime(n)`

Return the n -th prime number (1-indexed, so that 2 is the 1st prime).

INPUT:

- n – positive integer

OUTPUT: the n -th prime number

EXAMPLES:

```
sage: nth_prime(3)                                     #
˓needs sage.libs.pari
5
sage: nth_prime(10)                                    #
˓needs sage.libs.pari
29
sage: nth_prime(10^7)                                  #
˓needs sage.libs.pari
179424673
```

```
sage: nth_prime(0)
Traceback (most recent call last):
...
ValueError: nth prime meaningless for nonpositive n (=0)
```

`sage.arith.misc.number_of_divisors(n)`

Return the number of divisors of the integer n .

INPUT:

- n – nonzero integer

OUTPUT: integer; the number of divisors of n

EXAMPLES:

```
sage: number_of_divisors(100)                         #
˓needs sage.libs.pari
9
sage: number_of_divisors(-720)                         #
˓needs sage.libs.pari
30
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8 #_
˓needs numpy
sage: number_of_divisors(int8(100)) #_
˓needs numpy sage.libs.pari
9
sage: from gmpy2 import mpz #_
sage: number_of_divisors(mpz(100)) #_
˓needs sage.libs.pari
9
```

sage.arith.misc.**odd_part**(*n*)

The odd part of the integer *n*. This is $n/2^v$, where $v = \text{valuation}(n, 2)$.

EXAMPLES:

```
sage: odd_part(5)
5
sage: odd_part(4)
1
sage: odd_part(factorial(31))
122529844256906551386796875
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8 #_
˓needs numpy
sage: odd_part(int8(5)) #_
˓needs numpy
5
sage: from gmpy2 import mpz #_
sage: odd_part(mpz(5))
5
```

sage.arith.misc.**power_mod**(*a*, *n*, *m*)

Return the *n*-th power of *a* modulo *m*, where *a* and *m* are elements of a ring that implements the modulo operator %.

ALGORITHM: square-and-multiply

EXAMPLES:

```
sage: power_mod(2, 388, 389)
1
sage: power_mod(2, 390, 391)
285
sage: power_mod(2, -1, 7)
4
sage: power_mod(11, 1, 7)
4
```

This function works for fairly general rings:

```
sage: R.<x> = ZZ[]
sage: power_mod(3*x, 10, 7)
4*x^10
sage: power_mod(-3*x^2 + 4, 7, 2*x^3 - 5)
x^14 + x^8 + x^6 + x^3 + 962509*x^2 - 791910*x - 698281
```

`sage.arith.misc.previous_prime(n)`

The largest prime < n. The result is provably correct. If n <= 1, this function raises a `ValueError`.

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: previous_prime(10)
7
sage: previous_prime(7)
5
sage: previous_prime(8)
7
sage: previous_prime(7)
5
sage: previous_prime(5)
3
sage: previous_prime(3)
2
sage: previous_prime(2)
Traceback (most recent call last):
...
ValueError: no previous prime
sage: previous_prime(1)
Traceback (most recent call last):
...
ValueError: no previous prime
sage: previous_prime(-20)
Traceback (most recent call last):
...
ValueError: no previous prime
```

`sage.arith.misc.previous_prime_power(n)`

Return the largest prime power smaller than n.

The result is provably correct. If n is smaller or equal than 2 this function raises an error.

This function simply call the method `Integer.previous_prime_power()` of Integers.

See also

- `is_prime_power()` (and `Integer.is_prime_power()`)
- `next_prime_power()` (and `Integer.next_prime_power()`)

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: previous_prime_power(3)
2
sage: previous_prime_power(10)
9
sage: previous_prime_power(7)
5
sage: previous_prime_power(127)
125
```

The same results can be obtained with:

```
sage: # needs sage.libs.pari
sage: 3.previous_prime_power()
2
sage: 10.previous_prime_power()
9
sage: 7.previous_prime_power()
5
sage: 127.previous_prime_power()
125
```

Input less than or equal to 2 raises errors:

```
sage: previous_prime_power(2)
Traceback (most recent call last):
...
ValueError: no prime power less than 2
sage: previous_prime_power(-10)
Traceback (most recent call last):
...
ValueError: no prime power less than 2
```

```
sage: n = previous_prime_power(2^16 - 1) #_
  ↵needs sage.libs.pari
sage: while is_prime(n): #_
  ↵needs sage.libs.pari
....:     n = previous_prime_power(n)
sage: factor(n) #_
  ↵needs sage.libs.pari
251^2
```

`sage.arith.misc.prime_divisors(n)`

Return the list of prime divisors (up to units) of this element of a unique factorization domain.

INPUT:

- n – any object which can be decomposed into prime factors

OUTPUT:

A list of prime factors of n . For integers, this list is sorted in increasing order.

EXAMPLES:

Prime divisors of positive integers:

```
sage: prime_divisors(1)
[]
sage: prime_divisors(100)
[2, 5]
sage: prime_divisors(2004)
[2, 3, 167]
```

If n is negative, we do *not* include -1 among the prime divisors, since -1 is not a prime number:

```
sage: prime_divisors(-100)
[2, 5]
```

For polynomials we get all irreducible factors:

```
sage: R.<x> = PolynomialRing(QQ)
sage: prime_divisors(x^12 - 1)
# needs sage.libs.pari
[x - 1, x + 1, x^2 - x + 1, x^2 + 1, x^2 + x + 1, x^4 - x^2 + 1]
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
# needs numpy
sage: prime_divisors(int8(-100))
# needs numpy
[2, 5]
sage: from gmpy2 import mpz
sage: prime_divisors(mpz(-100))
[2, 5]
```

`sage.arith.misc.prime_factors(n)`

Return the list of prime divisors (up to units) of this element of a unique factorization domain.

INPUT:

- n – any object which can be decomposed into prime factors

OUTPUT:

A list of prime factors of n . For integers, this list is sorted in increasing order.

EXAMPLES:

Prime divisors of positive integers:

```
sage: prime_divisors(1)
[]
sage: prime_divisors(100)
[2, 5]
sage: prime_divisors(2004)
[2, 3, 167]
```

If n is negative, we do *not* include -1 among the prime divisors, since -1 is not a prime number:

```
sage: prime_divisors(-100)
[2, 5]
```

For polynomials we get all irreducible factors:

```
sage: R.<x> = PolynomialRing(QQ)
sage: prime_divisors(x^12 - 1)
# needs sage.libs.pari
[x - 1, x + 1, x^2 - x + 1, x^2 + 1, x^2 + x + 1, x^4 - x^2 + 1]
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
# needs numpy
sage: prime_divisors(int8(-100))
# needs numpy
[2, 5]
sage: from gmpy2 import mpz
sage: prime_divisors(mpz(-100))
[2, 5]
```

```
sage.arith.misc.prime_powers(start, stop=None)
```

List of all positive primes powers between `start` and `stop-1`, inclusive. If the second argument is omitted, returns the prime powers up to the first argument.

INPUT:

- `start` – integer; if two inputs are given, a lower bound for the returned set of prime powers. If this is the only input, then it is an upper bound.
- `stop` – integer (default: `None`); an upper bound for the returned set of prime powers

OUTPUT:

The set of all prime powers between `start` and `stop` or, if only one argument is passed, the set of all prime powers between 1 and `start`. The number n is a prime power if $n = p^k$, where p is a prime number and k is a positive integer. Thus, 1 is not a prime power.

EXAMPLES:

```
sage: prime_powers(20) #_
˓needs sage.libs.pari
[2, 3, 4, 5, 7, 8, 9, 11, 13, 16, 17, 19]
sage: len(prime_powers(1000)) #_
˓needs sage.libs.pari
193
sage: len(prime_range(1000)) #_
˓needs sage.libs.pari
168

sage: # needs sage.libs.pari
sage: a = [z for z in range(95, 1234) if is_prime_power(z)]
sage: b = prime_powers(95, 1234)
sage: len(b)
194
sage: len(a)
194
sage: a[:10]
[97, 101, 103, 107, 109, 113, 121, 125, 127, 128]
sage: b[:10]
[97, 101, 103, 107, 109, 113, 121, 125, 127, 128]
sage: a == b
True

sage: prime_powers(100) == [i for i in range(100) if is_prime_power(i)] #_
˓needs sage.libs.pari
True

sage: prime_powers(10, 7)
[]
sage: prime_powers(-5)
[]
sage: prime_powers(-1, 3) #_
˓needs sage.libs.pari
[2]
```

```
sage.arith.misc.prime_to_m_part(n, m)
```

Return the prime-to- m part of n .

This is the largest divisor of n that is coprime to m .

INPUT:

- n – integer (nonzero)
- m – integer

OUTPUT: integer

EXAMPLES:

```
sage: prime_to_m_part(240, 2)
15
sage: prime_to_m_part(240, 3)
80
sage: prime_to_m_part(240, 5)
48
sage: prime_to_m_part(43434, 20)
21717
```

Note that integers also have a method with the same name:

```
sage: 240.prime_to_m_part(2)
15
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int16
      ↵needs numpy
sage: prime_to_m_part(int16(240), int16(2))
      ↵needs numpy
15
sage: from gmpy2 import mpz
sage: prime_to_m_part(mpz(240), mpz(2))
15
```

`sage.arith.misc.primes(start=2, stop=None, proof=None)`

Return an iterator over all primes between `start` and `stop-1`, inclusive. This is much slower than `prime_range()`, but potentially uses less memory. As with `next_prime()`, the optional argument `proof` controls whether the numbers returned are guaranteed to be prime or not.

This command is like the Python 3 `range()` command, except it only iterates over primes. In some cases it is better to use `primes()` than `prime_range()`, because `primes()` does not build a list of all primes in the range in memory all at once. However, it is potentially much slower since it simply calls the `next_prime()` function repeatedly, and `next_prime()` is slow.

INPUT:

- `start` – integer (default: 2); lower bound for the primes
- `stop` – integer (or infinity); upper (open) bound for the primes
- `proof` – boolean or None (default: None); if True, the function yields only proven primes. If False, the function uses a pseudo-primality test, which is much faster for really big numbers but does not provide a proof of primality. If None, uses the global default (see `sage.structure.proof.proof`)

OUTPUT: an iterator over primes from `start` to `stop-1`, inclusive

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: for p in primes(5, 10):
....:     print(p)
5
```

(continues on next page)

(continued from previous page)

```
sage.arith.misc.primes_first_n(n, leave pari=False)
```

Return the first n primes.

INPUT:

- n – nonnegative integer

OUTPUT: list of the first n prime numbers

EXAMPLES:

```
sage: primes_first_n(10)
→needs sage.libs.pari
[2, 3, 5, 7, 11, 13, 17,
sage: len(primes_first_n(10))
→needs sage.libs.pari
1000
sage: primes_first_n(0)
[]

```

```
sage.arith.misc.primitive_root(n, check=True)
```

Return a positive integer that generates the multiplicative group of integers modulo n , if one exists; otherwise, raise a `ValueError`.

A primitive root exists if $n = 4$ or $n = p^k$ or $n = 2p^k$, where p is an odd prime and k is a nonnegative number.

INPUT:

- n – nonzero integer
 - `check` – boolean (default: `True`); if `False`, then n is assumed to be a positive integer possessing a primitive root, and behavior is undefined otherwise.

OUTPUT:

A primitive root of n . If n is prime, this is the smallest primitive root.

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: primitive_root(23)
5
sage: primitive_root(-46)
5
sage: primitive_root(25)
2
sage: print([primitive_root(p) for p in primes(100)])
[1, 2, 2, 3, 2, 2, 3, 2, 5, 2, 3, 2, 6, 3, 5, 2, 2, 2, 2, 7, 5, 3, 2, 3, 5]
sage: primitive_root(8)
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: no primitive root
```

Note

It takes extra work to check if n has a primitive root; to avoid this, use `check=False`, which may slightly speed things up (but could also result in undefined behavior). For example, the second call below is an order of magnitude faster than the first:

```
sage: n = 10^50 + 151 # a prime
sage: primitive_root(n) #_
˓needs sage.libs.pari
11
sage: primitive_root(n, check=False) #_
˓needs sage.libs.pari
11
```

`sage.arith.misc.quadratic_residues(n)`

Return a sorted list of all squares modulo the integer n in the range $0 \leq x < |n|$.

EXAMPLES:

```
sage: quadratic_residues(11)
[0, 1, 3, 4, 5, 9]
sage: quadratic_residues(1)
[0]
sage: quadratic_residues(2)
[0, 1]
sage: quadratic_residues(8)
[0, 1, 4]
sage: quadratic_residues(-10)
[0, 1, 4, 5, 6, 9]
sage: v = quadratic_residues(1000); len(v)
159
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8 #_
˓needs numpy
sage: quadratic_residues(int8(11)) #_
˓needs numpy
[0, 1, 3, 4, 5, 9]
sage: from gmpy2 import mpz
sage: quadratic_residues(mpz(11))
[0, 1, 3, 4, 5, 9]
```

`sage.arith.misc.radical(n, *args, **kwds)`

Return the product of the prime divisors of n .

This calls `n.radical(*args, **kwds)`.

EXAMPLES:

```
sage: radical(2 * 3^2 * 5^5)
30
sage: radical(0)
Traceback (most recent call last):
...
ArithmetricError: radical of 0 is not defined
sage: K.<i> = QuadraticField(-1)                                              # ...
    ↵needs sage.rings.number_field
sage: radical(K(2))                                                               # ...
    ↵needs sage.rings.number_field
i + 1
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8                                                 # ...
    ↵needs numpy
sage: radical(int8(50))                                                       # ...
    ↵needs numpy
10
sage: from gmpy2 import mpz
sage: radical(mpz(50))
10
```

`sage.arith.misc.random_prime(n, proof=None, lbound=2)`

Return a random prime p between lbound and n .

The returned prime p satisfies $\text{lbound} \leq p \leq n$.

The returned prime p is chosen uniformly at random from the set of prime numbers less than or equal to n .

INPUT:

- n – integer ≥ 2
- `proof` – boolean or `None` (default: `None`); if `False`, the function uses a pseudo-primality test, which is much faster for really big numbers but does not provide a proof of primality. If `None`, uses the global default (see `sage.structure.proof.proof`)
- lbound – integer; ≥ 2 , lower bound for the chosen primes

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: p = random_prime(100000)
sage: p.is_prime()
True
sage: p <= 100000
True
sage: random_prime(2)
2
```

Here we generate a random prime between 100 and 200:

```
sage: p = random_prime(200, lbound=100)
sage: p.is_prime()
True
sage: 100 <= p <= 200
True
```

If all we care about is finding a pseudo prime, then we can pass in `proof=False`

```
sage: p = random_prime(200, proof=False, lbound=100) #_
˓needs sage.libs.pari
sage: p.is_pseudoprime() #_
˓needs sage.libs.pari
True
sage: 100 <= p <= 200
True
```

AUTHORS:

- Jon Hanke (2006-08-08): with standard Stein cleanup
- Jonathan Bober (2007-03-17)

`sage.arith.misc.rational_reconstruction(a, m, algorithm='fast')`

This function tries to compute x/y , where x/y is a rational number in lowest terms such that the reduction of x/y modulo m is equal to a and the absolute values of x and y are both $\leq \sqrt{m/2}$. If such x/y exists, that pair is unique and this function returns it. If no such pair exists, this function raises `ZeroDivisionError`.

An efficient algorithm for computing rational reconstruction is very similar to the extended Euclidean algorithm. For more details, see Knuth, Vol 2, 3rd ed, pages 656-657.

INPUT:

- a – integer
- m – a modulus
- `algorithm` – string (default: '`fast`')
- **'fast'** – a fast implementation using direct GMP library calls
in Cython

OUTPUT:

Numerator and denominator n, d of the unique rational number $r = n/d$, if it exists, with n and $|d| \leq \sqrt{N/2}$. Return $(0, 0)$ if no such number exists.

The algorithm for rational reconstruction is described (with a complete nontrivial proof) on pages 656-657 of Knuth, Vol 2, 3rd ed. as the solution to exercise 51 on page 379. See in particular the conclusion paragraph right in the middle of page 657, which describes the algorithm thus:

This discussion proves that the problem can be solved efficiently by applying Algorithm 4.5.2X with $u = m$ and $v = a$, but with the following replacement for step X2: If $v3 \leq \sqrt{m/2}$, the algorithm terminates. The pair $(x, y) = (|v2|, v3 * \text{sign}(v2))$ is then the unique solution, provided that x and y are coprime and $x \leq \sqrt{m/2}$; otherwise there is no solution. (Alg 4.5.2X is the extended Euclidean algorithm.)

Knuth remarks that this algorithm is due to Wang, Kornerup, and Gregory from around 1983.

EXAMPLES:

```
sage: m = 100000
sage: (119*inverse_mod(53, m))%m
11323
sage: rational_reconstruction(11323, m)
119/53
```

```
sage: rational_reconstruction(400, 1000)
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```

...
ArithmeticError: rational reconstruction of 400 (mod 1000) does not exist

sage: rational_reconstruction(3, 292393)
3
sage: a = Integers(292393)(45/97); a
204977
sage: rational_reconstruction(a, 292393, algorithm='fast')
45/97
sage: rational_reconstruction(293048, 292393)
Traceback (most recent call last):
...
ArithmeticError: rational reconstruction of 655 (mod 292393) does not exist
sage: rational_reconstruction(0, 0)
Traceback (most recent call last):
...
ZeroDivisionError: rational reconstruction with zero modulus
sage: rational_reconstruction(0, 1, algorithm='foobar')
Traceback (most recent call last):
...
ValueError: unknown algorithm 'foobar'
```

Tests with numpy and gmpy2 numbers:

```

sage: from numpy import int32
#_
↳ needs numpy
sage: rational_reconstruction(int32(3), int32(292393))
#_
↳ needs numpy
3
sage: from gmpy2 import mpz
sage: rational_reconstruction(mpz(3), mpz(292393))
3
```

sage.arith.misc.rising_factorial(x, a)

Return the rising factorial $(x)^a$.

The notation in the literature is a mess: often $(x)^a$, but there are many other notations: GKP: Concrete Mathematics uses $x^{\bar{a}}$.

The rising factorial is also known as the Pochhammer symbol, see Maple and Mathematica.

Definition: for integer $a \geq 0$ we have $x(x+1)\cdots(x+a-1)$. In all other cases we use the GAMMA-function:
 $\frac{\Gamma(x+a)}{\Gamma(x)}$.

INPUT:

- x – element of a ring
- a – nonnegative integer or
- x, a – any numbers

OUTPUT: the rising factorial

See also

[falling_factorial\(\)](#)

EXAMPLES:

```
sage: rising_factorial(10, 3)
1320

sage: # needs sage.symbolic
sage: rising_factorial(10, RR('3.0'))
1320.00000000000
sage: rising_factorial(10, RR('3.3'))
2826.38895824964
sage: a = rising_factorial(1+I, I); a
gamma(2*I + 1)/gamma(I + 1)
sage: CC(a)
0.266816390637832 + 0.122783354006372*I
sage: a = rising_factorial(I, 4); a
-10

sage: x = polygen(ZZ)
sage: rising_factorial(x, 4)
x^4 + 6*x^3 + 11*x^2 + 6*x
```

AUTHORS:

- Jaap Spies (2006-03-05)

`sage.arith.misc.smooth_part(x, base)`

Given an element x of a Euclidean domain and a factor base $base$, return a `Factorization` object corresponding to the largest divisor of x that splits completely over $base$.

The factor base can be specified in the following ways:

- A sequence of elements.
- A `ProductTree` built from such a sequence. (Caching the tree in the caller will speed things up if this function is called multiple times with the same factor base.)

EXAMPLES:

```
sage: from sage.arith.misc import smooth_part
sage: from sage.rings.generic import ProductTree
sage: smooth_part(10^77+1, primes(1000))
11^2 * 23 * 463
sage: tree = ProductTree(primes(1000))
sage: smooth_part(10^77+1, tree)
11^2 * 23 * 463
sage: smooth_part(10^99+1, tree)
7 * 11^2 * 13 * 19 * 23
```

`sage.arith.misc.sort_complex_numbers_for_display(nums)`

Given a list of complex numbers (or a list of tuples, where the first element of each tuple is a complex number), we sort the list in a “pretty” order.

Real numbers (with a zero imaginary part) come before complex numbers, and are sorted. Complex numbers are sorted by their real part unless their real parts are quite close, in which case they are sorted by their imaginary part.

This is not a useful function mathematically (not least because there is no principled way to determine whether the real components should be treated as equal or not). It is called by various polynomial root-finders; its purpose is to make doctest printing more reproducible.

We deliberately choose a cumbersome name for this function to discourage use, since it is mathematically meaningless.

EXAMPLES:

```
sage: # needs sage.rings.complex_double
sage: import sage.arith.misc
sage: sort_c = sort_complex_numbers_for_display
sage: nums = [CDF(i) for i in range(3)]
sage: for i in range(3):
....:     nums.append(CDF(i + RDF.random_element(-3e-11, 3e-11),
....:                     RDF.random_element()))
....:     nums.append(CDF(i + RDF.random_element(-3e-11, 3e-11),
....:                     RDF.random_element()))
sage: shuffle(nums)
sage: nums = sort_c(nums)
sage: for i in range(len(nums)):
....:     if nums[i].imag():
....:         first_non_real = i
....:         break
....: else:
....:     first_non_real = len(nums)
sage: assert first_non_real >= 3
sage: for i in range(first_non_real - 1):
....:     assert nums[i].real() <= nums[i + 1].real()
sage: def truncate(n):
....:     if n.real() < 1e-10:
....:         return 0
....:     else:
....:         return n.real().n(digits=9)
sage: for i in range(first_non_real, len(nums)-1):
....:     assert truncate(nums[i]) <= truncate(nums[i + 1])
....:     if truncate(nums[i]) == truncate(nums[i + 1]):
....:         assert nums[i].imag() <= nums[i+1].imag()
```

`sage.arith.misc.squarefree_divisors(x)`

Return an iterator over the squarefree divisors (up to units) of this ring element.

Depends on the output of the prime_divisors function.

Squarefree divisors of an integer are not necessarily yielded in increasing order.

INPUT:

- x – an element of any ring for which the prime_divisors function works

EXAMPLES:

Integers with few prime divisors:

```
sage: list(squarefree_divisors(7))
[1, 7]
sage: list(squarefree_divisors(6))
[1, 2, 3, 6]
sage: list(squarefree_divisors(12))
[1, 2, 3, 6]
```

Squarefree divisors are not yielded in increasing order:

```
sage: list(squarefree_divisors(30))
[1, 2, 3, 6, 5, 10, 15, 30]
```

```
sage.arith.misc.subfactorial(n)
```

Subfactorial or rencontres numbers, or derangements: number of permutations of n elements with no fixed points.

INPUT:

- n – nonnegative integer

OUTPUT: integer

EXAMPLES:

```
sage: subfactorial(0)
1
sage: subfactorial(1)
0
sage: subfactorial(8)
14833
```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8
↳ needs numpy
sage: subfactorial(int8(8))
↳ needs numpy
14833
sage: from gmpy2 import mpz
sage: subfactorial(mpz(8))
14833
```

AUTHORS:

- Jaap Spies (2007-01-23)

```
sage.arith.misc.sum_of_k_squares(k, n)
```

Write the integer n as a sum of k integer squares if possible; otherwise raise a `ValueError`.

INPUT:

- k – nonnegative integer
- n – integer

OUTPUT: a tuple (x_1, \dots, x_k) of nonnegative integers such that their squares sum to n .

EXAMPLES:

```
sage: sum_of_k_squares(2, 9634)
(15, 97)
sage: sum_of_k_squares(3, 9634)
(0, 15, 97)
sage: sum_of_k_squares(4, 9634)
(1, 2, 5, 98)
sage: sum_of_k_squares(5, 9634)
(0, 1, 2, 5, 98)
sage: sum_of_k_squares(6, 11^1111 - 1)
↳ needs sage.libs.pari
(19215400822645944253860920437586326284, 37204645194585992174252915693267578306,
3473654819477394665857484221256136567800161086815834297092488779216863122,
↳
↳ 5860191799617673633547572610351797996721850737768032876360978911074629287841061578270832330322
```

(continues on next page)

(continued from previous page)

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int16
→needs numpy
sage: sum_of_k_squares(int16(2), int16(9634))
→needs numpy
(15, 97)
sage: from gmpy2 import mpz
sage: sum_of_k_squares(mpz(2), mpz(9634))
(15, 97)
```

```
sage.arith.misc.three_squares(n)
```

Write the integer n as a sum of three integer squares if possible; otherwise raise a `ValueError`.

INPUT:

- n – integer

OUTPUT: a tuple (a, b, c) of nonnegative integers such that $n = a^2 + b^2 + c^2$ with $a \leq b \leq c$.

EXAMPLES:

```

sage: three_squares(389)
(1, 8, 18)
sage: three_squares(946)
(9, 9, 28)
sage: three_squares(2986)
(3, 24, 49)
sage: three_squares(7^100)
(0, 0, 1798465042647412146620280340569649349251249)
sage: three_squares(11^111 - 1) #_
↳ needs sage.libs.pari
(616274160655975340150706442680, 901582938385735143295060746161,
 6270382387635744140394001363065311967964099981788593947233)
sage: three_squares(7 * 2^41) #_
↳ needs sage.libs.pari
(1048576, 2097152, 3145728)
sage: three_squares(7 * 2^42)
Traceback (most recent call last):
...
ValueError: 30786325577728 is not a sum of 3 squares
sage: three_squares(0)
(0, 0, 0)
sage: three_squares(-1)
Traceback (most recent call last):
...
ValueError: -1 is not a sum of 3 squares

```

ALGORITHM:

See <https://schorn.ch/lagrange.html>

`sage.arith.misc.trial_division(n, bound=None)`

Return the smallest prime divisor less than or equal to `bound` of the positive integer `n`, or `n` if there is no such prime. If the optional argument `bound` is omitted, then `bound` $\leq n$.

INPUT:

- `n` – positive integer
- `bound` – (optional) positive integer

OUTPUT: a prime `p=bound` that divides `n`, or `n` if there is no such prime

EXAMPLES:

```

sage: trial_division(15)
3
sage: trial_division(91)
7
sage: trial_division(11)
11
sage: trial_division(387833, 300)
387833
sage: # 300 is not big enough to split off a
sage: # factor, but 400 is.
sage: trial_division(387833, 400)
389

```

Tests with numpy and gmpy2 numbers:

```
sage: from numpy import int8          # ...
→needs numpy
sage: trial_division(int8(91))        # ...
→needs numpy
7
sage: from gmpy2 import mpz
sage: trial_division(mpz(91))          # ...
7
```

```
sage.arith.misc.two_squares(n)
```

Write the integer n as a sum of two integer squares if possible; otherwise raise a `ValueError`.

INPUT:

- n – integer

OUTPUT: a tuple (a, b) of nonnegative integers such that $n = a^2 + b^2$ with $a \leq b$.

EXAMPLES:

ALGORITHM:

See <https://schorn.ch/lagrange.html>

```
sage.arith.misc.valuation(m, *args, **kwds)
```

Return the valuation of m .

This function simply calls the `m.valuation()` method. See the documentation of `m.valuation()` for a more precise description.

Note that the use of this functions is discouraged as it is better to use `m.valuation()` directly.

Note

This is not always a valuation in the mathematical sense. For more information see: sage.rings.finite_rings.integer_mod.IntegerMod_int.valuation

EXAMPLES:

```
sage: valuation(512, 2)
9
sage: valuation(1, 2)
0
sage: valuation(5/9, 3)
-2
```

Valuation of 0 is defined, but valuation with respect to 0 is not:

```
sage: valuation(0, 7)
+Infinity
sage: valuation(3, 0)
Traceback (most recent call last):
...
ValueError: You can only compute the valuation with respect to a integer larger
than 1.
```

Here are some other examples:

```
sage: valuation(100, 10)
2
sage: valuation(200, 10)
2
sage: valuation(243, 3)
5
sage: valuation(243*10007, 3)
5
sage: valuation(243*10007, 10007)
1
sage: y = QQ['y'].gen()
sage: valuation(y^3, y)
3
sage: x = QQ[['x']].gen()
sage: valuation((x^3-x^2)/(x-4))
2
sage: valuation(4r, 2r)
2
sage: valuation(1r, 1r)
Traceback (most recent call last):
...
ValueError: You can only compute the valuation with respect to a integer larger
than 1.
sage: from numpy import int16
# needs numpy
sage: valuation(int16(512), int16(2))
# needs numpy
9
sage: from gmpy2 import mpz
sage: valuation(mpz(512), mpz(2))
9
```

`sage.arith.misc.xgcd(a, b=None)`

Return the greatest common divisor and the Bézout coefficients of the input arguments.

When both `a` and `b` are given, then return a triple `(g, s, t)` such that $g = s \cdot a + t \cdot b = \gcd(a, b)$. When only `a` is given, then return a tuple `r` of length `len(a) + 1` such that $r_0 = \sum_{i=0}^{\text{len}(a)-1} r_{i+1} a_i = \gcd(a_0, \dots, a_{\text{len}(a)-1})$

Note

One exception is if the elements are not in a principal ideal domain (see [Wikipedia article Principal_ideal_domain](#)), e.g., they are both polynomials over the integers. Then this function can't in general return `(g, s, t)` or `r` as above, since they need not exist. Instead, over the integers, when `a` and `b` are given, we first multiply `g` by a divisor of the resultant of a/g and b/g , up to sign.

INPUT:

One of the following:

- `a`, `b` – integers or more generally, element of a ring for which the `xgcd` make sense (e.g. a field or univariate polynomials).
- `a` – a list or tuple of at least two integers or more generally, elements of a ring which the `xgcd` make sense.

OUTPUT:

One of the following:

- `g`, `s`, `t` – when two inputs `a`, `b` are given. They satisfy $g = s \cdot a + t \cdot b$.
- `r` – a tuple, when only `a` is given (and `b = None`). Its first entry `r[0]` is the gcd of the inputs, and has length one longer than the length of `a`. Its entries satisfy $r_0 = \sum_{i=0}^{\text{len}(a)-1} r_{i+1} a_i$.

Note

There is no guarantee that the returned cofactors (`s` and `t`) are minimal.

EXAMPLES:

```
sage: xgcd(56, 44)
(4, 4, -5)
sage: 4*56 + (-5)*44
4
sage: xgcd([56, 44])
(4, 4, -5)
sage: r = xgcd([30, 105, 70, 42]); r
(1, -255, 85, -17, -2)
sage: (-255)*30 + 85*105 + (-17)*70 + (-2)*42
1
sage: xgcd([])
(0,)
sage: xgcd([42])
(42, 1)

sage: g, a, b = xgcd(5/1, 7/1); g, a, b
(1, 3, -2)
sage: a*(5/1) + b*(7/1) == g
True
```

(continues on next page)

(continued from previous page)

```

sage: x = polygen(QQ)
sage: xgcd(x^3 - 1, x^2 - 1)
(x - 1, 1, -x)
sage: g, a, b, c = xgcd([x^4 - x, x^6 - 1, x^4 - 1]); g, a, b, c
(x - 1, x^3, -x, 1)
sage: a*(x^4 - x) + b*(x^6 - 1) + c*(x^4 - 1) == g
True

sage: K.<g> = NumberField(x^2 - 3) #_
˓needs sage.rings.number_field
sage: g.xgcd(g + 2) #_
˓needs sage.rings.number_field
(1, 1/3*g, 0)

sage: # needs sage.rings.number_field
sage: R.<a,b> = K[]
sage: S.<y> = R.fraction_field() []
sage: xgcd(y^2, a*y + b)
(1, a^2/b^2, ((-a)/b^2)*y + 1/b)
sage: xgcd((b+g)*y^2, (a+g)*y + b)
(1, (a^2 + (2*g)*a + 3)/(b^3 + g*b^2), ((-a + (-g))/b^2)*y + 1/b)

```

Here is an example of a xgcd for two polynomials over the integers, where the linear combination is not the gcd but the gcd multiplied by the resultant:

```

sage: R.<x> = ZZ[]
sage: gcd(2*x*(x-1), x^2)
x
sage: xgcd(2*x*(x-1), x^2)
(2*x, -1, 2)
sage: (2*(x-1)).resultant(x) #_
˓needs sage.libs.pari
2

```

Tests with numpy and gmpy2 types:

```

sage: from numpy import int8 #_
˓needs numpy
sage: xgcd(4, int8(8)) #_
˓needs numpy
(4, 1, 0)
sage: xgcd(int8(4), int8(8)) #_
˓needs numpy
(4, 1, 0)
sage: xgcd([int8(4), int8(8), int(10)]) #_
˓needs numpy
(2, -2, 0, 1)
sage: from gmpy2 import mpz
sage: xgcd(mpz(4), mpz(8))
(4, 1, 0)
sage: xgcd(4, mpz(8))
(4, 1, 0)
sage: xgcd([4, mpz(8), mpz(10)])
(2, -2, 0, 1)

```

sage.arith.misc.**xkcd**(n=“”)

This function is similar to the xgcd function, but behaves in a completely different way.

See <https://xkcd.com/json.html> for more details.

INPUT:

- n – integer (optional)

OUTPUT: a fragment of HTML

EXAMPLES:

```
sage: xkcd(353) # optional - internet
<h1>Python</h1><div>Source: <a href="http://xkcd.com/353" target="_blank">http://xkcd.
 ↵com/353</a></div>
```

sage.arith.misc.**xlcm**(m, n)

Extended lcm function: given two positive integers m, n , returns a triple (l, m_1, n_1) such that $l = \text{lcm}(m, n) = m_1 \cdot n_1$ where $m_1|m, n_1|n$ and $\text{gcd}(m_1, n_1) = 1$, all with no factorization.

Used to construct an element of order l from elements of orders m, n in any group: see sage/groups/generic.py for examples.

EXAMPLES:

```
sage: xlcm(120, 36)
(360, 40, 9)
```

See also

- sage.sets.integer_range
- sage.sets.positive_integers
- sage.sets.non_negative_integers
- sage.sets.primes

RATIONALS

2.1 Field **Q** of Rational Numbers

The class `RationalField` represents the field **Q** of (arbitrary precision) rational numbers. Each rational number is an instance of the class `Rational`.

Interactively, an instance of `RationalField` is available as `QQ`:

```
sage: QQ
Rational Field
```

Values of various types can be converted to rational numbers by using the `__call__()` method of `RationalField` (that is, by treating `QQ` as a function).

```
sage: RealField(9).pi()                                     #
˓needs sage.rings.real_mpfr
3.1
sage: QQ(RealField(9).pi())                                 #
˓needs sage.rings.real_interval_field sage.rings.real_mpfr
22/7
sage: QQ(RealField().pi())                                  #
˓needs sage.rings.real_interval_field sage.rings.real_mpfr
245850922/78256779
sage: QQ(35)
35
sage: QQ('12/347')                                       #
12/347
sage: QQ(exp(pi*I))                                      #
˓needs sage.symbolic
-1
sage: x = polygen(ZZ)
sage: QQ((3*x)/(4*x))
3/4
```

AUTHORS:

- Niles Johnson (2010-08): Issue #3893: `random_element()` should pass on `*args` and `**kwds`.
- Travis Scrimshaw (2012-10-18): Added additional docstrings for full coverage. Removed duplicates of `discriminant()` and `signature()`.
- Anna Haensch (2018-03): Added function `quadratic_defect()`

```
class sage.rings.rational_field.RationalField
Bases: Singleton, NumberField
```

The class `RationalField` represents the field **Q** of rational numbers.

EXAMPLES:

```
sage: a = 901824309821093821093812093810928309183091832091
sage: b = QQ(a); b
901824309821093821093812093810928309183091832091
sage: QQ(b)
901824309821093821093812093810928309183091832091
sage: QQ(int(93820984323))
93820984323
sage: QQ(ZZ(901824309821093821093812093810928309183091832091))
901824309821093821093812093810928309183091832091
sage: QQ('-930482/9320842317')
-930482/9320842317
sage: QQ((-930482, 9320842317))
-930482/9320842317
sage: QQ([9320842317])
9320842317
sage: QQ(pari(39029384023840928309482842098430284398243982394)) #_
˓needs sage.libs.pari
39029384023840928309482842098430284398243982394
sage: QQ('sage')
Traceback (most recent call last):
...
TypeError: unable to convert 'sage' to a rational
```

Conversion from the reals to the rationals is done by default using continued fractions.

```
sage: QQ(RR(3929329/32))
3929329/32
sage: QQ(-RR(3929329/32))
-3929329/32
sage: QQ(RR(1/7)) - 1/7 #_
˓needs sage.rings.real_mpfr
0
```

If you specify the optional second argument `base`, then the string representation of the float is used.

```
sage: # needs sage.rings.real_mpfr
sage: QQ(23.2, 2)
6530219459687219/281474976710656
sage: 6530219459687219.0/281474976710656
23.200000000000000
sage: a = 23.2; a
23.200000000000000
sage: QQ(a, 10)
116/5
```

Here's a nice example involving elliptic curves:

```
sage: # needs sage.rings.real_mpfr sage.schemes
sage: E = EllipticCurve('11a')
sage: L = E.lseries().at1(300)[0]; L
0.2538418608559106843377589233...
sage: O = E.period_lattice().omega(); O
1.26920930427955
sage: t = L/O; t
```

(continues on next page)

(continued from previous page)

```
0.2000000000000000
sage: QQ(RealField(45)(t))
1/5
```

absolute_degree()

Return the absolute degree of **Q**, which is 1.

EXAMPLES:

```
sage: QQ.absolute_degree()
1
```

absolute_discriminant()

Return the absolute discriminant, which is 1.

EXAMPLES:

```
sage: QQ.absolute_discriminant()
1
```

absolute_polynomial()

Return a defining polynomial of **Q**, as for other number fields.

This is also aliased to `defining_polynomial()` and `absolute_polynomial()`.

EXAMPLES:

```
sage: QQ.polynomial()
x
```

algebraic_closure()

Return the algebraic closure of `self` (which is $\overline{\mathbb{Q}}$).

EXAMPLES:

```
sage: QQ.algebraic_closure()
# ...
needs sage.rings.number_field
Algebraic Field
```

automorphisms()

Return all Galois automorphisms of `self`.

OUTPUT: a sequence containing just the identity morphism

EXAMPLES:

```
sage: QQ.automorphisms()
[
Ring endomorphism of Rational Field
Defn: 1 |--> 1
]
```

characteristic()

Return 0 since the rational field has characteristic 0.

EXAMPLES:

```
sage: c = QQ.characteristic(); c
0
sage: parent(c)
Integer Ring
```

class_number()

Return the class number of the field of rational numbers, which is 1.

EXAMPLES:

```
sage: QQ.class_number()
1
```

completion(*p, prec, extras={}*)

Return the completion of **Q** at *p*.

EXAMPLES:

```
sage: QQ.completion(infinity, 53)
˓needs sage.rings.real_mpfr
Real Field with 53 bits of precision
sage: QQ.completion(5, 15, {'print_mode': 'bars'})
˓needs sage.rings.padics
5-adic Field with capped relative precision 15
```

complex_embedding(*prec=53*)

Return embedding of the rational numbers into the complex numbers.

EXAMPLES:

```
sage: QQ.complex_embedding()
˓needs sage.rings.real_mpfr
Ring morphism:
From: Rational Field
To:   Complex Field with 53 bits of precision
Defn: 1 |--> 1.00000000000000
sage: QQ.complex_embedding(20)
˓needs sage.rings.real_mpfr
Ring morphism:
From: Rational Field
To:   Complex Field with 20 bits of precision
Defn: 1 |--> 1.0000
```

construction()

Return a pair (`functor`, `parent`) such that `functor(parent)` returns `self`.

This is the construction of **Q** as the fraction field of **Z**.

EXAMPLES:

```
sage: QQ.construction()
(FractionField, Integer Ring)
```

defining_polynomial()

Return a defining polynomial of **Q**, as for other number fields.

This is also aliased to `defining_polynomial()` and `absolute_polynomial()`.

EXAMPLES:

```
sage: QQ.polynomial()
x
```

degree()

Return the degree of **Q**, which is 1.

EXAMPLES:

```
sage: QQ.degree()
1
```

discriminant()

Return the discriminant of the field of rational numbers, which is 1.

EXAMPLES:

```
sage: QQ.discriminant()
1
```

embeddings(K)

Return the list containing the unique embedding of **Q** into **K**, if it exists, and an empty list otherwise.

EXAMPLES:

```
sage: QQ.embeddings(QQ)
[Identity endomorphism of Rational Field]
sage: QQ.embeddings(CyclotomicField(5))
# ...
← needs sage.rings.number_field
[Coercion map:
From: Rational Field
To: Cyclotomic Field of order 5 and degree 4]
```

The field **K** must have characteristic 0 for an embedding of **Q** to exist:

```
sage: QQ.embeddings(GF(3))
[]
```

extension(poly, names, **kwds)

Create a field extension of **Q**.

EXAMPLES:

We make a single absolute extension:

```
sage: x = polygen(QQ, 'x')
sage: K.<a> = QQ.extension(x^3 + 5); K
# ...
← needs sage.rings.number_field
Number Field in a with defining polynomial x^3 + 5
```

We make an extension generated by roots of two polynomials:

```
sage: K.<a,b> = QQ.extension([x^3 + 5, x^2 + 3]); K
# ...
← needs sage.rings.number_field
Number Field in a with defining polynomial x^3 + 5 over its base field
sage: b^2
# ...
← needs sage.rings.number_field
-3
```

(continues on next page)

(continued from previous page)

```
sage: a^3
→needs sage.rings.number_field
-5
```

#_

gen (n=0)

Return the n-th generator of \mathbf{Q} .

There is only the 0-th generator, which is 1.

EXAMPLES:

```
sage: QQ.gen()
1
```

gens ()

Return a tuple of generators of \mathbf{Q} , which is only (1,).

EXAMPLES:

```
sage: QQ.gens()
(1, )
```

hilbert_symbol_negative_at_S (S, b, check=True)

Return an integer that has a negative Hilbert symbol with respect to a given rational number and a given set of primes (or places).

The function is algorithm 3.4.1 in [Kir2016]. It finds an integer a that has negative Hilbert symbol with respect to a given rational number exactly at a given set of primes (or places).

INPUT:

- S – list of rational primes, the infinite place as real embedding of \mathbf{Q} or as -1
- b – a nonzero rational number which is a non-square locally at every prime in S
- check – boolean (default: True); perform additional checks on input and confirm the output

OUTPUT:

- An integer a that has negative Hilbert symbol $(a, b)_p$ for every place p in S and no other place.

EXAMPLES:

```
sage: QQ.hilbert_symbol_negative_at_S([-1, 5, 3, 2, 7, 11, 13, 23], -10/7)
→needs sage.rings.padics
-9867
sage: QQ.hilbert_symbol_negative_at_S([3, 5, QQ.places()[0], 11], -15)
→needs sage.rings.padics
-33
sage: QQ.hilbert_symbol_negative_at_S([3, 5], 2)
→needs sage.rings.padics
15
```

#_

#_

#_

AUTHORS:

- Simon Brandhorst, Juanita Duque, Anna Haensch, Manami Roy, Sandi Rudzinski (10-24-2017)

is_absolute ()

\mathbf{Q} is an absolute extension of \mathbf{Q} .

EXAMPLES:

```
sage: QQ.is_absolute()
True
```

is_prime_field()

Return True since **Q** is a prime field.

EXAMPLES:

```
sage: QQ.is_prime_field()
True
```

maximal_order()

Return the maximal order of the rational numbers, i.e., the ring **Z** of integers.

EXAMPLES:

```
sage: QQ.maximal_order()
Integer Ring
sage: QQ.ring_of_integers ()
Integer Ring
```

ngens()

Return the number of generators of **Q**, which is 1.

EXAMPLES:

```
sage: QQ.ngens()
1
```

number_field()

Return the number field associated to **Q**. Since **Q** is a number field, this just returns **Q** again.

EXAMPLES:

```
sage: QQ.number_field() is QQ
True
```

order()

Return the order of **Q**, which is ∞ .

EXAMPLES:

```
sage: QQ.order()
+Infinity
```

places (all_complex=False, prec=None)

Return the collection of all infinite places of `self`, which in this case is just the embedding of `self` into **R**.

By default, this returns homomorphisms into **RR**. If `prec` is not None, we simply return homomorphisms into `RealField(prec)` (or `RDF` if `prec=53`).

There is an optional flag `all_complex`, which defaults to False. If `all_complex` is True, then the real embeddings are returned as embeddings into the corresponding complex field.

For consistency with non-trivial number fields.

EXAMPLES:

polynomial()

Return a defining polynomial of \mathbf{Q} , as for other number fields.

This is also aliased to `defining_polynomial()` and `absolute_polynomial()`.

EXAMPLES:

```
sage: QQ.polynomial()
```

power_basis ()

Return a power basis for this number field over its base field.

The power basis is always [1] for the rational field. This method is defined to make the rational field behave more like a number field.

EXAMPLES:

```
sage: QQ.power_basis()
[1]
```

```
primes_of_bounded_norm_iter(B)
```

Iterator yielding all primes less than or equal to B .

INPUT:

- B – positive integer; upper bound on the primes generated

OUTPUT: an iterator over all integer primes less than or equal to B

Note

This function exists for compatibility with the related number field method, though it returns prime integers, not ideals.

EXAMPLES:

```
sage: it = QQ.primes_of_bounded_norm_iter(10)
sage: list(it)
```

(continues on next page)

(continued from previous page)

```
needs sage.libs.pari
[2, 3, 5, 7]
sage: list(QQ.primes_of_bounded_norm_iter(1))
[]
```

quadratic_defect (*a, p, check=True*)

Return the valuation of the quadratic defect of *a* at *p*.

INPUT:

- *a* – an element of `self`
- *p* – a prime ideal or a prime number
- *check* – (default: `True`) check if *p* is prime

REFERENCE:

[Kir2016]

EXAMPLES:

```
sage: QQ.quadratic_defect(0, 7)
+Infinity
sage: QQ.quadratic_defect(5, 7)
0
sage: QQ.quadratic_defect(5, 2)
2
sage: QQ.quadratic_defect(5, 5)
1
```

random_element (*num_bound=None, den_bound=None, *args, **kwds*)

Return a random element of \mathbb{Q} .

Elements are constructed by randomly choosing integers for the numerator and denominator, not necessarily coprime.

INPUT:

- *num_bound* – positive integer, specifying a bound on the absolute value of the numerator. If absent, no bound is enforced.
- *den_bound* – positive integer, specifying a bound on the value of the denominator. If absent, the bound for the numerator will be reused.

Any extra positional or keyword arguments are passed through to `sage.rings.integer_ring.IntegerRing_class.random_element()`.

EXAMPLES:

```
sage: QQ.random_element().parent() is QQ
True
sage: while QQ.random_element() != 0:
....:     pass
sage: while QQ.random_element() != -1/2:
....:     pass
```

In the following example, the resulting numbers range from $-5/1$ to $5/1$ (both inclusive), while the smallest possible positive value is $1/10$:

```
sage: q = QQ.random_element(5, 10)
sage: -5/1 <= q <= 5/1
True
sage: q.denominator() <= 10
True
sage: q.numerator() <= 5
True
```

Extra positional or keyword arguments are passed through:

```
sage: QQ.random_element(distribution='1/n').parent() is QQ
True
sage: QQ.random_element(distribution='1/n').parent() is QQ
True
```

`range_by_height` (*start, end=None*)

Range function for rational numbers, ordered by height.

Returns a Python generator for the list of rational numbers with heights in `range(start, end)`. Follows the same convention as Python `range()`, type `range?` for details.

See also `__iter__()`.

EXAMPLES:

All rational numbers with height strictly less than 4:

```
sage: list(QQ.range_by_height(4))
[0, 1, -1, 1/2, -1/2, 2, -2, 1/3, -1/3, 3, -3, 2/3, -2/3, 3/2, -3/2]
sage: [a.height() for a in QQ.range_by_height(4)]
[1, 1, 1, 2, 2, 2, 3, 3, 3, 3, 3, 3]
```

All rational numbers with height 2:

```
sage: list(QQ.range_by_height(2, 3))
[1/2, -1/2, 2, -2]
```

Nonsensical integer arguments will return an empty generator:

```
sage: list(QQ.range_by_height(3, 3))
[]
sage: list(QQ.range_by_height(10, 1))
[]
```

There are no rational numbers with height ≤ 0 :

```
sage: list(QQ.range_by_height(-10, 1))
[]
```

`relative_discriminant()`

Return the relative discriminant, which is 1.

EXAMPLES:

```
sage: QQ.relative_discriminant()
1
```

residue_field(*p*, *check=True*)

Return the residue field of \mathbf{Q} at the prime *p*, for consistency with other number fields.

INPUT:

- *p* – prime integer
- **check – (default: True)** if **True**, check the primality of *p*, else do not

OUTPUT: the residue field at this prime

EXAMPLES:

```
sage: QQ.residue_field(5)
Residue field of Integers modulo 5
sage: QQ.residue_field(next_prime(10^9)) #_
    ↪needs sage.rings.finite_rings
Residue field of Integers modulo 1000000007
```

selmer_generators(*S*, *m*, *proof=True*, *orders=False*)

Return generators of the group $\mathbf{Q}(S, m)$.

INPUT:

- *S* – set of primes
- *m* – positive integer
- *proof* – ignored
- *orders* – (default: *False*) if *True*, output two lists, the generators and their orders

OUTPUT:

A list of generators of $\mathbf{Q}(S, m)$ (and, optionally, their orders in $\mathbf{Q}^\times / (\mathbf{Q}^\times)^m$). This is the subgroup of $\mathbf{Q}^\times / (\mathbf{Q}^\times)^m$ consisting of elements *a* such that the valuation of *a* is divisible by *m* at all primes not in *S*. It is equal to the group of *S*-units modulo *m*-th powers. The group $\mathbf{Q}(S, m)$ contains the subgroup of those *a* such that $\mathbf{Q}(\sqrt[m]{a})/\mathbf{Q}$ is unramified at all primes of \mathbf{Q} outside of *S*, but may contain it properly when not all primes dividing *m* are in *S*.

See also

`RationalField.selmer_space()`, which gives additional output when *m = p* is prime: as well as generators, it gives an abstract vector space over \mathbf{F}_p isomorphic to $\mathbf{Q}(S, p)$ and maps implementing the isomorphism between this space and $\mathbf{Q}(S, p)$ as a subgroup of $\mathbf{Q}^* / (\mathbf{Q}^*)^p$.

EXAMPLES:

```
sage: QQ.selmer_generators((), 2)
[-1]
sage: QQ.selmer_generators((3,), 2)
[-1, 3]
sage: QQ.selmer_generators((5,), 2)
[-1, 5]
```

The previous examples show that the group generated by the output may be strictly larger than the ‘true’ Selmer group of elements giving extensions unramified outside *S*.

When *m* is even, -1 is a generator of order 2:

```
sage: QQ.selmer_generators((2,3,5,7,), 2, orders=True)
([-1, 2, 3, 5, 7], [2, 2, 2, 2])
sage: QQ.selmer_generators((2,3,5,7,), 3, orders=True)
([2, 3, 5, 7], [3, 3, 3, 3])
```

selmer_group(*args, **kwds)

Deprecated: Use `selmer_generators()` instead. See [Issue #31345](#) for details.

selmer_group_iterator(S, m, proof=True)

Return an iterator through elements of the finite group $\mathbf{Q}(S, m)$.

INPUT:

- S – set of primes
- m – positive integer
- proof – ignored

OUTPUT:

An iterator yielding the distinct elements of $\mathbf{Q}(S, m)$. See the docstring for `selmer_generators()` for more information.

EXAMPLES:

```
sage: list(QQ.selmer_group_iterator((), 2))
[1, -1]
sage: list(QQ.selmer_group_iterator((2,), 2))
[1, 2, -1, -2]
sage: list(QQ.selmer_group_iterator((2,3), 2))
[1, 3, 2, 6, -1, -3, -2, -6]
sage: list(QQ.selmer_group_iterator((5,), 2))
[1, 5, -1, -5]
```

selmer_space(S, p, proof=None)

Compute the group $\mathbf{Q}(S, p)$ as a vector space with maps to and from \mathbf{Q}^* .

INPUT:

- S – list of prime numbers
- p – a prime number

OUTPUT:

(tuple) QSp, QSp_gens, from_QSp, to_QSp where

- QSp is an abstract vector space over \mathbf{F}_p isomorphic to $\mathbf{Q}(S, p)$;
- QSp_gens is a list of elements of \mathbf{Q}^* generating $\mathbf{Q}(S, p)$;
- from_QSp is a function from QSp to \mathbf{Q}^* implementing the isomorphism from the abstract $\mathbf{Q}(S, p)$ to $\mathbf{Q}(S, p)$ as a subgroup of $\mathbf{Q}^*/(\mathbf{Q}^*)^p$;
- to_QSp is a partial function from \mathbf{Q}^* to QSp, defined on elements a whose image in $\mathbf{Q}^*/(\mathbf{Q}^*)^p$ lies in $\mathbf{Q}(S, p)$, mapping them via the inverse isomorphism to the abstract vector space QSp.

The group $\mathbf{Q}(S, p)$ is the finite subgroup of $\mathbf{Q}^*/(\mathbf{Q}^*)^p$ consisting of elements whose valuation at all primes not in S is a multiple of p. It contains the subgroup of those $a \in \mathbf{Q}^*$ such that $\mathbf{Q}(\sqrt[p]{a})/\mathbf{Q}$ is unramified at all primes of \mathbf{Q} outside of S, but may contain it properly when p is not in S.

EXAMPLES:

When S is empty, $\mathbf{Q}(S, p)$ is only nontrivial for $p = 2$:

```
sage: QS2, QS2gens, fromQS2, toQS2 = QQ.selmer_space([], 2)
→needs sage.rings.number_field
sage: QS2
→needs sage.rings.number_field
Vector space of dimension 1 over Finite Field of size 2
sage: QS2gens
→needs sage.rings.number_field
[-1]

sage: all(QQ.selmer_space([], p)[0].dimension() == 0
→needs sage.libs.pari sage.rings.number_field
....:     for p in primes(3, 10))
True
```

In general there is one generator for each $p \in S$, and an additional generator of -1 when $p = 2$:

```
sage: # needs sage.modules sage.rings.number_field
sage: QS2, QS2gens, fromQS2, toQS2 = QQ.selmer_space([5, 7], 2)
sage: QS2
Vector space of dimension 3 over Finite Field of size 2
sage: QS2gens
[5, 7, -1]
sage: toQS2(-7)
(0, 1, 1)
sage: fromQS2((0, 1, 1))
-7
```

The map `fromQS2` is only well-defined modulo p -th powers (in this case, modulo squares):

```
sage: toQS2(-5/7)
→needs sage.modules sage.rings.number_field
(1, 1, 1)
sage: fromQS2((1, 1, 1))
→needs sage.modules sage.rings.number_field
-35
sage: ((-5/7) / (-35)).is_square()
True
```

The map `toQS2` is not defined on all of \mathbf{Q}^* , only on those numbers which are squares away from 5 and 7:

```
sage: toQS2(210)
→needs sage.modules sage.rings.number_field
Traceback (most recent call last):
...
ValueError: argument 210 should have valuations divisible by 2
at all primes in [5, 7]
```

`signature()`

Return the signature of the rational field, which is $(1, 0)$, since there are 1 real and no complex embeddings.

EXAMPLES:

```
sage: QQ.signature()
(1, 0)
```

`some_elements()`

Return some elements of \mathbb{Q} .

See `TestSuite()` for a typical use case.

OUTPUT: an iterator over 100 elements of \mathbb{Q}

EXAMPLES:

```
sage: tuple(QQ.some_elements())
(1/2, -1/2, 2, -2,
 0, 1, -1, 42,
 2/3, -2/3, 3/2, -3/2,
 4/5, -4/5, 5/4, -5/4,
 6/7, -6/7, 7/6, -7/6,
 8/9, -8/9, 9/8, -9/8,
 10/11, -10/11, 11/10, -11/10,
 12/13, -12/13, 13/12, -13/12,
 14/15, -14/15, 15/14, -15/14,
 16/17, -16/17, 17/16, -17/16,
 18/19, -18/19, 19/18, -19/18,
 20/441, -20/441, 441/20, -441/20,
 22/529, -22/529, 529/22, -529/22,
 24/625, -24/625, 625/24, -625/24,
 ...)
```

valuation(*p*)

Return the discrete valuation with uniformizer *p*.

EXAMPLES:

```
sage: v = QQ.valuation(3); v
˓needs sage.rings.padics
3-adic valuation
sage: v(1/3)
˓needs sage.rings.padics
-1
```

See also

`NumberField_generic.valuation()`, `IntegerRing_class.valuation()`

zeta(*n*=2)

Return a root of unity in `self`.

INPUT:

- *n* – integer (default: 2); order of the root of unity

EXAMPLES:

```
sage: QQ.zeta()
-1
sage: QQ.zeta(2)
-1
sage: QQ.zeta(1)
1
sage: QQ.zeta(3)
```

(continues on next page)

(continued from previous page)

```
Traceback (most recent call last):
...
ValueError: no n-th root of unity in rational field
```

`sage.rings.rational_field.frac(n,d)`

Return the fraction n/d.

EXAMPLES:

```
sage: from sage.rings.rational_field import frac
sage: frac(1,2)
1/2
```

`sage.rings.rational_field.is_RationalField(x)`

Check to see if x is the rational field.

EXAMPLES:

```
sage: from sage.rings.rational_field import is_RationalField as is_RF
sage: is_RF(QQ)
doctest:warning...
DeprecationWarning: The function is_RationalField is deprecated;
use 'isinstance(..., RationalField)' instead.
See https://github.com/sagemath/sage/issues/38128 for details.
True
sage: is_RF(ZZ)
False
```

2.2 Rational Numbers

AUTHORS:

- William Stein (2005): first version
- William Stein (2006-02-22): floor and ceil (pure fast GMP versions).
- Gonzalo Tornaria and William Stein (2006-03-02): greatly improved python/GMP conversion; hashing
- William Stein and Naqi Jaffery (2006-03-06): height, sqrt examples, and improve behavior of sqrt.
- David Harvey (2006-09-15): added nth_root
- Pablo De Napoli (2007-04-01): corrected the implementations of multiplicative_order, is_one; optimized __bool__ ; documented: lcm,gcd
- John Cremona (2009-05-15): added support for local and global logarithmic heights.
- Travis Scrimshaw (2012-10-18): Added doctests for full coverage.
- Vincent Delecroix (2013): continued fraction
- Vincent Delecroix (2017-05-03): faster integer-rational comparison
- Vincent Klein (2017-05-11): add __mpq__() to class Rational
- Vincent Klein (2017-05-22): Rational constructor support gmpy2.mpq or gmpy2mpz parameter. Add __mpz__ to class Rational.

```
class sage.rings.rational.Q_to_Z
```

Bases: Map

A morphism from \mathbf{Q} to \mathbf{Z} .

section()

Return a section of this morphism.

EXAMPLES:

```
sage: sage.rings.rational.Q_to_Z(QQ, ZZ).section()
Natural morphism:
  From: Integer Ring
  To:   Rational Field
```

```
class sage.rings.rational.Rational
```

Bases: FieldElement

A rational number.

Rational numbers are implemented using the GMP C library.

EXAMPLES:

```
sage: a = -2/3
sage: type(a)
<class 'sage.rings.rational.Rational'>
sage: parent(a)
Rational Field
sage: Rational('1/0')
Traceback (most recent call last):
...
TypeError: unable to convert '1/0' to a rational
sage: Rational(1.5)
3/2
sage: Rational('9/6')
3/2
sage: Rational((2^99,2^100))
1/2
sage: Rational("2", "10"), 16
1/8
sage: Rational(QQbar(125/8).nth_root(3))
→needs sage.rings.number_field
5/2
sage: Rational(AA(209735/343 - 17910/49*golden_ratio).nth_root(3))
→needs sage.rings.number_field sage.symbolic
.....:
+ 3*AA(golden_ratio))
53/7
sage: QQ(float(1.5))
3/2
sage: QQ(RDF(1.2))
6/5
```

Conversion from fractions:

```
sage: import fractions
sage: f = fractions.Fraction(1r, 2r)
sage: Rational(f)
1/2
```

Conversion from PARI:

```
sage: Rational(pari(' -939082/3992923 '))
# needs sage.libs.pari
-939082/3992923
sage: Rational(pari('Pol([-1/2])')) #9595
# needs sage.libs.pari
-1/2
```

Conversions from numpy:

```
sage: # needs numpy
sage: import numpy as np
sage: QQ(np.int8(' -15 '))
-15
sage: QQ(np.int16(' -32 '))
-32
sage: QQ(np.int32(' -19 '))
-19
sage: QQ(np.uint32('1412 '))
1412

sage: QQ(np.float16('12 '))
# needs numpy
12
```

Conversions from gmpy2:

```
sage: from gmpy2 import *
sage: QQ(mpq('3/4'))
3/4
sage: QQ(mpz(42))
42
sage: Rational(mpq(2/3))
2/3
sage: Rational(mpz(5))
5
```

absolute_norm()

Return the norm from Q to Q of x (which is just x). This was added for compatibility with NumberFields.

EXAMPLES:

```
sage: (6/5).absolute_norm()
6/5

sage: QQ(7/5).absolute_norm()
7/5
```

additive_order()

Return the additive order of self.

OUTPUT: integer or infinity

EXAMPLES:

```
sage: QQ(0).additive_order()
1
```

(continues on next page)

(continued from previous page)

```
sage: QQ(1).additive_order()
+Infinity
```

as_integer_ratio()

Return the pair (self.numerator(), self.denominator()).

EXAMPLES:

```
sage: x = -12/29
sage: x.as_integer_ratio()
(-12, 29)
```

ceil()

Return the ceiling of this rational number.

OUTPUT: integer

If this rational number is an integer, this returns this number, otherwise it returns the floor of this number +1.

EXAMPLES:

```
sage: n = 5/3; n.ceil()
2
sage: n = -17/19; n.ceil()
0
sage: n = -7/2; n.ceil()
-3
sage: n = 7/2; n.ceil()
4
sage: n = 10/2; n.ceil()
5
```

charpoly(var='x')

Return the characteristic polynomial of this rational number. This will always be just var - self; this is really here so that code written for number fields won't crash when applied to rational numbers.

INPUT:

- var – string

OUTPUT: polynomial

EXAMPLES:

```
sage: (1/3).charpoly('x')
x - 1/3
```

The default is var='x'. (Issue #20967):

```
sage: a = QQ(2); a.charpoly('x')
x - 2
```

AUTHORS:

- Craig Citro

conjugate()

Return the complex conjugate of this rational number, which is the number itself.

EXAMPLES:

```
sage: n = 23/11
sage: n.conjugate()
23/11
```

content (other)

Return the content of `self` and `other`, i.e., the unique positive rational number c such that self/c and other/c are coprime integers.

`other` can be a rational number or a list of rational numbers.

EXAMPLES:

```
sage: a = 2/3
sage: a.content(2/3)
2/3
sage: a.content(1/5)
1/15
sage: a.content([2/5, 4/9])
2/45
```

continued_fraction()

Return the continued fraction of that rational.

EXAMPLES:

```
sage: (641/472).continued_fraction()
[1; 2, 1, 3, 1, 4, 1, 5]

sage: a = (355/113).continued_fraction(); a
[3; 7, 16]
sage: a.n(digits=10) #_
˓needs sage.rings.real_mpfr
3.141592920
sage: pi.n(digits=10) #_
˓needs sage.rings.real_mpfr sage.symbolic
3.141592654
```

It's almost pi!

continued_fraction_list(type='std')

Return the list of partial quotients of this rational number.

INPUT:

- `type` – either '`std`' (the default) for the standard continued fractions or '`hj`' for the Hirzebruch-Jung ones

EXAMPLES:

```
sage: (13/9).continued_fraction_list()
[1, 2, 4]
sage: 1 + 1/(2 + 1/4)
13/9

sage: (225/157).continued_fraction_list()
[1, 2, 3, 4, 5]
sage: 1 + 1/(2 + 1/(3 + 1/(4 + 1/5)))
225/157
```

(continues on next page)

(continued from previous page)

```
sage: (fibonacci(20)/fibonacci(19)).continued_fraction_list() #_
˓needs sage.libs.pari
[1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 2]

sage: (-1/3).continued_fraction_list()
[-1, 1, 2]
```

Check that the partial quotients of an integer n is simply $[n]$:

```
sage: QQ(1).continued_fraction_list()
[1]
sage: QQ(0).continued_fraction_list()
[0]
sage: QQ(-1).continued_fraction_list()
[-1]
```

Hirzebruch-Jung continued fractions:

```
sage: (11/19).continued_fraction_list("hj")
[1, 3, 2, 3, 2]
sage: 1 - 1/(3 - 1/(2 - 1/(3 - 1/2)))
11/19

sage: (225/137).continued_fraction_list("hj")
[2, 3, 5, 10]
sage: 2 - 1/(3 - 1/(5 - 1/10))
225/137

sage: (-23/19).continued_fraction_list("hj")
[-1, 5, 4]
sage: -1 - 1/(5 - 1/4)
-23/19
```

denom()

Return the denominator of this rational number. `denom()` is an alias of `denominator()`.

EXAMPLES:

```
sage: x = -5/11
sage: x.denominator()
11

sage: x = 9/3
sage: x.denominator()
1

sage: x = 5/13
sage: x.denom()
13
```

denominator()

Return the denominator of this rational number. `denom()` is an alias of `denominator()`.

EXAMPLES:

```
sage: x = -5/11
sage: x.denominator()
```

(continues on next page)

(continued from previous page)

```
11

sage: x = 9/3
sage: x.denominator()
1

sage: x = 5/13
sage: x.denom()
13
```

factor()

Return the factorization of this rational number.

OUTPUT: factorization

EXAMPLES:

```
sage: (-4/17).factor()
-1 * 2^2 * 17^-1
```

Trying to factor 0 gives an arithmetic error:

```
sage: (0/1).factor()
Traceback (most recent call last):
...
ArithmetricError: factorization of 0 is not defined
```

floor()

Return the floor of this rational number as an integer.

OUTPUT: integer

EXAMPLES:

```
sage: n = 5/3; n.floor()
1
sage: n = -17/19; n.floor()
-1
sage: n = -7/2; n.floor()
-4
sage: n = 7/2; n.floor()
3
sage: n = 10/2; n.floor()
5
```

gamma (prec=None)

Return the gamma function evaluated at `self`. This value is exact for integers and half-integers, and returns a symbolic value otherwise. For a numerical approximation, use keyword `prec`.

EXAMPLES:

```
sage: # needs sage.symbolic
sage: gamma(1/2)
sqrt(pi)
sage: gamma(7/2)
15/8*sqrt(pi)
sage: gamma(-3/2)
```

(continues on next page)

(continued from previous page)

```
4/3*sqrt(pi)
sage: gamma(6/1)
120
sage: gamma(1/3)
gamma(1/3)
```

This function accepts an optional precision argument:

```
sage: (1/3).gamma(prec=100) #_
→needs sage.rings.real_mpfr
2.6789385347077476336556929410
sage: (1/2).gamma(prec=100) #_
→needs sage.rings.real_mpfr
1.7724538509055160272981674833
```

global_height (prec=None)

Return the absolute logarithmic height of this rational number.

INPUT:

- `prec` – integer (default: default `RealField` precision); desired floating point precision

OUTPUT:

(real) The absolute logarithmic height of this rational number.

ALGORITHM:

The height is the sum of the total archimedean and non-archimedean components, which is equal to $\max(\log(n), \log(d))$ where n, d are the numerator and denominator of the rational number.

EXAMPLES:

```
sage: # needs sage.rings.real_mpfr
sage: a = QQ(6/25)
sage: a.global_height_arch() + a.global_height_non_arch()
3.21887582486820
sage: a.global_height()
3.21887582486820
sage: (1/a).global_height()
3.21887582486820
sage: QQ(0).global_height()
0.000000000000000
sage: QQ(1).global_height()
0.000000000000000
```

global_height_arch (prec=None)

Return the total archimedean component of the height of this rational number.

INPUT:

- `prec` – integer (default: default `RealField` precision); desired floating point precision

OUTPUT:

(real) The total archimedean component of the height of this rational number.

ALGORITHM:

Since \mathbb{Q} has only one infinite place this is just the value of the local height at that place. This separate function is included for compatibility with number fields.

EXAMPLES:

```
sage: a = QQ(6/25)
sage: a.global_height_arch()
# needs sage.rings.real_mpfr
0.000000000000000
sage: (1/a).global_height_arch()
# needs sage.rings.real_mpfr
1.42711635564015
sage: (1/a).global_height_arch(100)
# needs sage.rings.real_mpfr
1.4271163556401457483890413081
```

global_height_non_arch(*prec=None*)

Return the total non-archimedean component of the height of this rational number.

INPUT:

- *prec* – integer (default: default RealField precision); desired floating point precision

OUTPUT:

(real) The total non-archimedean component of the height of this rational number.

ALGORITHM:

This is the sum of the local heights at all primes p , which may be computed without factorization as the log of the denominator.

EXAMPLES:

```
sage: a = QQ(5/6)
sage: a.support()
[2, 3, 5]
sage: a.global_height_non_arch()
# needs sage.rings.real_mpfr
1.79175946922805
sage: [a.local_height(p) for p in a.support()]
# needs sage.rings.real_mpfr
[0.693147180559945, 1.09861228866811, 0.000000000000000]
sage: sum([a.local_height(p) for p in a.support()])
# needs sage.rings.real_mpfr
1.79175946922805
```

height()

The max absolute value of the numerator and denominator of *self*, as an *Integer*.

OUTPUT: integer

EXAMPLES:

```
sage: a = 2/3
sage: a.height()
3
sage: a = 34/3
sage: a.height()
34
sage: a = -97/4
sage: a.height()
97
```

AUTHORS:

- Naqi Jaffery (2006-03-05): examples

Note

For the logarithmic height, use `global_height()`.

imag()

Return the imaginary part of `self`, which is zero.

EXAMPLES:

```
sage: (1/239).imag()
0
```

is_S_integral(S=[])

Determine if the rational number is S-integral.

x is S-integral if $x.\text{valuation}(p) \geq 0$ for all p not in S , i.e., the denominator of x is divisible only by the primes in S .

INPUT:

- S – list or tuple of primes

OUTPUT: boolean

Note

Primality of the entries in S is not checked.

EXAMPLES:

```
sage: QQ(1/2).is_S_integral()
False
sage: QQ(1/2).is_S_integral([2])
True
sage: [a for a in range(1,11) if QQ(101/a).is_S_integral([2,5])]
[1, 2, 4, 5, 8, 10]
```

is_S_unit(S=None)

Determine if the rational number is an S-unit.

x is an S-unit if $x.\text{valuation}(p) == 0$ for all p not in S , i.e., the numerator and denominator of x are divisible only by the primes in S .

INPUT:

- S – list or tuple of primes

OUTPUT: boolean

Note

Primality of the entries in S is not checked.

EXAMPLES:

```
sage: QQ(1/2).is_S_unit()
False
sage: QQ(1/2).is_S_unit([2])
True
sage: [a for a in range(1,11) if QQ(10/a).is_S_unit([2,5])]
[1, 2, 4, 5, 8, 10]
```

is_integer()

Determine if a rational number is integral (i.e., is in \mathbf{Z}).

OUTPUT: boolean

EXAMPLES:

```
sage: QQ(1/2).is_integral()
False
sage: QQ(4/4).is_integral()
True
```

is_integral()

Determine if a rational number is integral (i.e., is in \mathbf{Z}).

OUTPUT: boolean

EXAMPLES:

```
sage: QQ(1/2).is_integral()
False
sage: QQ(4/4).is_integral()
True
```

is_norm(*L*, *element=False*, *proof=True*)

Determine whether *self* is the norm of an element of *L*.

INPUT:

- *L* – a number field
- *element* – boolean (default: *False*); whether to also output an element of which *self* is a norm
- *proof* – if *True*, then the output is correct unconditionally; if *False*, then the output assumes GRH

OUTPUT:

If *element* is *False*, then the output is a boolean *B*, which is *True* if and only if *self* is the norm of an element of *L*. If *element* is *True*, then the output is a pair (*B*, *x*), where *B* is as above. If *B* is *True*, then *x* an element of *L* such that *self* == *x.norm()*. Otherwise, *x* is *None*.

ALGORITHM:

Uses the PARI function `pari:bnfisnorm`. See `_bnfisnorm()`.

EXAMPLES:

```
sage: # needs sage.rings.number_field
sage: x = polygen(QQ, 'x')
sage: K = NumberField(x^2 - 2, 'beta')
sage: (1/7).is_norm(K)
True
```

(continues on next page)

(continued from previous page)

```
sage: (1/10).is_norm(K)
False
sage: 0.is_norm(K)
True
sage: (1/7).is_norm(K, element=True)
(True, 1/7*beta + 3/7)
sage: (1/10).is_norm(K, element=True)
(False, None)
sage: (1/691).is_norm(QQ, element=True)
(True, 1/691)
```

The number field doesn't have to be defined by an integral polynomial:

```
sage: B, e = (1/5).is_norm(QuadraticField(5/4, 'a'), element=True)      #
    ↪needs sage.rings.number_field
sage: B
    ↪needs sage.rings.number_field
True
sage: e.norm()                                                               #
    ↪needs sage.rings.number_field
1/5
```

A non-Galois number field:

```
sage: # needs sage.rings.number_field
sage: K.<a> = NumberField(x^3 - 2)
sage: B, e = (3/5).is_norm(K, element=True); B
True
sage: e.norm()
3/5
sage: 7.is_norm(K)                                                          #
    ↪needs sage.groups
Traceback (most recent call last):
...
NotImplementedError: is_norm is not implemented unconditionally
for norms from non-Galois number fields
sage: 7.is_norm(K, proof=False)
False
```

AUTHORS:

- Craig Citro (2008-04-05)
- Marco Streng (2010-12-03)

`is_nth_power(n)`

Return True if `self` is an n -th power, else False.

INPUT:

- `n` – integer (must fit in C `int` type)

Note

Use this function when you need to test if a rational number is an n -th power, but do not need to know the value of its n -th root. If the value is needed, use `nth_root()`.

AUTHORS:

- John Cremona (2009-04-04)

EXAMPLES:

```
sage: QQ(25/4).is_nth_power(2)
True
sage: QQ(125/8).is_nth_power(3)
True
sage: QQ(-125/8).is_nth_power(3)
True
sage: QQ(25/4).is_nth_power(-2)
True

sage: QQ(9/2).is_nth_power(2)
False
sage: QQ(-25).is_nth_power(2)
False
```

is_one()

Determine if a rational number is one.

OUTPUT: boolean

EXAMPLES:

```
sage: QQ(1/2).is_one()
False
sage: QQ(4/4).is_one()
True
```

is_padic_square(*p*, *check=True*)

Determines whether this rational number is a square in \mathbf{Q}_p (or in R when $p = \text{infinity}$).

INPUT:

- *p* – a prime number, or infinity
- *check* – boolean (default: True); check if *p* is prime

EXAMPLES:

```
sage: QQ(2).is_padic_square(7)
True
sage: QQ(98).is_padic_square(7)
True
sage: QQ(2).is_padic_square(5)
False
```

is_perfect_power(*expected_value=False*)

Return True if self is a perfect power.

INPUT:

- *expected_value* – boolean; whether or not this rational is expected to be a perfect power. This does not affect the correctness of the output, only the runtime.

If *expected_value* is False (default) it will check the smallest of the numerator and denominator is a perfect power as a first step, which is often faster than checking if the quotient is a perfect power.

EXAMPLES:

```
sage: (4/9).is_perfect_power()
True
sage: (144/1).is_perfect_power()
True
sage: (4/3).is_perfect_power()
False
sage: (2/27).is_perfect_power()
False
sage: (4/27).is_perfect_power()
False
sage: (-1/25).is_perfect_power()
False
sage: (-1/27).is_perfect_power()
True
sage: (0/1).is_perfect_power()
True
```

The second parameter does not change the result, but may change the runtime.

```
sage: (-1/27).is_perfect_power(True)
True
sage: (-1/25).is_perfect_power(True)
False
sage: (2/27).is_perfect_power(True)
False
sage: (144/1).is_perfect_power(True)
True
```

This test makes sure we workaround a bug in GMP (see Issue #4612):

```
sage: [-a for a in srange(100) if not QQ(-a^3).is_perfect_power()]
[]
sage: [-a for a in srange(100) if not QQ(-a^3).is_perfect_power(True)]
[]
```

is_rational()

Return True since this is a rational number.

EXAMPLES:

```
sage: (3/4).is_rational()
True
```

is_square()

Return whether or not this rational number is a square.

OUTPUT: boolean

EXAMPLES:

```
sage: x = 9/4
sage: x.is_square()
True
sage: x = (7/53)^100
sage: x.is_square()
True
sage: x = 4/3
sage: x.is_square()
```

(continues on next page)

(continued from previous page)

```
False
sage: x = -1/4
sage: x.is_square()
False
```

list()

Return a list with the rational element in it, to be compatible with the method for number fields.

OUTPUT: the list [self]

EXAMPLES:

```
sage: m = 5/3
sage: m.list()
[5/3]
```

local_height(*p*, *prec=None*)

Return the local height of this rational number at the prime *p*.

INPUT:

- *p* – a prime number
- *prec* – integer (default: default RealField precision); desired floating point precision

OUTPUT:

(real) The local height of this rational number at the prime *p*.

EXAMPLES:

```
sage: a = QQ(25/6)
sage: a.local_height(2)                                              #_
˓needs sage.rings.real_mpfr
0.693147180559945
sage: a.local_height(3)                                              #_
˓needs sage.rings.real_mpfr
1.09861228866811
sage: a.local_height(5)                                              #_
˓needs sage.rings.real_mpfr
0.0000000000000000
```

local_height_arch(*prec=None*)

Return the Archimedean local height of this rational number at the infinite place.

INPUT:

- *prec* – integer (default: default RealField precision); desired floating point precision

OUTPUT:

(real) The local height of this rational number *x* at the unique infinite place of **Q**, which is $\max(\log(|x|), 0)$.

EXAMPLES:

```
sage: a = QQ(6/25)
sage: a.local_height_arch()                                         #_
˓needs sage.rings.real_mpfr
0.0000000000000000
sage: (1/a).local_height_arch()                                     #_
```

(continues on next page)

(continued from previous page)

```

→needs sage.rings.real_mpfr
1.42711635564015
sage: (1/a).local_height_arch(100) #_
→needs sage.rings.real_mpfr
1.4271163556401457483890413081

```

log (m=None, prec=None)

Return the log of self.

INPUT:

- m – the base (default: natural log base e)
- prec – integer (optional); the precision in bits

OUTPUT:

When prec is not given, the log as an element in symbolic ring unless the logarithm is exact. Otherwise the log is a RealField approximation to prec bit precision.

EXAMPLES:

```

sage: (124/345).log(5) #_
→needs sage.symbolic
log(124/345)/log(5)
sage: (124/345).log(5, 100) #_
→needs sage.rings.real_mpfr
-0.63578895682825611710391773754
sage: log(QQ(125)) #_
→needs sage.symbolic
3*log(5)
sage: log(QQ(125), 5) #_
3
sage: log(QQ(125), 3) #_
→needs sage.symbolic
3*log(5)/log(3)
sage: QQ(8).log(1/2)
-3
sage: (1/8).log(1/2)
3
sage: (1/2).log(1/8)
1/3
sage: (1/2).log(8)
-1/3
sage: (16/81).log(8/27) #_
→needs sage.libs.pari
4/3
sage: (8/27).log(16/81) #_
→needs sage.libs.pari
3/4
sage: log(27/8, 16/81) #_
→needs sage.libs.pari
-3/4
sage: log(16/81, 27/8) #_
→needs sage.libs.pari
-4/3
sage: (125/8).log(5/2) #_
→needs sage.libs.pari

```

(continues on next page)

(continued from previous page)

```
3
sage: (125/8).log(5/2, prec=53) #_
˓needs sage.rings.real_mpfr
3.000000000000000
```

minpoly (*var*='x')

Return the minimal polynomial of this rational number. This will always be just $x - \text{self}$; this is really here so that code written for number fields won't crash when applied to rational numbers.

INPUT:

- var - string

OUTPUT: polynomial

EXAMPLES:

```
sage: (1/3).minpoly()
x - 1/3
sage: (1/3).minpoly('y')
y - 1/3
```

AUTHORS:

- Craig Citro

mod ui (n)

Return the remainder upon division of self by the unsigned long integer n.

INPUT:

- n – an unsigned long integer

OUTPUT: integer

EXAMPLES:

```
sage: (-4/17).mod_ui()
1
sage: (-4/17).mod_ui()
Traceback (most recent call last)
...
ArithmeticError: The
```

`multiplicative_order()`

Return the multiplicative order of `self`.

OUTPUT: integer or infinity

EXAMPLES:

```
sage: QQ(1).multiplicative_order()
1
sage: QQ('1/-1').multiplicative_order()
2
sage: QQ(0).multiplicative_order()
+Infinity
sage: QQ('2/3').multiplicative_order()
+Infinity
```

(continues on next page)

(continued from previous page)

```
sage: QQ('1/2').multiplicative_order()
+Infinity
```

norm()

Return the norm from \mathbf{Q} to \mathbf{Q} of x (which is just x). This was added for compatibility with `NumberField`.

OUTPUT: Rational – reference to `self`

EXAMPLES:

```
sage: (1/3).norm()
1/3
```

AUTHORS:

- Craig Citro

nth_root(n)

Compute the n -th root of `self`, or raises a `ValueError` if `self` is not a perfect n -th power.

INPUT:

- n – integer (must fit in `C int` type)

AUTHORS:

- David Harvey (2006-09-15)

EXAMPLES:

```
sage: (25/4).nth_root(2)
5/2
sage: (125/8).nth_root(3)
5/2
sage: (-125/8).nth_root(3)
-5/2
sage: (25/4).nth_root(-2)
2/5
```

```
sage: (9/2).nth_root(2)
Traceback (most recent call last):
...
ValueError: not a perfect 2nd power
```

```
sage: (-25/4).nth_root(2)
Traceback (most recent call last):
...
ValueError: cannot take even root of negative number
```

numer()

Return the numerator of this rational number. `numer()` is an alias of `numerator()`.

EXAMPLES:

```
sage: x = 5/11
sage: x.numerator()
5
```

(continues on next page)

(continued from previous page)

```
sage: x = 9/3
sage: x.numerator()
3

sage: x = -5/11
sage: x.numer()
-5
```

numerator()

Return the numerator of this rational number. `numer()` is an alias of `numerator()`.

EXAMPLES:

```
sage: x = 5/11
sage: x.numerator()
5

sage: x = 9/3
sage: x.numerator()
3

sage: x = -5/11
sage: x.numer()
-5
```

ord(*p*)

Return the power of *p* in the factorization of `self`.

INPUT:

- *p* – a prime number

OUTPUT:

(integer or infinity) `Infinity` if `self` is zero, otherwise the (positive or negative) integer *e* such that `self = m * pe` with *m* coprime to *p*.

Note

See also `val_unit()` which returns the pair (e, m) . The function `ord()` is an alias for `valuation()`.

EXAMPLES:

```
sage: x = -5/9
sage: x.valuation(5)
1
sage: x.ord(5)
1
sage: x.valuation(3)
-2
sage: x.valuation(2)
0
```

Some edge cases:

```
sage: (0/1).valuation(4)
+Infinity
sage: (7/16).valuation(4)
-2
```

period()

Return the period of the repeating part of the decimal expansion of this rational number.

ALGORITHM:

When a rational number n/d with $(n, d) = 1$ is expanded, the period begins after s terms and has length t , where s and t are the smallest numbers satisfying $10^s \equiv 10^{s+t} \pmod{d}$. In general if $d = 2^a 5^b m$ where m is coprime to 10, then $s = \max(a, b)$ and t is the order of 10 modulo m .

EXAMPLES:

```
sage: (1/7).period() #_
→needs sage.libs.pari
6
sage: RR(1/7) #_
→needs sage.rings.real_mpfr
0.142857142857143
sage: (1/8).period() #_
→needs sage.libs.pari
1
sage: RR(1/8) #_
→needs sage.rings.real_mpfr
0.125000000000000
sage: RR(1/6) #_
→needs sage.rings.real_mpfr
0.1666666666666667
sage: (1/6).period() #_
→needs sage.libs.pari
1
sage: x = 333/106 #_
sage: x.period() #_
→needs sage.libs.pari
13
sage: RealField(200)(x) #_
→needs sage.rings.real_mpfr
3.141509433962264150943396226415094339622641509
```

prime_to_S_part(S=[])

Return `self` with all powers of all primes in `S` removed.

INPUT:

- `S` – list or tuple of primes

OUTPUT: rational

Note

Primality of the entries in `S` is not checked.

EXAMPLES:

```
sage: QQ(3/4).prime_to_S_part()
3/4
sage: QQ(3/4).prime_to_S_part([2])
3
sage: QQ(-3/4).prime_to_S_part([3])
-1/4
sage: QQ(700/99).prime_to_S_part([2,3,5])
7/11
sage: QQ(-700/99).prime_to_S_part([2,3,5])
-7/11
sage: QQ(0).prime_to_S_part([2,3,5])
0
sage: QQ(-700/99).prime_to_S_part([])
-700/99
```

real()

Return the real part of `self`, which is `self`.

EXAMPLES:

```
sage: (1/2).real()
1/2
```

relative_norm()

Return the norm from \mathbb{Q} to \mathbb{Q} of `x` (which is just `x`). This was added for compatibility with NumberFields.

EXAMPLES:

```
sage: (6/5).relative_norm()
6/5

sage: QQ(7/5).relative_norm()
7/5
```

round(*mode=None*)

Return the nearest integer to `self`, rounding away by default. Deprecation: in the future the default will be changed to rounding to even, for consistency with the builtin Python `round()`.

INPUT:

- `self` – a rational number
- `mode` – a rounding mode for half integers:
 - '`toward`' rounds toward zero
 - '`away`' (default) rounds away from zero
 - '`up`' rounds up
 - '`down`' rounds down
 - '`even`' rounds toward the even integer
 - '`odd`' rounds toward the odd integer

OUTPUT: integer

EXAMPLES:

```
sage: (9/2).round()
doctest:::: DeprecationWarning: the default rounding for rationals, currently `away`, will be changed to `even`.
See https://github.com/sagemath/sage/issues/35473 for details.
5
sage: n = 4/3; n.round()
1
sage: n = -17/4; n.round()
-4
sage: n = -5/2; n.round()
-3
sage: n.round("away")
-3
sage: n.round("up")
-2
sage: n.round("down")
-3
sage: n.round("even")
-2
sage: n.round("odd")
-3
```

sign()

Return the sign of this rational number, which is -1, 0, or 1 depending on whether this number is negative, zero, or positive respectively.

OUTPUT: integer

EXAMPLES:

```
sage: (2/3).sign()
1
sage: (0/3).sign()
0
sage: (-1/6).sign()
-1
```

sqrt(*prec=None, extend=True, all=False*)

The square root function.

INPUT:

- *prec* – integer (default: None); if None, returns an exact square root; otherwise returns a numerical square root if necessary, to the given bits of precision.
- *extend* – boolean (default: True); if True, return a square root in an extension ring, if necessary. Otherwise, raise a `ValueError` if the square is not in the base ring. Ignored if *prec* is not None.
- *all* – boolean (default: False); if True, return all square roots of *self* (a list of length 0, 1, or 2)

EXAMPLES:

```
sage: x = 25/9
sage: x.sqrt()
5/3
sage: sqrt(x)
5/3
sage: x = 64/4
sage: x.sqrt()
```

(continues on next page)

(continued from previous page)

```

4
sage: x = 100/1
sage: x.sqrt()
10
sage: x.sqrt(all=True)
[10, -10]
sage: x = 81/5
sage: x.sqrt()
#_
˓needs sage.symbolic
9*sqrt(1/5)
sage: x = -81/3
sage: x.sqrt()
#_
˓needs sage.symbolic
3*sqrt(-3)

```

```

sage: n = 2/3
sage: n.sqrt()
#_
˓needs sage.symbolic
sqrt(2/3)

sage: # needs sage.rings.real_mpfr
sage: n.sqrt(prec=10)
0.82
sage: n.sqrt(prec=100)
0.81649658092772603273242802490
sage: n.sqrt(prec=100)^2
0.666666666666666666666666666667
sage: n.sqrt(prec=53, all=True)
[0.816496580927726, -0.816496580927726]
sage: sqrt(-2/3, prec=53)
0.816496580927726*I
sage: sqrt(-2/3, prec=53, all=True)
[0.816496580927726*I, -0.816496580927726*I]

sage: n.sqrt(extend=False)
Traceback (most recent call last):
...
ValueError: square root of 2/3 not a rational number
sage: n.sqrt(extend=False, all=True)
[]
sage: sqrt(-2/3, all=True)
#_
˓needs sage.symbolic
[sqrt(-2/3), -sqrt(-2/3)]

```

AUTHORS:

- Naqi Jaffery (2006-03-05): some examples

`squarefree_part()`

Return the square free part of x , i.e., an integer z such that $x = zy^2$, for a perfect square y^2 .

EXAMPLES:

```

sage: a = 1/2
sage: a.squarefree_part()
2
sage: b = a/a.squarefree_part()

```

(continues on next page)

(continued from previous page)

```
sage: b, b.is_square()
(1/4, True)
sage: a = 24/5
sage: a.squarefree_part()
30
```

str(base=10)

Return a string representation of `self` in the given base.

INPUT:

- `base` – integer (default: 10); base must be between 2 and 36

OUTPUT: string

EXAMPLES:

```
sage: (-4/17).str()
'-4/17'
sage: (-4/17).str(2)
'-100/10001'
```

Note that the base must be at most 36.

```
sage: (-4/17).str(40)
Traceback (most recent call last):
...
ValueError: base (=40) must be between 2 and 36
sage: (-4/17).str(1)
Traceback (most recent call last):
...
ValueError: base (=1) must be between 2 and 36
```

support()

Return a sorted list of the primes where this rational number has nonzero valuation.

OUTPUT: the set of primes appearing in the factorization of this rational with nonzero exponent, as a sorted list.

EXAMPLES:

```
sage: (-4/17).support()
[2, 17]
```

Trying to find the support of 0 gives an arithmetic error:

```
sage: (0/1).support()
Traceback (most recent call last):
...
ArithmetricError: Support of 0 not defined.
```

trace()

Return the trace from **Q** to **Q** of `x` (which is just `x`). This was added for compatibility with `NumberFields`.

OUTPUT: Rational – reference to `self`

EXAMPLES:

```
sage: (1/3).trace()
1/3
```

AUTHORS:

- Craig Citro

trunc()

Round this rational number to the nearest integer toward zero.

EXAMPLES:

```
sage: (5/3).trunc()
1
sage: (-5/3).trunc()
-1
sage: QQ(42).trunc()
42
sage: QQ(-42).trunc()
-42
```

val_unit(*p*)

Return a pair: the *p*-adic valuation of `self`, and the *p*-adic unit of `self`, as a *Rational*.

We do not require the *p* be prime, but it must be at least 2. For more documentation see [Integer.val_unit\(\)](#).

INPUT:

- *p* – a prime

OUTPUT:

- integer; the *p*-adic valuation of this rational
- *Rational*; *p*-adic unit part of `self`

EXAMPLES:

```
sage: (-4/17).val_unit(2)
(2, -1/17)
sage: (-4/17).val_unit(17)
(-1, -4)
sage: (0/1).val_unit(17)
(+Infinity, 1)
```

AUTHORS:

- David Roe (2007-04-12)

valuation(*p*)

Return the power of *p* in the factorization of `self`.

INPUT:

- *p* – a prime number

OUTPUT:

(integer or infinity) `Infinity` if `self` is zero, otherwise the (positive or negative) integer *e* such that `self = m * pe` with *m* coprime to *p*.

Note

See also `val_unit()` which returns the pair (e, m) . The function `ord()` is an alias for `valuation()`.

EXAMPLES:

```
sage: x = -5/9
sage: x.valuation(5)
1
sage: x.ord(5)
1
sage: x.valuation(3)
-2
sage: x.valuation(2)
0
```

Some edge cases:

```
sage: (0/1).valuation(4)
+Infinity
sage: (7/16).valuation(4)
-2
```

class sage.rings.rational.Z_to_Q

Bases: `Morphism`

A morphism from \mathbf{Z} to \mathbf{Q} .

is_surjective()

Return whether this morphism is surjective.

EXAMPLES:

```
sage: QQ.coerce_map_from(ZZ).is_surjective()
False
```

section()

Return a section of this morphism.

EXAMPLES:

```
sage: f = QQ.coerce_map_from(ZZ).section(); f
Generic map:
  From: Rational Field
  To:   Integer Ring
```

This map is a morphism in the category of sets with partial maps (see Issue #15618):

```
sage: f.parent()
Set of Morphisms from Rational Field to Integer Ring
in Category of sets with partial maps
```

class sage.rings.rational.int_to_Q

Bases: `Morphism`

A morphism from Python 3 `int` to \mathbf{Q} .

```
sage.rings.rational.integer_rational_power(a,b)
```

Compute a^b as an integer, if it is integral, or return None.

The nonnegative real root is taken for even denominators.

INPUT:

- a – an Integer
- b – a nonnegative Rational

OUTPUT: a^b as an Integer or None

EXAMPLES:

```
sage: from sage.rings.rational import integer_rational_power
sage: integer_rational_power(49, 1/2)
7
sage: integer_rational_power(27, 1/3)
3
sage: integer_rational_power(-27, 1/3) is None
True
sage: integer_rational_power(-27, 2/3) is None
True
sage: integer_rational_power(512, 7/9)
128

sage: integer_rational_power(27, 1/4) is None
True
sage: integer_rational_power(-16, 1/4) is None
True

sage: integer_rational_power(0, 7/9)
0
sage: integer_rational_power(1, 7/9)
1
sage: integer_rational_power(-1, 7/9) is None
True
sage: integer_rational_power(-1, 8/9) is None
True
sage: integer_rational_power(-1, 9/8) is None
True
```

TESTS (Issue #11228):

```
sage: integer_rational_power(-10, QQ(2))
100
sage: integer_rational_power(0, QQ(0))
1
```

```
sage.rings.rational.is_Rational(x)
```

Return True if x is of the Sage *Rational* type.

EXAMPLES:

```
sage: from sage.rings.rational import is_Rational
sage: is_Rational(2)
doctest:warning...
DeprecationWarning: The function is_Rational is deprecated;
use 'isinstance(..., Rational)' instead.
```

(continues on next page)

(continued from previous page)

```
See https://github.com/sagemath/sage/issues/38128 for details.  
False  
sage: is_Rational(2/1)  
True  
sage: is_Rational(int(2))  
False  
sage: is_Rational('5')  
False
```

```
sage.rings.rational.make_rational(s)
```

Make a rational number from s (a string in base 32).

INPUT:

- s – string in base 32

OUTPUT: rational

EXAMPLES:

```
sage: (-7/15).str(32)  
'-7/f'  
sage: sage.rings.rational.make_rational('-7/f')  
-7/15
```

```
sage.rings.rational.rational_power_parts(a, b, factor_limit=100000)
```

Compute rationals or integers c and d such that $a^b = c * d^b$ with d small. This is used for simplifying radicals.

INPUT:

- a – a rational or integer
- b – a rational
- factor_limit – the limit used in factoring a

EXAMPLES:

```
sage: from sage.rings.rational import rational_power_parts  
sage: rational_power_parts(27, 1/2)  
(3, 3)  
sage: rational_power_parts(-128, 3/4)  
(8, -8)  
sage: rational_power_parts(-4, 1/2)  
(2, -1)  
sage: rational_power_parts(-4, 1/3)  
(1, -4)  
sage: rational_power_parts(9/1000, 1/2)  
(3/10, 1/10)
```

CHAPTER
THREE

INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

a

sage.arith.functions, 74
sage.arith.misc, 79
sage.arith.multi_modular, 76
sage.arith.power, 75

r

sage.rings.bernmm, 63
sage.rings.bernoulli_mod_p, 64
sage.rings.factorint, 67
sage.rings.factorint_flint, 69
sage.rings.factorint_pari, 70
sage.rings.fast_arith, 71
sage.rings.integer, 13
sage.rings.integer_ring, 1
sage.rings.rational, 167
sage.rings.rational_field, 153
sage.rings.sum_of_squares, 72

INDEX

Non-alphabetical

`__pow__()` (*sage.rings.integer.Integer method*), 16

A

`absolute_degree()` (*sage.rings.integer_ring.IntegerRing_class method*), 4
`absolute_degree()` (*sage.rings.rational_field.RationalField method*), 155
`absolute_discriminant()` (*sage.rings.rational_field.RationalField method*), 155
`absolute_norm()` (*sage.rings.rational.Rational method*), 169
`absolute_polynomial()` (*sage.rings.rational_field.RationalField method*), 155
`additive_order()` (*sage.rings.integer.Integer method*), 17
`additive_order()` (*sage.rings.rational.Rational method*), 169
`algdep()` (*in module sage.arith.misc*), 90
`algebraic_closure()` (*sage.rings.rational_field.RationalField method*), 155
`algebraic_dependency()` (*in module sage.arith.misc*), 92
`arith_int` (*class in sage.rings.fast_arith*), 71
`arith_llong` (*class in sage.rings.fast_arith*), 71
`as_integer_ratio()` (*sage.rings.integer.Integer method*), 17
`as_integer_ratio()` (*sage.rings.rational.Rational method*), 170
`aurifeuillian()` (*in module sage.rings.factorint*), 67
`automorphisms()` (*sage.rings.rational_field.RationalField method*), 155

B

`balanced_digits()` (*sage.rings.integer.Integer method*), 17
`bernmmp_bern_modp()` (*in module sage.rings.bernmmp*), 63
`bernmmp_bern_rat()` (*in module sage.rings.bernmmp*), 64
`bernoulli()` (*in module sage.arith.misc*), 94

`bernoulli_mod_p()` (*in module sage.rings.bernpoly_mod_p*), 64
`bernoulli_mod_p_single()` (*in module sage.rings.bernpoly_mod_p*), 65
`binary()` (*sage.rings.integer.Integer method*), 18
`binomial()` (*in module sage.arith.misc*), 95
`binomial()` (*sage.rings.integer.Integer method*), 18
`binomial_coefficients()` (*in module sage.arith.misc*), 97
`bit_length()` (*sage.rings.integer.Integer method*), 19
`bits()` (*sage.rings.integer.Integer method*), 19

C

`carmichael_lambda()` (*in module sage.arith.misc*), 97
`ceil()` (*sage.rings.integer.Integer method*), 20
`ceil()` (*sage.rings.rational.Rational method*), 170
`characteristic()` (*sage.rings.integer_ring.IntegerRing_class method*), 4
`characteristic()` (*sage.rings.rational_field.RationalField method*), 155
`charpoly()` (*sage.rings.rational.Rational method*), 170
`class_number()` (*sage.rings.integer.Integer method*), 20
`class_number()` (*sage.rings.rational_field.RationalField method*), 156
`completion()` (*sage.rings.integer_ring.IntegerRing_class method*), 4
`completion()` (*sage.rings.rational_field.RationalField method*), 156
`complex_embedding()` (*sage.rings.rational_field.RationalField method*), 156
`conjugate()` (*sage.rings.integer.Integer method*), 21
`conjugate()` (*sage.rings.rational.Rational method*), 170
`construction()` (*sage.rings.rational_field.RationalField method*), 156
`content()` (*sage.rings.rational.Rational method*), 171
`continuant()` (*in module sage.arith.misc*), 99
`continued_fraction()` (*sage.rings.rational.Rational method*), 171

continued_fraction_list() (*sage.rings.rational.Rational method*), 171
coprime_integers() (*sage.rings.integer.Integer method*), 21
coprime_part() (*in module sage.arith.misc*), 100
CRT() (*in module sage.arith.misc*), 79
crt() (*in module sage.arith.misc*), 101
crt() (*sage.arith.multi_modular.MultiModularBasis_base method*), 77
crt() (*sage.rings.integer.Integer method*), 21
CRT_basis() (*in module sage.arith.misc*), 81
crt_basis() (*in module sage.rings.integer_ring*), 12
CRT_list() (*in module sage.arith.misc*), 82
CRT_vectors() (*in module sage.arith.misc*), 83

D

dedekind_psi() (*in module sage.arith.misc*), 103
dedekind_sum() (*in module sage.arith.misc*), 103
defining_polynomial() (*sage.rings.rational_field.RationalField method*), 156
degree() (*sage.rings.integer_ring.IntegerRing_class method*), 5
degree() (*sage.rings.rational_field.RationalField method*), 157
denom() (*sage.rings.rational.Rational method*), 172
denominator() (*sage.rings.integer.Integer method*), 22
denominator() (*sage.rings.rational.Rational method*), 172
differences() (*in module sage.arith.misc*), 105
digits() (*sage.rings.integer.Integer method*), 22
discriminant() (*sage.rings.rational_field.RationalField method*), 157
divide_knowing_divisible_by() (*sage.rings.integer.Integer method*), 24
divides() (*sage.rings.integer.Integer method*), 24
divisors() (*in module sage.arith.misc*), 105
divisors() (*sage.rings.integer.Integer method*), 24

E

embeddings() (*sage.rings.rational_field.RationalField method*), 157
eratosthenes() (*in module sage.arith.misc*), 106
euclidean_degree() (*sage.rings.integer.Integer method*), 25
Euler_Phi (*class in sage.arith.misc*), 83
exact_log() (*sage.rings.integer.Integer method*), 26
exp() (*sage.rings.integer.Integer method*), 27
extend_with_primes() (*sage.arith.multi_modular.MultiModularBasis_base method*), 77
extension() (*sage.rings.integer_ring.IntegerRing_class method*), 5
extension() (*sage.rings.rational_field.RationalField method*), 157

F

factor() (*in module sage.arith.misc*), 107
factor() (*sage.rings.integer.Integer method*), 27
factor() (*sage.rings.rational.Rational method*), 173
factor_aurifeuillian() (*in module sage.rings.factorint*), 68
factor_cunningham() (*in module sage.rings.factorint*), 68
factor_trial_division() (*in module sage.rings.factorint*), 69
factor_using_flint() (*in module sage.rings.factorint_flint*), 69
factor_using_pari() (*in module sage.rings.factorint_pari*), 70
factorial() (*in module sage.arith.misc*), 109
factorial() (*sage.rings.integer.Integer method*), 29
falling_factorial() (*in module sage.arith.misc*), 110
floor() (*sage.rings.integer.Integer method*), 29
floor() (*sage.rings.rational.Rational method*), 173
four_squares() (*in module sage.arith.misc*), 111
four_squares_pyx() (*in module sage.rings.sum_of_squares*), 72
frac() (*in module sage.rings.rational_field*), 167
fraction_field() (*sage.rings.integer_ring.IntegerRing_class method*), 5
free_integer_pool() (*in module sage.rings.integer*), 62
from_bytes() (*sage.rings.integer_ring.IntegerRing_class method*), 6
fundamental_discriminant() (*in module sage.arith.misc*), 112

G

gamma() (*sage.rings.integer.Integer method*), 30
gamma() (*sage.rings.rational.Rational method*), 173
gauss_sum() (*in module sage.arith.misc*), 112
GCD() (*in module sage.arith.misc*), 85
gcd() (*in module sage.arith.misc*), 113
gcd_int() (*sage.rings.fast_arith.arith_int method*), 71
GCD_list() (*in module sage.rings.integer*), 15
gcd_longlong() (*sage.rings.fast_arith.arith_llong method*), 71
gen() (*sage.rings.integer_ring.IntegerRing_class method*), 6
gen() (*sage.rings.rational_field.RationalField method*), 158
generic_power() (*in module sage.arith.power*), 75
gens() (*sage.rings.integer_ring.IntegerRing_class method*), 6
gens() (*sage.rings.rational_field.RationalField method*), 158
get_gcd() (*in module sage.arith.misc*), 114
get_inverse_mod() (*in module sage.arith.misc*), 114

```

global_height() (sage.rings.integer.Integer method), 30
global_height() (sage.rings.rational.Rational method), 174
global_height_arch() (sage.rings.rational.Rational method), 174
global_height_non_arch() (sage.rings.rational.Rational method), 175
is_integer() (sage.rings.integer.Integer method), 33
is_integer() (sage.rings.rational.Rational method), 177
is_IntegerRing() (in module sage.rings.integer_ring), 13
is_integral() (sage.rings.integer.Integer method), 33
is_integral() (sage.rings.rational.Rational method), 177
is_integrally_closed() (sage.rings.integer_ring.IntegerRing_class method), 7
is_irreducible() (sage.rings.integer.Integer method), 33
is_norm() (sage.rings.integer.Integer method), 33
is_norm() (sage.rings.rational.Rational method), 177
is_nth_power() (sage.rings.rational.Rational method), 178
is_one() (sage.rings.integer.Integer method), 34
is_one() (sage.rings.rational.Rational method), 179
is_padic_square() (sage.rings.rational.Rational method), 179
is_perfect_power() (sage.rings.integer.Integer method), 34
is_perfect_power() (sage.rings.rational.Rational method), 179
is_power_of() (sage.rings.integer.Integer method), 34
is_power_of_two() (in module sage.arith.misc), 119
is_prime() (in module sage.arith.misc), 119
is_prime() (sage.rings.integer.Integer method), 36
is_prime_field() (sage.rings.rational_field.RationalField method), 159
is_prime_power() (in module sage.arith.misc), 120
is_prime_power() (sage.rings.integer.Integer method), 37
is_pseudoprime() (in module sage.arith.misc), 121
is_pseudoprime() (sage.rings.integer.Integer method), 38
is_pseudoprime_power() (in module sage.arith.misc), 121
is_pseudoprime_power() (sage.rings.integer.Integer method), 38
is_Rational() (in module sage.rings.rational), 193
is_rational() (sage.rings.integer.Integer method), 39
is_rational() (sage.rings.rational.Rational method), 180
is_RationalField() (in module sage.rings.rational_field), 167
is_S_integral() (sage.rings.rational.Rational method), 176
is_S_unit() (sage.rings.rational.Rational method), 176
is_square() (in module sage.arith.misc), 122
is_square() (sage.rings.integer.Integer method), 39
is_square() (sage.rings.rational.Rational method), 180

H
height() (sage.rings.rational.Rational method), 175
hex() (sage.rings.integer.Integer method), 30
hilbert_conductor() (in module sage.arith.misc), 115
hilbert_conductor_inverse() (in module sage.arith.misc), 115
hilbert_symbol() (in module sage.arith.misc), 116
hilbert_symbol_negative_at_S() (sage.rings.rational_field.RationalField method), 158

I
imag() (sage.rings.integer.Integer method), 31
imag() (sage.rings.rational.Rational method), 176
int_to_Q (class in sage.rings.rational), 192
int_to_Z (class in sage.rings.integer), 62
Integer (class in sage.rings.integer), 15
integer_ceil() (in module sage.arith.misc), 117
integer_floor() (in module sage.arith.misc), 117
integer_rational_power() (in module sage.rings.rational), 192
integer_trunc() (in module sage.arith.misc), 118
IntegerRing() (in module sage.rings.integer_ring), 1
IntegerRing_class (class in sage.rings.integer_ring), 1
IntegerWrapper (class in sage.rings.integer), 62
inverse_mod() (in module sage.arith.misc), 118
inverse_mod() (sage.rings.integer.Integer method), 31
inverse_mod_int() (sage.rings.fast_arith.arith_int method), 71
inverse_mod_longlong() (sage.rings.fast_arith.arith_llong method), 71
inverse_of_unit() (sage.rings.integer.Integer method), 32
is_absolute() (sage.rings.rational_field.RationalField method), 158
is_discriminant() (sage.rings.integer.Integer method), 32
is_field() (sage.rings.integer_ring.IntegerRing_class method), 6
is_fundamental_discriminant() (sage.rings.integer.Integer method), 32
is_Integer() (in module sage.rings.integer), 62

```

is_squarefree() (*in module sage.arith.misc*), 123
 is_squarefree() (*sage.rings.integer.Integer method*), 39
 is_sum_of_two_squares_pyx() (*in module sage.rings.sum_of_squares*), 73
 is_surjective() (*sage.rings.rational.Z_to_Q method*), 192
 is_unit() (*sage.rings.integer.Integer method*), 39
 isqrt() (*sage.rings.integer.Integer method*), 40

J

jacobi() (*sage.rings.integer.Integer method*), 40
 jacobi_symbol() (*in module sage.arith.misc*), 124

K

kronecker() (*in module sage.arith.misc*), 125
 kronecker() (*sage.rings.integer.Integer method*), 40
 kronecker_symbol() (*in module sage.arith.misc*), 126
 krull_dimension() (*sage.rings.integer_ring.IntegerRing_class method*), 7

L

lcm() (*in module sage.arith.functions*), 75
 LCM_list() (*in module sage.arith.functions*), 74
 legendre_symbol() (*in module sage.arith.misc*), 126
 list() (*sage.arith.multi_modular.MultiModularBasis_base method*), 77
 list() (*sage.rings.integer.Integer method*), 41
 list() (*sage.rings.rational.Rational method*), 181
 local_height() (*sage.rings.rational.Rational method*), 181
 local_height_arch() (*sage.rings.rational.Rational method*), 181
 log() (*sage.rings.integer.Integer method*), 41
 log() (*sage.rings.rational.Rational method*), 182

M

make_integer() (*in module sage.rings.integer*), 63
 make_rational() (*in module sage.rings.rational*), 194
 maximal_order() (*sage.rings.rational_field.RationalField method*), 159
 minpoly() (*sage.rings.rational.Rational method*), 183
 mod_ui() (*sage.rings.rational.Rational method*), 183
 module
 sage.arith.functions, 74
 sage.arith.misc, 79
 sage.arith.multi_modular, 76
 sage.arith.power, 75
 sage.rings.bernmm, 63
 sage.rings.bernoulli_mod_p, 64
 sage.rings.factorint, 67
 sage.rings.factorint_flint, 69

sage.rings.factorint_pari, 70
 sage.rings.fast_arith, 71
 sage.rings.integer, 13
 sage.rings.integer_ring, 1
 sage.rings.rational, 167
 sage.rings.rational_field, 153
 sage.rings.sum_of_squares, 72
 Moebius (*class in sage.arith.misc*), 86
 mqrr_rational_reconstruction() (*in module sage.arith.misc*), 127
 multifactorial() (*sage.rings.integer.Integer method*), 42
 MultiModularBasis (*class in sage.arith.multi_modular*), 76
 MultiModularBasis_base (*class in sage.arith.multi_modular*), 76
 multinomial() (*in module sage.arith.misc*), 128
 multinomial_coefficients() (*in module sage.arith.misc*), 128
 multiplicative_order() (*sage.rings.integer.Integer method*), 43
 multiplicative_order() (*sage.rings.rational.Rational method*), 183
 MutableMultiModularBasis (*class in sage.arith.multi_modular*), 78

N

nbits() (*sage.rings.integer.Integer method*), 43
 ndigits() (*sage.rings.integer.Integer method*), 43
 next_prime() (*in module sage.arith.misc*), 129
 next_prime() (*sage.arith.multi_modular.MutableMultiModularBasis method*), 78
 next_prime() (*sage.rings.integer.Integer method*), 44
 next_prime_power() (*in module sage.arith.misc*), 130
 next_prime_power() (*sage.rings.integer.Integer method*), 44
 next_probable_prime() (*in module sage.arith.misc*), 130
 next_probable_prime() (*sage.rings.integer.Integer method*), 45
 ngens() (*sage.rings.integer_ring.IntegerRing_class method*), 7
 ngens() (*sage.rings.rational_field.RationalField method*), 159
 norm() (*sage.rings.rational.Rational method*), 184
 nth_prime() (*in module sage.arith.misc*), 131
 nth_root() (*sage.rings.integer.Integer method*), 45
 nth_root() (*sage.rings.rational.Rational method*), 184
 number_field() (*sage.rings.rational_field.RationalField method*), 159
 number_of_divisors() (*in module sage.arith.misc*), 131
 numer() (*sage.rings.rational.Rational method*), 184

numerator () (*sage.rings.integer.Integer method*), 47
 numerator () (*sage.rings.rational.Rational method*),
 185

O

oct () (*sage.rings.integer.Integer method*), 47
 odd_part () (*in module sage.arith.misc*), 132
 odd_part () (*sage.rings.integer.Integer method*), 48
 ord () (*sage.rings.integer.Integer method*), 48
 ord () (*sage.rings.rational.Rational method*), 185
 order () (*sage.rings.integer_ring.IntegerRing_class method*), 7
 order () (*sage.rings.rational_field.RationalField method*), 159
 ordinal_str () (*sage.rings.integer.Integer method*), 48

P

p_primary_part () (*sage.rings.integer.Integer method*), 49
 parameter () (*sage.rings.integer_ring.IntegerRing_class method*), 7
 partial_product () (*sage.arith.multi_modular.MultiModularBasis_base method*), 78
 perfect_power () (*sage.rings.integer.Integer method*), 49
 period () (*sage.rings.rational.Rational method*), 186
 places () (*sage.rings.rational_field.RationalField method*), 159
 plot () (*sage.arith.misc.Euler_Phi method*), 84
 plot () (*sage.arith.misc.Moebius method*), 87
 plot () (*sage.arith.misc.Sigma method*), 88
 polynomial () (*sage.rings.rational_field.RationalField method*), 160
 popcorn () (*sage.rings.integer.Integer method*), 50
 power_basis () (*sage.rings.rational_field.RationalField method*), 160
 power_mod () (*in module sage.arith.misc*), 132
 powermod () (*sage.rings.integer.Integer method*), 50
 precomputation_list () (*sage.arith.multi_modular.MultiModularBasis_base method*), 78
 previous_prime () (*in module sage.arith.misc*), 132
 previous_prime () (*sage.rings.integer.Integer method*), 51
 previous_prime_power () (*in module sage.arith.misc*), 133
 previous_prime_power () (*sage.rings.integer.Integer method*), 51
 prime_divisors () (*in module sage.arith.misc*), 134
 prime_divisors () (*sage.rings.integer.Integer method*), 52
 prime_factors () (*in module sage.arith.misc*), 135
 prime_factors () (*sage.rings.integer.Integer method*), 53
 prime_powers () (*in module sage.arith.misc*), 135

prime_range () (*in module sage.rings.fast_arith*), 71
 prime_to_m_part () (*in module sage.arith.misc*), 136
 prime_to_m_part () (*sage.rings.integer.Integer method*), 53
 prime_to_S_part () (*sage.rings.rational.Rational method*), 186
 primes () (*in module sage.arith.misc*), 137
 primes_first_n () (*in module sage.arith.misc*), 138
 primes_of_bounded_norm_iter () (*sage.rings.rational_field.RationalField method*), 160
 primitive_root () (*in module sage.arith.misc*), 138
 prod () (*sage.arith.multi_modular.MultiModularBasis_base method*), 78
 Python Enhancement Proposals
 PEP 3127, 15

Q

Q_to_Z (*class in sage.rings.rational*), 167
 quadratic_defect () (*sage.rings.rational_field.RationalField method*), 161
 quadratic_residues () (*in module sage.arith.misc*), 139
 quo_rem () (*sage.rings.integer.Integer method*), 54
 quotient () (*sage.rings.integer_ring.IntegerRing_class method*), 8

R

radical () (*in module sage.arith.misc*), 139
 random_element () (*sage.rings.integer_ring.IntegerRing_class method*), 8
 random_element () (*sage.rings.rational_field.RationalField method*), 161
 random_prime () (*in module sage.arith.misc*), 140
 range () (*sage.arith.misc.Moebius method*), 87
 range () (*sage.rings.integer_ring.IntegerRing_class method*), 10
 range_by_height () (*sage.rings.rational_field.RationalField method*), 162
 Rational (*class in sage.rings.rational*), 168
 rational_power_parts () (*in module sage.rings.rational*), 194
 rational_recon_int () (*sage.rings.fast_arith.arith_int method*), 71
 rational_recon_longlong () (*sage.rings.fast_arith.arith_llong method*), 71
 rational_reconstruction () (*in module sage.arith.misc*), 141
 rational_reconstruction () (*sage.rings.integer.Integer method*), 54
 RationalField (*class in sage.rings.rational_field*), 153
 real () (*sage.rings.integer.Integer method*), 55
 real () (*sage.rings.rational.Rational method*), 187

```

relative_discriminant()      (sage.rings.rational_field.RationalField method), 162
relative_norm()      (sage.rings.rational.Rational method), 187
replace_prime()      (sage.arith.multi_modular.MutableMultiModularBasis method), 79
residue_field()      (sage.rings.integer_ring.IntegerRing_class method), 10
residue_field()      (sage.rings.rational_field.RationalField method), 162
rising_factorial()  (in module sage.arith.misc), 142
round()      (sage.rings.integer.Integer method), 55
round()      (sage.rings.rational.Rational method), 187

S
sage.arith.functions
    module, 74
sage.arith.misc
    module, 79
sage.arith.multi_modular
    module, 76
sage.arith.power
    module, 75
sage.rings.bernmm
    module, 63
sage.rings.bernoulli_mod_p
    module, 64
sage.rings.factorint
    module, 67
sage.rings.factorint_flint
    module, 69
sage.rings.factorint pari
    module, 70
sage.rings.fast_arith
    module, 71
sage.rings.integer
    module, 13
sage.rings.integer_ring
    module, 1
sage.rings.rational
    module, 167
sage.rings.rational_field
    module, 153
sage.rings.sum_of_squares
    module, 72
section()      (sage.rings.rational.Q_to_Z method), 168
section()      (sage.rings.rational.Z_to_Q method), 192
selmer_generators()  (sage.rings.rational_field.RationalField method), 163
selmer_group()      (sage.rings.rational_field.RationalField method), 164
selmer_group_iterator()  (sage.rings.rational_field.RationalField method), 164
selmer_space()      (sage.rings.rational_field.RationalField method), 164
Sigma (class in sage.arith.misc), 87
sign()      (sage.rings.integer.Integer method), 55
sign()      (sage.rings.rational.Rational method), 188
signature()      (sage.rings.rational_field.RationalField method), 165
smooth_part()  (in module sage.arith.misc), 143
some_elements()  (sage.rings.rational_field.RationalField method), 165
sort_complex_numbers_for_display()  (in module sage.arith.misc), 143
sqrt()      (sage.rings.integer.Integer method), 55
sqrt()      (sage.rings.rational.Rational method), 188
sqrtrem()      (sage.rings.integer.Integer method), 56
squarefree_divisors()  (in module sage.arith.misc), 144
squarefree_part()  (sage.rings.integer.Integer method), 56
squarefree_part()  (sage.rings.rational.Rational method), 189
str()      (sage.rings.integer.Integer method), 57
str()      (sage.rings.rational.Rational method), 190
subfactorial()  (in module sage.arith.misc), 144
sum_of_k_squares()  (in module sage.arith.misc), 145
support()      (sage.rings.integer.Integer method), 58
support()      (sage.rings.rational.Rational method), 190

T
test_bit()      (sage.rings.integer.Integer method), 58
three_squares()  (in module sage.arith.misc), 146
three_squares_pyx()  (in module sage.rings.sum_of_squares), 73
to_bytes()      (sage.rings.integer.Integer method), 58
trace()      (sage.rings.rational.Rational method), 190
trailing_zero_bits()  (sage.rings.integer.Integer method), 59
trial_division()  (in module sage.arith.misc), 147
trial_division()  (sage.rings.integer.Integer method), 59
trunc()      (sage.rings.integer.Integer method), 60
trunc()      (sage.rings.rational.Rational method), 191
two_squares()  (in module sage.arith.misc), 148
two_squares_pyx()  (in module sage.rings.sum_of_squares), 74

V
val_unit()      (sage.rings.integer.Integer method), 60
val_unit()      (sage.rings.rational.Rational method), 191
valuation()      (in module sage.arith.misc), 148
valuation()      (sage.rings.integer_ring.IntegerRing_class method), 11
valuation()      (sage.rings.integer.Integer method), 61

```

valuation() (*sage.rings.rational_field.RationalField method*), 166
valuation() (*sage.rings.rational.Rational method*), 191
verify_bernoulli_mod_p() (*in module sage.rings.bernoulli_mod_p*), 66

X

XGCD () (*in module sage.arith.misc*), 88
xgcd () (*in module sage.arith.misc*), 149
xgcd () (*sage.rings.integer.Integer method*), 61
xgcd_int () (*sage.rings.fast_arith.arith_int method*), 71
xkcd () (*in module sage.arith.misc*), 151
xlcm () (*in module sage.arith.misc*), 152

Z

z_to_Q (*class in sage.rings.rational*), 192
zeta() (*sage.rings.integer_ring.IntegerRing_class method*), 11
zeta() (*sage.rings.rational_field.RationalField method*), 166